Go



- Clock and Timing ICs
- Crystal and Crystal Oscillator
- Display Interface
- Home Appliance
- Interface Logic
- PCle Switch
- PCle / PCl Bridges
- Power Management IC
- ReDriver / Repeater / Signal Conditioners
- Signal Switch IC / Multiplexers
- UART
- Video Decoder
- Part Cross Reference
- Protocols
 - Bluetooth / WiFi
- DDR Technology
- Type C
- Ethernet
- Fibre Channel
- InfiniBand
- LVDS
- PCI and PCIe Technology
- SATA / SAS Technology
- USB Technology
- Video/Display
- XAUI
- SRIO
- Applications
- Automotive
- Computer and Peripheral
- Digital Media
- Embedded Systems
- Networking and Telecom
- Server and Storage
- Ultra Mobility & Wireless
- Application Notes
- Support
 - Quality
 - Packaging
 - Contact Support
- FAQ
- Technical Articles
- Collateral & Downloads
- Application Notes
- Company
- About Pericom
- Investors
- Newsroom
- CareersPericom Saronix-eCera (PSE)
- Contact
 - Contact Sales
 - Driving Directions
 - Contact Pericom
 - Contact Support

Home » Products » PCle Switch

« Back to PCle Switch

PI7C9X442SLB

PCI Express-to-USB 2.0 Swidge $^{\text{TM}}$ (PCIe Packet Switch + USB 2.0 Host Controller)

» Get Datasheet

SPECS & TECH DOCS

PRODUCT OPTIONS	
PCNS	
FAQS	
Product Specifications Product Specs	
Ports	3
Lanes	3
Power	0.55
Latency	150
Related	
Applications	
Blade Server, Infotainment, Notebook, Tablet PC, Desktop PC, Rack Server, Set-top Box, Wireless Access, Base station, Industrial PC, Monitors, Storage Array, Broadband Access, Docking, Medical Device, HDD, Multi-Function Printer, GPS, Security	

Protocols
USB 2.0, PCI Express

Quality & Reliability

Quality Documentation

℃ Contact Sales

Sign In

Sign in to see your update request status or to request updates about this part.

Copyright © 2015 Pericom Senticonductor Corporation
Terms & Conditions | Privacy

Follow Us:

| Image: Conditions | Privacy | Image: Conditions |