

\$ 4.99 - Standard Global Shipping

[Home](#) > [Products](#) > [RF & Wireless Control](#) > [RF Diode](#) > [RF Mixer and Detector Schottky Diode](#) > [BAT62-02V](#)

BAT62-02V

- Overview**
- Documents
- Order
- Simulation
- Support

Description:

Silicon Schottky Diodes

Summary of Features:

- Low barrier diode for detectors up to GHz frequencies
- Pb-free (RoHS compliant) package

Target Applications:


- Wireless Communications
- Satellite Receivers
- Base Stations
- High Speed Data Networks
- RFID

Buy online

Designers who used this product also designed with


In order to optimize your browsing experience Infineon uses cookies. You agree to the usage of cookies when you continue browsing this site. For more information regarding cookies and the processing of your personal data please read our [Privacy Policy](#).

OK




BAT60B |

Medium Power IF max \geq 500mA




BGA420 |

General Purpose LNAs




SPB08P06P G |

12V-250V P-Channel Power MOSFET



BSP75N |

Automotive Smart Low-Side Switch | HITFET™



BFP420F |

Low-Noise Si Transistors up to 5 GHz

Documents

+ Expand all

+ [Application Notes](#)

+ [Product Qualification Report](#)

+ [Material Content Sheet](#) Info

Order

Sales Product Name	BAT62-02V
OPN	BAT6202VH6327XTSA1
Product Status	active and preferred
Package name	SC79
Order online	
Completely lead free	yes
Halogen free	yes
RoHS compliant	yes
Packing Size	3000
Packing Type	TAPE & REEL
Moisture Level	1
Moisture Packing	NON DRY

Simulation

+ [Simulation Models](#)

Support

Live Chat Online
在线支持



Technical Assistance Center
技术支持中心 (TAC)



Call us Toll Free
免费热线联系我们



+ [Find an answer to your question](#)

+ [Technical Assistance Center \(TAC\)](#)

+ [Support forum](#)

Follow us