

BCP69; BC869; BC69PA

20 V, 2 A PNP medium power transistors

Rev. 7 — 12 October 2011

Product data sheet

1. Product profile

1.1 General description

PNP medium power transistor series in Surface-Mounted Device (SMD) plastic packages.

Table 1. Product overview

| Type number ^[1] | Package | | | NPN complement |
|----------------------------|----------|-------|--------|----------------|
| | Nexperia | JEITA | JEDEC | |
| BCP69 | SOT223 | SC-73 | - | BCP68 |
| BC869 | SOT89 | SC-62 | TO-243 | BC868 |
| BC69PA | SOT1061 | - | - | BC68PA |

[1] Valid for all available selection groups.

1.2 Features and benefits

- High current
- Three current gain selections
- High power dissipation capability
- Exposed heatsink for excellent thermal and electrical conductivity (SOT89, SOT1061)
- Leadless very small SMD plastic package with medium power capability (SOT1061)
- AEC-Q101 qualified

1.3 Applications

- Linear voltage regulators
- High-side switches
- Battery-driven devices
- Power management
- MOSFET drivers
- Amplifiers

1.4 Quick reference data

Table 2. Quick reference data

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|-----------|---------------------------|-------------------------------|-----|-----|-----|------|
| V_{CEO} | collector-emitter voltage | open base | - | - | -20 | V |
| I_C | collector current | | - | - | -2 | A |
| I_{CM} | peak collector current | single pulse; $t_p \leq 1$ ms | - | - | -3 | A |

nexperia







Table 2. Quick reference data ...continued

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|----------|------------------------|---|---------|-----|-----|------|
| h_{FE} | DC current gain | $V_{CE} = -1\text{ V};$ $I_C = -500\text{ mA}$ | [1] 85 | - | 375 | |
| | h_{FE} selection -16 | $V_{CE} = -1\text{ V};$ $I_C = -500\text{ mA}$ | [1] 100 | - | 250 | |
| | h_{FE} selection -25 | $V_{CE} = -1\text{ V};$ $I_C = -500\text{ mA}$ | [1] 160 | - | 375 | |

[1] Pulse test: $t_p \leq 300\ \mu\text{s}; \delta = 0.02$.

2. Pinning information

Table 3. Pinning

| Pin | Description | Simplified outline | Graphic symbol |
|----------------|-------------|--|--|
| SOT223 | | | |
| 1 | base |  |  sym028 |
| 2 | collector | | |
| 3 | emitter | | |
| 4 | collector | | |
| SOT89 | | | |
| 1 | emitter |  |  006aaa231 |
| 2 | collector | | |
| 3 | base | | |
| SOT1061 | | | |
| 1 | base |  Transparent top view |  sym013 |
| 2 | emitter | | |
| 3 | collector | | |

3. Ordering information

Table 4. Ordering information

| Type number ^[1] | Package | | |
|----------------------------|---------|--|---------|
| | Name | Description | Version |
| BCP69 | SC-73 | plastic surface-mounted package with increased heatsink; 4 leads | SOT223 |
| BC869 | SC-62 | plastic surface-mounted package; exposed die pad for good heat transfer; 3 leads | SOT89 |
| BC69PA | HUSON3 | plastic thermal enhanced ultra thin small outline package; no leads; 3 terminals; body 2 × 2 × 0.65 mm | SOT1061 |

[1] Valid for all available selection groups.

4. Marking

Table 5. Marking codes

| Type number | Marking code |
|-------------|--------------|
| BCP69 | BCP69 |
| BCP69-16 | BCP69/16 |
| BCP69-25 | BCP69/25 |
| BC869 | CEC |
| BC869-16 | CGC |
| BC869-25 | CHC |
| BC69PA | B3 |
| BC69-16PA | BM |
| BC69-25PA | BN |

5. Limiting values

Table 6. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol | Parameter | Conditions | Min | Max | Unit | | | | | | |
|-----------|---------------------------|----------------------------------|-----|------|------|-----------|----------------------|---|------|------|----|
| V_{CBO} | collector-base voltage | open emitter | - | -32 | V | | | | | | |
| V_{CEO} | collector-emitter voltage | open base | - | -20 | V | | | | | | |
| V_{EBO} | emitter-base voltage | open collector | - | -5 | V | | | | | | |
| I_C | collector current | | - | -2 | A | | | | | | |
| I_{CM} | peak collector current | single pulse; $t_p \leq 1$ ms | - | -3 | A | | | | | | |
| I_B | base current | | - | -0.4 | A | | | | | | |
| I_{BM} | peak base current | single pulse; $t_p \leq 1$ ms | - | -0.4 | A | | | | | | |
| P_{tot} | total power dissipation | $T_{amb} \leq 25$ °C | | | | | | | | | |
| | | | | | | BCP69 | [1] | - | 0.65 | W | |
| | | | | | | | [2] | - | 1.00 | W | |
| | | | | | | | [3] | - | 1.35 | W | |
| | | | | | | BC869 | [1] | - | 0.50 | W | |
| | | | | | | | [2] | - | 0.95 | W | |
| | | | | | | | [3] | - | 1.35 | W | |
| | | | | | | BC69PA | [1] | - | 0.42 | W | |
| | | | | | | | [2] | - | 0.83 | W | |
| | | | | | | | [3] | - | 1.10 | W | |
| | | | | | | | [4] | - | 0.81 | W | |
| | | | | | | | [5] | - | 1.65 | W | |
| | | | | | | T_j | junction temperature | | - | 150 | °C |
| | | | | | | T_{amb} | ambient temperature | | -55 | +150 | °C |
| | | | | | | T_{stg} | storage temperature | | -65 | +150 | °C |


[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1 cm².

[3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6 cm².


[4] Device mounted on an FR4 PCB, 4-layer copper, tin-plated and standard footprint.

[5] Device mounted on an FR4 PCB, 4-layer copper, tin-plated, mounting pad for collector 1 cm².




- (1) FR4 PCB, mounting pad for collector 6 cm²
- (2) FR4 PCB, mounting pad for collector 1 cm²
- (3) FR4 PCB, standard footprint

Fig 1. Power derating curves SOT223



- (1) FR4 PCB, mounting pad for collector 6 cm²
- (2) FR4 PCB, mounting pad for collector 1 cm²
- (3) FR4 PCB, standard footprint

Fig 2. Power derating curves SOT89



- (1) FR4 PCB, 4-layer copper, mounting pad for collector 1 cm²
- (2) FR4 PCB, single-sided copper, mounting pad for collector 6 cm²
- (3) FR4 PCB, single-sided copper, mounting pad for collector 1 cm²
- (4) FR4 PCB, 4-layer copper, standard footprint
- (5) FR4 PCB, single-sided copper, standard footprint

Fig 3. Power derating curves SOT1061

6. Thermal characteristics

Table 7. Thermal characteristics

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit | | |
|---------------|---|--|--------|-----|-----|------|-----|-----|
| $R_{th(j-a)}$ | thermal resistance from junction to ambient | in free air | | | | | | |
| | | | BCP69 | [1] | - | - | 192 | K/W |
| | | | | [2] | - | - | 125 | K/W |
| | | | | [3] | - | - | 93 | K/W |
| | | | BC869 | [1] | - | - | 250 | K/W |
| | | | | [2] | - | - | 132 | K/W |
| | | | | [3] | - | - | 93 | K/W |
| | | | BC69PA | [1] | - | - | 298 | K/W |
| | | | | [2] | - | - | 151 | K/W |
| | [3] | - | | - | 114 | K/W | | |
| | [4] | - | | - | 154 | K/W | | |
| | [5] | - | | - | 76 | K/W | | |
| | $R_{th(j-sp)}$ | thermal resistance from junction to solder point | | | | | | |
| | | | BCP69 | - | - | 16 | K/W | |
| | | | BC869 | - | - | 16 | K/W | |
| BC69PA | | | - | - | 20 | K/W | | |

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1 cm².

[3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6 cm².

[4] Device mounted on an FR4 PCB, 4-layer copper, tin-plated and standard footprint.

[5] Device mounted on an FR4 PCB, 4-layer copper, tin-plated, mounting pad for collector 1 cm².




Fig 4. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT223; typical values






Fig 5. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT223; typical values




FR4 PCB, mounting pad for collector 6 cm²

Fig 6. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT223; typical values




FR4 PCB, standard footprint

Fig 7. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT89; typical values




FR4 PCB, mounting pad for collector 1 cm²

Fig 8. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT89; typical values




FR4 PCB, mounting pad for collector 6 cm²

Fig 9. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT89; typical values




FR4 PCB, single-sided copper, standard footprint

Fig 10. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT1061; typical values




FR4 PCB, single-sided copper, mounting pad for collector 1 cm^2

Fig 11. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT1061; typical values




FR4 PCB, single-sided copper, mounting pad for collector 6 cm²

Fig 12. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT1061; typical values



FR4 PCB, 4-layer copper, standard footprint

Fig 13. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT1061; typical values



FR4 PCB, 4-layer copper, mounting pad for collector 1 cm²

Fig 14. Transient thermal impedance from junction to ambient as a function of pulse duration for SOT1061; typical values


7. Characteristics

Table 8. Characteristics

$T_{amb} = 25\text{ °C}$ unless otherwise specified.


| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|------------------------|--------------------------------------|---|--------|-----|------|---------------|
| I_{CBO} | collector-base cut-off current | $V_{CB} = -25\text{ V}; I_E = 0\text{ A}$ | - | - | -100 | nA |
| | | $V_{CB} = -25\text{ V}; I_E = 0\text{ A}; T_j = 150\text{ °C}$ | - | - | -10 | μA |
| I_{EBO} | emitter-base cut-off current | $V_{EB} = -5\text{ V}; I_C = 0\text{ A}$ | - | - | -100 | nA |
| h_{FE} | DC current gain | $V_{CE} = -10\text{ V}$ | | | | |
| | | $I_C = -5\text{ mA}$ | 50 | - | - | |
| | DC current gain | $V_{CE} = -1\text{ V}$ | | | | |
| | | $I_C = -500\text{ mA}$ | [1] 85 | - | 375 | |
| | | $I_C = -1\text{ A}$ | [1] 60 | - | - | |
| | | $I_C = -2\text{ A}$ | [1] 40 | - | - | |
| | DC current gain | $V_{CE} = -1\text{ V}$ | | | | |
| h_{FE} selection -16 | $I_C = -500\text{ mA}$ | [1] 100 | - | 250 | | |
| h_{FE} selection -25 | $I_C = -500\text{ mA}$ | [1] 160 | - | 375 | | |
| V_{CEsat} | collector-emitter saturation voltage | $I_C = -1\text{ A}; I_B = -100\text{ mA}$ | [1] - | - | -0.5 | V |
| | | $I_C = -2\text{ A}; I_B = -200\text{ mA}$ | [1] - | - | -0.6 | V |
| V_{BE} | base-emitter voltage | $V_{CE} = -10\text{ V}; I_C = -5\text{ mA}$ | [1] - | - | -0.7 | V |
| | | $V_{CE} = -1\text{ V}; I_C = -1\text{ A}$ | [1] - | - | -1 | V |
| C_c | collector capacitance | $V_{CB} = -10\text{ V}; I_E = I_C = 0\text{ A}; f = 1\text{ MHz}$ | - | 28 | - | pF |
| f_T | transition frequency | $V_{CE} = -5\text{ V}; I_C = -50\text{ mA}; f = 100\text{ MHz}$ | 40 | 140 | - | MHz |

[1] Pulse test: $t_p \leq 300\text{ }\mu\text{s}$; $\delta = 0.02$.




$V_{CE} = -1\text{ V}$
 (1) $T_{amb} = 100\text{ °C}$
 (2) $T_{amb} = 25\text{ °C}$
 (3) $T_{amb} = -55\text{ °C}$

Fig 15. h_{FE} selection -16: DC current gain as a function of collector current; typical values




$T_{amb} = 25\text{ °C}$

Fig 16. h_{FE} selection -16: collector current as a function of collector-emitter voltage; typical values




$V_{CE} = -1\text{ V}$
 (1) $T_{amb} = -55\text{ °C}$
 (2) $T_{amb} = 25\text{ °C}$
 (3) $T_{amb} = 100\text{ °C}$

Fig 17. h_{FE} selection -16: base-emitter voltage as a function of collector current; typical values




$I_C/I_B = 10$
 (1) $T_{amb} = 100\text{ °C}$
 (2) $T_{amb} = 25\text{ °C}$
 (3) $T_{amb} = -55\text{ °C}$

Fig 18. h_{FE} selection -16: collector-emitter saturation voltage as a function of collector current; typical values




$V_{CE} = -1\text{ V}$
 (1) $T_{amb} = 100\text{ °C}$
 (2) $T_{amb} = 25\text{ °C}$
 (3) $T_{amb} = -55\text{ °C}$

Fig 19. h_{FE} selection -25: DC current gain as a function of collector current; typical values




$T_{amb} = 25\text{ °C}$

Fig 20. h_{FE} selection -25: collector current as a function of collector-emitter voltage; typical values



$V_{CE} = -1\text{ V}$
 (1) $T_{amb} = -55\text{ °C}$
 (2) $T_{amb} = 25\text{ °C}$
 (3) $T_{amb} = 100\text{ °C}$

Fig 21. h_{FE} selection -25: base-emitter voltage as a function of collector current; typical values



$I_C/I_B = 10$
 (1) $T_{amb} = 100\text{ °C}$
 (2) $T_{amb} = 25\text{ °C}$
 (3) $T_{amb} = -55\text{ °C}$

Fig 22. h_{FE} selection -25: collector-emitter saturation voltage as a function of collector current; typical values

8. Test information

8.1 Quality information

This product has been qualified in accordance with the Automotive Electronics Council (AEC) standard *Q101 - Stress test qualification for discrete semiconductors*, and is suitable for use in automotive applications.

9. Package outline




Fig 23. Package outline SOT223 (SC-73)




Fig 24. Package outline SOT89 (SC-62/TO-243)




Fig 25. Package outline SOT1061 (HUSON3)

10. Packing information

Table 9. Packing methods

The indicated -xxx are the last three digits of the 12NC ordering code.^[1]

| Type number ^[2] | Package | Description | Packing quantity | | |
|----------------------------|---------|--|------------------|------|------|
| | | | 1000 | 3000 | 4000 |
| BCP69 | SOT223 | 8 mm pitch, 12 mm tape and reel | -115 | - | -135 |
| BC869 | SOT89 | 8 mm pitch, 12 mm tape and reel; T1 ^[3] | -115 | - | -135 |
| | | 8 mm pitch, 12 mm tape and reel; T3 ^[4] | -146 | - | - |
| BC69PA | SOT1061 | 4 mm pitch, 8 mm tape and reel | - | -115 | - |

[1] For further information and the availability of packing methods, see [Section 14](#).

[2] Valid for all available selection groups.

[3] T1: normal taping

[4] T3: 90° rotated taping

11. Soldering




Fig 26. Reflow soldering footprint SOT223 (SC-73)




Fig 27. Wave soldering footprint SOT223 (SC-73)

12. Revision history

Table 10. Revision history

| Document ID | Release date | Data sheet status | Change notice | Supersedes |
|------------------------|--------------|-----------------------|---------------|---|
| BCP69_BC869_BC69PA v.7 | 20111012 | Product data sheet | - | BC869_6 BCP69_6 |
| Modifications: | | | | <ul style="list-style-type: none"> • The format of this document has been redesigned to comply with the new identity guidelines of NXP Semiconductors. • Legal texts have been adapted to the new company name where appropriate. • Type number BC69PA added • Type number BCP69-16/DG and BCP69-16/IN removed • Section 1 “Product profile”: updated • Section 2 “Pinning information”: updated • Section 3 “Ordering information”: updated • Section 4 “Marking”: updated • Section 10 “Packing information”: updated • Table 6, 7 and 8: updated according to latest measurements • Figure 1, 15 to 18 updated • Figure 2 to 14, 24 to 25, 28 to 30: added |
| BC869_6 | 20041108 | Product data sheet | - | BC869_5 |
| BC869_5 | 20031202 | Product specification | - | BC869_4 |
| BC869_4 | 19990408 | Product specification | - | BC869_3 |
| BC869_3 | 19980716 | Product specification | - | BC869_CNV_2 |
| BC869_CNV_2 | 19970401 | Product specification | - | - |
| BCP69_6 | 20081202 | Product data sheet | - | BCP69_5 |
| BCP69_5 | 20031125 | Product specification | - | BCP69_4 |
| BCP69_4 | 20021115 | Product specification | - | BCP69_3 |
| BCP69_3 | 19990408 | Product specification | - | BCP69_CNV_2 |
| BCP69_CNV_2 | 19970312 | Product specification | - | - |

13. Legal information

13.1 Data sheet status

| Document status ^{[1][2]} | Product status ^[3] | Definition |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nexperia.com>.

13.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

13.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or

malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia accepts no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

13.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

14. Contact information

For more information, please visit: <http://www.nexperia.com>

For sales office addresses, please send an email to: salesaddresses@nexperia.com

15. Contents

| | | |
|-----------|--|-----------|
| 1 | Product profile | 1 |
| 1.1 | General description | 1 |
| 1.2 | Features and benefits | 1 |
| 1.3 | Applications | 1 |
| 1.4 | Quick reference data | 1 |
| 2 | Pinning information | 2 |
| 3 | Ordering information | 3 |
| 4 | Marking | 3 |
| 5 | Limiting values | 4 |
| 6 | Thermal characteristics | 6 |
| 7 | Characteristics | 13 |
| 8 | Test information | 16 |
| 8.1 | Quality information | 16 |
| 9 | Package outline | 16 |
| 10 | Packing information | 17 |
| 11 | Soldering | 18 |
| 12 | Revision history | 21 |
| 13 | Legal information | 22 |
| 13.1 | Data sheet status | 22 |
| 13.2 | Definitions | 22 |
| 13.3 | Disclaimers | 22 |
| 13.4 | Trademarks | 23 |
| 14 | Contact information | 23 |
| 15 | Contents | 24 |