


Features

- Ideal for Printed Circuit Board
- Surge Overload Rating of 125A Peak
- Low forward Voltage Drop
- The Plastic Material Carries U/L Recognition 94V-0
- **Lead Free Finish, RoHS Compliant (Date Code 0514+) (Note 1)**

Mechanical Data

- Case: PB-6, Plastic
- Terminals: Leads Solderable per MIL-STD-202, Method 208
- Polarity: Symbols Marked on Body
- Weight: 4.56 grams



Maximum Ratings and Electrical Characteristics

Ratings at 25° C ambient temperature unless otherwise specified.
Single phase, 60Hz, resistive or inductive load.

Characteristic	Symbol	PB605	PB61	PB62	PB64	PB66	PB68	PB610	Unit
Maximum Recurrent Peak Reverse Voltage	VRRM	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Input Voltage	V _{RSM}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Output Current @ T _{HS} (Heatsink Temp) = 50°C	I <sub(av)< sub=""></sub(av)<>	6.0							A
Peak Forward Surge Current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	125							A
Maximum Forward Voltage Drop per element at 3.0A _{dc}	V _F	1.1							V
Maximum dc Reverse Current at rated dc Blocking Voltage per element @ T _A = 25°C @ T _A = 100°C	I _R	10 1							μA mA
Typical Thermal Resistance	R _{θJC}	8							°C/W
Operating and Storage Temperature Range	T _J , T _{STG}	-65 to +150							°C

Notes: 1. EC Directive 2002/95/EC (RoHS) revision 13.2.2003. Glass and High Temperature Solder Exemptions Applied where applicable, see *EU Directive Annex Notes 5 and 7.*

OBSOLETE - PART DISCONTINUED

OBSOLETE - PART DISCONTINUED




Fig. 1, Derating Curve for Output Rectified Current




Fig. 2, Typical Forward Characteristics




Fig. 3, Maximum Forward Surge Current




Fig. 4, Typical Reverse Characteristics

Ordering Information (Note 2)

Device	Packaging	Shipping
PB605	PB-6	200 Bulk
PB61	PB-6	200 Bulk
PB62	PB-6	200 Bulk
PB64	PB-6	200 Bulk
PB66	PB-6	200 Bulk
PB68	PB-6	200 Bulk
PB610	PB-6	200 Bulk

Notes: 2. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

- A. Life support devices or systems are devices or systems which:
 - 1. are intended to implant into the body, or
 - 2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.
- B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2016, Diodes Incorporated

www.diodes.com

OBSOLETE - PART DISCONTINUED