


## Features

- Dual N-Channel MOSFET
- Low On-Resistance
- Very Low Gate Threshold Voltage, 1.0V Max
- Low Input Capacitance
- Fast Switching Speed
- Low Input/Output Leakage
- Ultra-Small Surface Mount Package
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **ESD Protected up to 2kV**
- **Qualified to AEC-Q101 Standards for High Reliability**




ESD protected up to 2kV




SOT563  
Top View

## Mechanical Data

- Case: SOT563
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminal Connections: See Diagram
- Terminals: Finish – Matte Tin Annealed over Copper Leadframe. Solderable per MIL-STD-202, Method 208 (E3)
- Weight: 0.006 grams (Approximate)



DMN5L06VK



DMN5L06VAK  
DMN5010VAK


## Ordering Information (Note 4)

Part Number	Case	Packaging
DMN5L06VK-7	SOT563	3,000/Tape & Reel
DMN5L06VK-7A	SOT563	3,000/Tape & Reel
DMN5L06VK-13	SOT563	10,000/Tape & Reel
DMN5L06VK-13A	SOT563	10,000/Tape & Reel
DMN5L06VAK-7	SOT563	3,000/Tape & Reel
DMN5L06VAK-7A	SOT563	3,000/Tape & Reel
DMN5L06VAK-13	SOT563	10,000/Tape & Reel
DMN5L06VAK-13A	SOT563	10,000/Tape & Reel
DMN5010VAK-7	SOT563	3,000/Tape & Reel
DMN5010VAK-7A	SOT563	3,000/Tape & Reel
DMN5010VAK-13	SOT563	10,000/Tape & Reel
DMN5010VAK-13A	SOT563	10,000/Tape & Reel


- Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
  2. See [http://www.diodes.com/quality/lead\\_free.html](http://www.diodes.com/quality/lead_free.html) for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
  3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
  4. For packaging details, go to our website at <http://www.diodes.com/products/packages.html>.

**Marking Information** (Note 5 & 6)

**DMN5L06VK-7/-13 (Note 5)**




**DMN5L06VK-7A/-13A (Note 6)**




KAB= DMN5L06VK Product Type  
Marking Code  
YM= Date Code Marking  
Y = Year (ex: E = 2017)  
M = Month (ex: 9 = September)

**DMN5L06VAK-7/-13 (Note 5)**  
**DMN5010VAK-7/-13 (Note 5)**



**DMN5L06VAK-7A/-13A (Note 6)**  
**DMN5010VAK-7A/-13A (Note 6)**



xxx = Product Type Marking Code:  
KAE or KAE or KAC  
YM= Date Code Marking  
Y = Year (ex: E = 2017)  
M = Month (ex: 9 = September)

Date Code Key

<b>Year</b>	2006	~	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025
<b>Code</b>	T	~	D	E	F	G	H	I	J	K	L	M
<b>Month</b>	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Code</b>	1	2	3	4	5	6	7	8	9	O	N	D

Notes: 5. Package is non-polarized. Parts may be on reel in orientation illustrated, 180° rotated, or mixed (both ways).  
6. Part number with suffix 7A and 13A designates devices marked with a Pin 1 indicator. There is no other difference between both devices.

**Maximum Ratings** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Unit
Drain Source Voltage		V <sub>DSS</sub>	50	V
Drain-Gate Voltage R <sub>GS</sub> ≤ 1.0MΩ		V <sub>DGR</sub>	50	V
Gate-Source Voltage	Continuous	V <sub>GSS</sub>	±20	V
	Pulsed		±40	
Drain Current (Note 7)	Continuous	I <sub>D</sub>	280	mA
	Pulsed	I <sub>DM</sub>	1.5	A

**Thermal Characteristics**

Characteristic	Symbol	Value	Unit
Total Power Dissipation (Note 7)	P <sub>D</sub>	250	mW
Thermal Resistance, Junction to Ambient (Note 7)	R <sub>θJA</sub>	500	°C/W
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to +150	°C

**Electrical Characteristics** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition	
<b>OFF CHARACTERISTICS</b> (Note 8)							
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	50	—	—	V	V <sub>GS</sub> = 0V, I <sub>D</sub> = 10μA	
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	—	—	60	nA	@ T <sub>C</sub> = +25°C V <sub>DS</sub> = 50V, V <sub>GS</sub> = 0V	
Gate-Body Leakage	I <sub>GSS</sub>	—	—	1	μA	V <sub>GS</sub> = ±12V, V <sub>DS</sub> = 0V	
				500	nA	V <sub>GS</sub> = ±10V, V <sub>DS</sub> = 0V	
				50	nA	V <sub>GS</sub> = ±5V, V <sub>DS</sub> = 0V	
<b>ON CHARACTERISTICS</b> (Note 8)							
Gate Threshold Voltage	V <sub>GS(TH)</sub>	@T <sub>J</sub> = +25°C	0.49	—	1.0	V	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA
		@T <sub>J</sub> = +0°C to +85°C (Note 9)	0.30	—	1.2		
Static Drain-Source On-Resistance	R <sub>DS(ON)</sub>	—	—	3.0	Ω	V <sub>GS</sub> = 1.8V, I <sub>D</sub> = 50mA	
		—	—	2.5		V <sub>GS</sub> = 2.5V, I <sub>D</sub> = 50mA	
		—	—	2.0		V <sub>GS</sub> = 5.0V, I <sub>D</sub> = 50mA	
On-State Drain Current	I <sub>D(ON)</sub>	0.5	1.4	—	A	V <sub>GS</sub> = 10V, V <sub>DS</sub> = 7.5V	
Forward Transconductance	Y <sub>fs</sub>	200	—	—	mS	V <sub>DS</sub> = 10V, I <sub>D</sub> = 0.2A	
Source-Drain Diode Forward Voltage	V <sub>SD</sub>	0.5	—	1.4	V	V <sub>GS</sub> = 0V, I <sub>S</sub> = 115mA	
<b>DYNAMIC CHARACTERISTICS</b> (Note 9)							
Input Capacitance	C <sub>iss</sub>	—	—	50	pF	V <sub>DS</sub> = 25V, V <sub>GS</sub> = 0V f = 1.0MHz	
Output Capacitance	C <sub>oss</sub>	—	—	25	pF		
Reverse Transfer Capacitance	C <sub>rss</sub>	—	—	5.0	pF		

- Notes:
- Device mounted on FR-4 substrate PC board, 2oz copper, with minimum recommended pad layout.
  - Short duration pulse test used to minimize self-heating effect.
  - Guaranteed by design. Not subject to product testing.




Fig. 1 Typical Output Characteristics




Fig. 2 Typical Transfer Characteristics




Fig. 3 Gate Threshold Voltage vs. Channel Temperature




Fig. 4 Static Drain-Source On-Resistance vs. Drain Current




Fig. 5 Static Drain-Source On-Resistance vs. Drain Current




Fig. 6 Static Drain-Source On-Resistance vs. Gate-Source Voltage




Fig. 7 Static Drain-Source On-State Resistance vs. Ambient Temperature




Fig. 8 Reverse Drain Current vs. Source-Drain Voltage




Fig. 9 Reverse Drain Current vs. Source-Drain Voltage




Fig. 10 Forward Transfer Admittance vs. Drain Current





Fig. 11 Derating Curve - Total

**Package Outline Dimensions**

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

**SOT563**




SOT563			
Dim	Min	Max	Typ
A	0.15	0.30	0.20
B	1.10	1.25	1.20
C	1.55	1.70	1.60
D	-	-	0.50
G	0.90	1.10	1.00
H	1.50	1.70	1.60
K	0.55	0.60	0.60
L	0.10	0.30	0.20
M	0.10	0.18	0.11
All Dimensions in mm			

**Suggested Pad Layout**

Please see <http://www.diodes.com/package-outlines.html> for the latest version.

**SOT563**



Dimensions	Value (in mm)
Z	2.2
G	1.2
X	0.375
Y	0.5
C1	1.7
C2	0.5

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2017, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)