


**GLASS PASSIVATED
SURFACE MOUNT BRIDGE RECTIFIERS**

**REVERSE VOLTAGE – 1000 Volts
FORWARD CURRENT – 1.5 Ampere**

GENERAL DESCRIPTION

Suitable for AC-to-DC bridge full wave rectification for SMPS, LED lighting, adapter, battery charger, home appliances, office equipment, and telecommunication applications.




FEATURES

- Rated at 1000V PRV
- Compact, thin profile package design
- Ideal for SMT manufacturing
- Reliable robust construction
- UL recognized file#E364304

MECHANICAL DATA

- Molding compound meets UL 94 V-0 flammability rating, Halogen-free, RoHS-compliant, and commercial grade
- Polarity indicator: As marked on body
- Marking : MB15MH
- Weight: 216 mg

Pin Assignment



Maximum Ratings & Thermal Characteristics @ T_A = 25°C unless otherwise specified

Characteristics	Symbol	Limit	Unit
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	1000	V
Maximum DC Blocking Voltage	V _{DC}	1000	V
Maximum Average Forward Rectified Current @T _c = 110 °C	I _(AV)	1.5	A
Peak Forward Surge Current 8.3ms single half sine-wave @T _J =25°C @T _J =125°C	I _{FSM}	70 56	A
Peak Forward Surge Current 1.0ms single half sine-wave @T _J =25°C @T _J =125°C	I _{FSM}	140 112	A
I ² t Rating for fusing (1ms < t < 8.3ms)	I ² t	20.33	A ² S
Operating and Storage Temperature Range	T _J , T _{STG}	-55 to +150	°C

Electrical Characteristics @ T_A = 25°C unless otherwise specified

Characteristics	Test Condition	Symbol	Min	Typ.	Max	Unit
Maximum Forward Voltage @T _J =25°C @T _J =125°C	IF = 0.75A	V _F	--	--- 0.77	1.02 ---	V
Maximum Forward Voltage @T _J =25°C @T _J =125°C	IF = 1.5A	V _F	--	--- 0.94	1.1 --	V
Maximum DC Reverse Current at Rated DC Blocking Voltage @T _J =25°C @T _J =125°C	VR = 1000V	I _R	--	--	5 500	µA
Typical junction capacitance per element	Note(1)	C _J	--	25	--	pF

Thermal Characteristics


Characteristics	Symbol	Min	Typ.	Max	Unit
Typical thermal resistance (Note 2)	R _{θJC}	--	10	--	°C/W
	R _{θJL}	--	15	--	
	R _{θJA}	--	50	--	

Note :

- (1) Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
- (2) Thermal Resistance test performed in accordance with JESD-51. Unit mounted on glass-epoxy substrate with 1oz/ft² 15x15 mm copper pad per pin.

REV. 1, Feb-2016, KBDA39

Package Dimension



MSBL			
Dim.	Min.	Typ.	Max.
A	1.30	1.40	1.50
A1	0.04	0.06	0.08
C	0.27	0.30	0.40
D	6.50	6.60	6.70
D1	0.95	1.10	1.25
E	7.20	7.30	7.40
E1	7.90	8.30	8.60
E2	0.95	1.10	1.25
L	0.80	1.00	1.05
b	0.95	1.00	1.15
e	5.00	5.10	5.20
K	2.90	3.00	3.10
All dimensions in millimeter			

RATING AND CHARACTERISTIC CURVES
MSB15MH



FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL JUNCTION CAPACITANCE




FIG.5- TYPICAL REVERSE CHARACTERISTICS






FIG.6- NON-REPETITIVE SURGE CURRENT




Packaging Information

DEVICE	Q'TY/REEL (PCS)	REEL DIA. (mm)	Liner (mm)	CARTON SIZE (mm)	Q'TY/CARTON (PCS)	MOQ
MSB15MH	2500	330	1300x200	355x245x350	25K	25K

Polar Units



Embossed Carrier Dimension



TAPE SIZE	D	E	PO	t (MAX)	A0	B0	K0
16	1.55+0.10 /-0.0	1.75+/- 0.10	4.0+/-0.10	0.4	7.0+/-0.1	8.4+/-0.1	1.7+/-0.1
	B1 (MAX)	B2 (MAX)	F	K (MAX)	P2	W	P
	8.2	1.5	5.5+/-0.1	2.2	2.0+/-0.05	16.0+/-0.30	12.0+/-0.1

Unit:mm

Typical IR Reflow Soldering Thermal Profile




Table 1- Reflow profile

Reflow condition	Sn-Pb assembly	Pb-free assembly
Average ramp-up rate (Liquidus Temperature (TL) to Peak)	3 °C/second max.	3 °C/second max.
Preheat		
--Temperature Min, Ts (Min)	100 °C	150 °C
--Temperature Max, Ts (Max)	150 °C	200 °C
--Time (min to max, ts)	60-120 seconds	60-180 seconds
Ts(max) to TL		3 °C/second max.
- Ramp-up Rate		
Time maintained above:		
--Temperature(TL)	183 °C	217 °C
--Time(tL)	60-150 seconds	60-150 seconds
Peak Temperature (Tp)	240 +0/-5 °C	260 +0/-5 °C
Time within 5 °C of actual Peak Temperature(tp)	10-30 seconds	20-40 seconds
Ramp-down Rate	6 °C/second max.	6 °C/second max.
Time 25 °C to Peak Temperature.	6 minutes max.	8 minutes max.

Note: All temperatures refer to topside of the package, measured on the package body surface

Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.