

**SURFACE MOUNT
SUPER FAST RECTIFIERS**


REVERSE VOLTAGE - 600 Volts
FORWARD CURRENT - 3.0 Amperes

FEATURES

- Glass passivated chip
- Super fast switching for high efficiency
- For surface mounted applications
- Low forward voltage drop and high current capability
- Low reverse leakage current

MECHANICAL DATA

- Case: Molded plastic
- Case Material: Molding compound, UL Flammability classification 94V-0, (No Br. Sb. Cl.) "Halogen-free".
- Polarity: Color band denotes cathode
- Weight: 0.003 ounces, 0.093 grams
- Marking: U3JB



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS
Ratings at 25°C ambient temperature unless otherwise specified.

CHARACTERISTICS	SYMBOL	MURS360B	UNIT
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	600	V
Maximum DC Blocking Voltage	VDC	600	A
Maximum Average Forward Rectified Current @ $T_C=130^{\circ}C$	I_{AV}	3.0	A
Peak Forward Surge 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	100	A
Maximum Forward Voltage at 3.0A DC	V_F	1.25	V
Maximum DC Reverse Current @ $T_j=25^{\circ}C$ at Rated DC Blocking Voltage @ $T_j=150^{\circ}C$	I_R	3.0 150	μA
Maximum Reverse Recovery time ($I_F=0.5A$, $I_R=1.0A$, $I_R=0.25A$)	t_{rr}	50	ns
Single pulse avalanche energy @15mH	E_{AS}	10.8	mJ
Typical Junction Capacitance (Note 1)	C_j	45	pF
Typical Thermal Resistance (Note 2, 3)	$R_{\theta JC}$	12	$^{\circ}C/W$
	$R_{\theta JL}$	26	
	$R_{\theta JA}$	47	
Operating Junction Temperature Range	T_j	-55 to +175	$^{\circ}C$
Storage Temperature Range	T_{STG}	-55 to +175	$^{\circ}C$

Note: (1) Measured at 1.0MHz and applied reverse voltage of 4.0V DC...
(2) Thermal Resistance Junction to Case, Lead and Ambient
(3) Unit mounted on glass epoxy substrate 1oz/ft 12 mm x 12 mm copper pad.

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3- TYPICAL JUNCTION CAPACITANCE




FIG.4- TYPICAL FORWARD CHARACTERISTICS





FIG.5- TYPICAL REVERSE CHARACTERISTICS



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.