

**SURFACE MOUNT  
ULTRA FAST RECTIFIER**


**REVERSE VOLTAGE – 50 to 400 Volts**  
**FORWARD CURRENT – 1.0 Amperes**

**FEATURES**

- Glass passivated chip
- Ultra fast switching for high efficiency
- Low forward voltage drop and high current capability
- Low reverse leakage current

**MECHANICAL DATA**

- Case : Molded plastic
- Case Material: "Green" Molding compound, UL flammability classification 94V- 0,"Halogen-free"
- Polarity : Indicated by cathode band
- Weight: 0.002 ounces , 0.069 grams (Approximate)



**SMA**

SMA		
DIM	MIN	MAX
A	4.06	4.57
B	2.29	2.92
C	1.27	1.63
D	0.15	0.31
E	4.83	5.59
F	0.05	0.20
G	2.01	2.40
H	0.76	1.52
All Dimensions in millimeter		

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.

**ABSOLUTE RATINGS**

PARAMETER	SYMBOL	US1A	US1B	US1D	US1G	UNIT
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	V
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	V
Maximum DC Blocking voltage	$V_{DC}$	50	100	200	400	V
Maximum Average rectified forward current	@ $T_L=110^\circ C$	1.0				A
Peak forward surge single half sine-wave	@ $t_p=8.3ms$	30				A
Operating and Storage temperature range	$T_J, T_{STG}$	-55 ~ +150				°C

**STATIC ELECTRICAL CHARACTERISTICS**

PARAMETER	TEST CONDITION	SYMBOL	MAX		UNIT
Forward voltage (Note 1)	$I_F=1A, T_J=25^\circ C$	$V_F$	1.0	1.3	V
Reverse leakage current at Rated DC blocking voltage	$T_J=25^\circ C, T_J=100^\circ C$	$I_R$	5.0	100	uA
Typical junction capacitance(Note 2)		$C_j$	20		pF

**THERMAL PERFORMANCE**

PARAMETER	SYMBOL	TYP	UNIT
Typical thermal resistance(Note 3)	$R_{thJA}$	60	°C/W
	$R_{thJL}$	22	
	$R_{thJC}$	18	

**DYNAMIC ELECTRICAL CHARACTERISTICS**

PARAMETER	SYMBOL	MAX	UNIT
Reverse recovery time	$I_F=0.5A, I_{rr}=0.25A, I_R=1.0A$	50	nS

**Note :**


- (1) 300us pulse with, 2% duty cycle
- (2) Measured at 1.0MHz and reverse voltage of 4.0V DC.
- (3) Thermal resistance junction to Ambient, Lead and Case

REV.-11, Oct-2019, KSFA01


# RATING AND CHARACTERISTIC CURVES US1A thru US1G




**FIG.1- FORWARD CURRENT DERATING CURVE**




**FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT**




**FIG.3- TYPICAL FORWARD CHARACTERISTICS**



**FIG.4- TYPICAL JUNCTION CAPACITANCE**



**FIG.5- TYPICAL REVERSE CHARACTERISTICS**



## **Important Notice and Disclaimer**

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.