

SCHOTTKY BARRIER RECTIFIER

REVERSE VOLTAGE – 100 Volts
FORWARD CURRENT – 30 Amperes


FEATURES

- Metal of silicon rectifier, majority carrier conduction
- Guard ring for transient protection
- Low power loss, high efficiency
- Low leakage current
- High current capability, low V_F
- High surge capacity

MECHANICAL DATA

- Case :TO-220AB molded plastic
- Case Material: "Green" molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl.) "Halogen-free"
- Polarity : As marked on the body
- Wight : 0.072 ounces, 2.0275grams (Approximate)
- Mounting position : Any
- Marking : MBR30100CT
- Lead free finish, RoHS compliant
- Max. mounting torque=0.5N.m(5.1Kgf.cm)

TO-220AB



TO-220AB		
DIM	MIN	MAX
A	14.22	15.88
B	9.65	10.67
C	2.54	3.43
D	5.84	6.86
E	8.26	9.28
F	--	6.35
G	12.70	14.73
H	2.29	2.79
I	0.51	1.14
J	0.30	0.64
K	3.53φ	4.09φ
L	3.56	4.83
M	1.14	1.40
N	2.03	2.92
O	1.14	1.70

All dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

ABSOLUTE RATINGS

PARAMETER	SYMBOL	VALUE	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	100	V
Maximum RMS Voltage	V_{RMS}	70	
Maximum DC blocking voltage	V_{DC}	100	V
Maximum Average rectified output current	$I_{(AV)}$	30	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load.	I_{FSM}	250	A
Voltage Rate of Charge (Rated VR)	dV/dt	10000	V/uS
Operating and Storage temperature range	T_J, T_{STG}	-65 to +175	°C

STATIC ELECTRICAL CHARACTERISTICS

PARAMETER	TEST CONDITION	SYMBOL	MAX	UNIT
Forward voltage (Note1)	$I_F=15A$	V_F	$T_J=25°C$	0.80
			$T_J=125°C$	0.67
	$I_F=30A$	V_F	$T_J=25°C$	0.93
			$T_J=125°C$	0.80
Leakage current	$V_R=100V$	I_R	100	uA
			5	mA
Typical junction capacitance (Note2)		C_j	300	pF

THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	TYP	UNIT
Typical thermal resistance (Note3,4)	R_{thJc}	2	°C/W
	R_{thJa}	7	
	R_{thJL}	1	

Note :

- (1) 300us pulse width, 2% duty cycle.
- (2) Measured at 1.0MHz and applied reverse voltage of 4.0 VDC
- (3) Thermal Resistance Junction to Case.
- (4) The unit mounted on copper plate (75x75x15) mm heatsink

REV. 4, Jun.-2015, KTHC20

RATING AND CHARACTERISTIC CURVES
MBR30100CT



FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL JUNCTION CAPACITANCE





FIG.5- TYPICAL REVERSE CHARACTERISTICS



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.