

**DUAL ESD PROTECTION DIODES**

STAND-OFF VOLTAGE - **5 ~24** Volts  
POWER DISSIPATION - **300** WATTS

**GENERAL DESCRIPTION**

- The L30ESD5V0C3-2~L30ESD24VC3-2 are a dual voltage suppressor designed to protect components which are connected to data and transmission lines against Electro Static Discharge (ESD).
- It clamps the voltage just above the logic level supply for positive transients , and to a diode drop below ground for negative transients.
- It can work as bi-directional suppressor by connecting only pin 1 to 2.

**FEATURES**

- 2 Unidirectional ESD protection.
- Max. peak pulse power : Ppp = 300W at tp = 8/20 us
- Ultra low leakage current : IRM < 1uA @ VBR
- ESD protection > 25KV per MIL-STD-883C, Method 3015-6: Class 3.
- IEC 61000-4-2, level 4 ( ESD ),>15KV(air) ;>8KV(contact ) .
- Ultra small SMD plastic packages


**APPLICATION**

- Computers and peripherals
- Communication system
- Portable electronics
- Cellular handsets and accessories.

**MECHANICAL DATA**

- Case Material: "Green" molding compound UL flammability classification 94V-0 (No Br.Sb, Cl)
- Terminals: Lead Free Plating (Matte Tin Finish), solderable per J-STD-002 and JESD22-B/02.
- Moisture Sensitivity: Leve 1 per J-STD-020C
- Component in accordance to RoHs 2002/95/EC

**SOT23**




SOT23		
DIM.	MIN.	MAX.
A	0.89	1.05
B	0.30	0.51
C	0.085	0.18
D	2.75	3.04
E	1.20	1.60
F	0.85	1.05
G	1.70	2.10
H	2.10	2.75
I	0.0	0.1
L	0.6 typ.	
S	0.35	0.65

All Dimensions in millimeter

PIN ASSIGNMENT	
1,2	Cathode
3	Ground

**Marking & Orientation**



Marking: L30ESD5V0C3-2, XX XX: LT E5  
L30ESD12VC3-2, XXX XX: VCC YM  
L30ESD24VC3-2, XXX XX: VCO YM

**MAXIMUM RATINGS** (Tj= 25°C unless otherwise noticed)

Rating	Symbol	Value	Unit
Peak pulse Power ( 8/20us Waveform)	PPPM	300	W
Operating Junction Temperature Range	TJ	-55 to + 125	°C
Storage Temperature Range	Tstg	-55 to + 150	°C
Soldering Temperature, t max = 10s	TL	260	°C

REV. 6, Dec-2013, KSIR03

**ELECTRICAL CHARACTERISTICS** (T<sub>j</sub>= 25°C unless otherwise noticed)

**L30ESD5V0C3-2**

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse standoff voltage	V <sub>DRM</sub>	---	---	---	5	V
Reverse leakage current	I <sub>RM</sub>	V <sub>DRM</sub> = 5V	---	---	1	uA
Peak pulse Current	I <sub>pp</sub>	t <sub>p</sub> = 8/20us	---	---	17	A
Breakdown voltage	V <sub>BR</sub>	I <sub>R</sub> = 1 mA	6.4	---	7.2	V
Diode capacitance	C <sub>J</sub>	V <sub>R</sub> = 0 V , f = 1MHz	---	156	160	pF
Clamping Voltage	V <sub>CL</sub>	I <sub>pp</sub> = 1 A, t <sub>p</sub> = 8/20us	---	---	9.8	V
Clamping Voltage	V <sub>CL</sub>	I <sub>pp</sub> = 15 A, t <sub>p</sub> = 8/20us	---	---	20	V

**L30ESD12VC3-2**

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse standoff voltage	V <sub>DRM</sub>	---	---	---	12	V
Reverse leakage current	I <sub>RM</sub>	V <sub>DRM</sub> = 12 V	---	---	1	uA
Peak pulse Current	I <sub>pp</sub>	t <sub>p</sub> = 8/20us	---	---	12	A
Breakdown voltage	V <sub>BR</sub>	I <sub>R</sub> = 1 mA	14.2	---	15.8	V
Diode capacitance	C <sub>J</sub>	V <sub>R</sub> = 0 V , f = 1MHz	---	78	100	pF
Clamping Voltage	V <sub>CL</sub>	I <sub>pp</sub> = 1 A, t <sub>p</sub> = 8/20us	---	---	19	V
Clamping Voltage	V <sub>CL</sub>	I <sub>pp</sub> = 12 A, t <sub>p</sub> = 8/20us	---	---	25	V

**L30ESD24VC3-2**

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse standoff voltage	V <sub>DRM</sub>	---	---	---	24	V
Reverse leakage current	I <sub>RM</sub>	V <sub>DRM</sub> = 24V	---	---	1	uA
Peak pulse Current	I <sub>pp</sub>	t <sub>p</sub> = 8/20us	---	---	4	A
Breakdown voltage	V <sub>BR</sub>	I <sub>R</sub> = 1 mA	26.7	---	29.6	V
Diode capacitance	C <sub>J</sub>	V <sub>R</sub> = 0 V , f = 1MHz	---	30	60	pF
Clamping Voltage	V <sub>CL</sub>	I <sub>pp</sub> = 1 A, t <sub>p</sub> = 8/20us	---	---	36	V
Clamping Voltage	V <sub>CL</sub>	I <sub>pp</sub> = 4 A, t <sub>p</sub> = 8/20us	---	---	43	V




Figure 1. 8/20 us pulse waveform according to IEC 61000-4-5




Figure 2. ESD pulse waveform according to IEC 61000-4-2




Figure 3. Power Dissipation versus Pulse Time




Figure 4. Peak pulse power versus T<sub>J</sub>




Figure 5. Typical Junction Capacitance




Figure 6. Reverse Leakage Current versus T<sub>J</sub>




Figure 7. ESD Test Configuration

L30ESD5V0C3-2




Figure 8. Clamped +8 kV ESD voltage waveform




Figure 9. Clamped -8 kV ESD voltage waveform

L30ESD12VC3-2




Figure 10. Clamped +8 kV ESD voltage waveform




Figure 11. Clamped -8 kV ESD voltage waveform

L30ESD24VC3-2




Figure 12. Clamped +8 kV ESD voltage waveform




Figure 13. Clamped -8 kV ESD voltage waveform

## Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.