

Products



Contact Us News Corporate Info **Careers Investors**

Language: English | 简体中文 | 繁體中文

Search GO **⑥** Part#/Keyword **⑥** Inventory **⑥** Cross Ref.

Contact Sales

Applications

Products Discrete Analog **Power Management Connectivity & Timing** Clock ICs **Crystal and Crystal** Oscillator CXO VCXO/TCXO/VCTCXO Xtals/Crystals **>>** Interface PCIe Packet Switch/Bridges Signal Integrity -ReDrivers/Repeaters Switches/MUX Logic

Automotive

< BACK TO XTALS/CRYSTALS

Protocols

Quality

Design

Glass Sealed SMD

Specs & Tech Docs

PCNs

FAQs

Product Specifications

Product Parameters

ProductSeries FQ Family Crystal **Legacy PN** NES3 Freq Range (MHz) 8 to 66 **Package Type** Ceramic Glass **Package Size** 3.2 x 2.5 x 0.75 **Pads** NotRecommended

Related Content

Quality Documentation

Applications

Industrial PC, Docking, Multi-Function Printer, Digital Cameras, DVD/Blu-Ray, Storage Array, Smart Grid, Monitors, Security, Smartphones, STB, TVs

Protocols

USB 3.0, USB 2.0, USB

Quality & Reliability

Technical Documents

Recommended Soldering Techniques

In TN1.pdf

Additional Technical Documents are available upon request: Application information, Evaluation board, and Other technical documents

Request Documents

Privacy Policy | Terms & Conditions | Login or Register Copyright © 2019 Diodes Incorporated

Follow Us: f g+ in 💆 🚳 🗅







