

- Products
 - Clock and Timing ICs
 - Crystal and Crystal Oscillator
 - Programmable XO
 - 32kHz XO
 - CXO
 - VCXO
 - TCXO / VCTCXO
 - Xtals/Crystals
 - Standard Xtal Parts
 - Display Interface
 - Home Appliance
 - Interface Logic
 - PCIe Switch
 - PCIe / PCI Bridges
 - Power Management IC
 - ReDriver / Repeater / Signal Conditioners
 - Signal Switch IC / Multiplexers
 - UART
 - Video Decoder
 - Part Cross Reference
- Protocols
 - Bluetooth / WiFi
 - DDR Technology
 - Type C
 - Ethernet
 - Fibre Channel
 - InfiniBand
 - LVDS
 - PCI and PCIe Technology
 - SATA / SAS Technology
 - USB Technology
 - Video/Display
 - XAUJ
 - SRIO
- Applications
 - Automotive
 - Computer and Peripheral
 - Digital Media
 - Embedded Systems
 - Networking and Telecom
 - Server and Storage
 - Ultra Mobility & Wireless
 - Application Notes
- Support
 - Quality
 - Packaging
 - Contact Support
 - FAQ
 - Technical Articles
 - Collateral & Downloads
 - Application Notes
- Company
 - About Pericom
 - Investors
 - Newsroom
 - Careers
 - Pericom Saronix-eCera (PSE)
- Contact
 - Contact Sales
 - Driving Directions
 - Contact Pericom
 - Contact Support

Home » Products » Crystal and Crystal Oscillator » Xtals/Crystals » Standard Xtal Parts

[« Back to Standard Xtal/Crystal Parts](#)

GC2400032



SPECS & TECH DOCS **FAQS**

Product Specifications

Product Specs

Series	GC
ESR (max)	30
Shunt Cap	7
Oper. Temp (-)	-40-85
Drive Level	100 typ, 500 max

Package Size	11.5*4.5*4.0mm
Tolerance	30
Stability	50
C.Load	18
Frequency	24
NotRecommended	0

Related

N/A

Quality & Reliability

[Quality Documentation](#)

[Contact Sales](#)

[Sign In](#)

Sign in to see your update request status or to request updates about this part.