


**POWER MOSFET
THRU-HOLE (MO-036AB)**

**IRFG6110
JANTX2N7336
JANTXV2N7336
REF:MIL-PRF-19500/598
100V, Combination 2N-2P-CHANNEL
HEXFET[®] MOSFET TECHNOLOGY**

Product Summary

| Part Number | R _{DS(on)} | I _D | CHANNEL |
|-------------|---------------------|----------------|---------|
| IRFG6110 | 0.7Ω | 1.0A | N |
| IRFG6110 | 1.4Ω | -0.75A | P |



HEXFET[®] MOSFET technology is the key to International Rectifier's advanced line of power MOSFET transistors. The efficient geometry design achieves very low on-state resistance combined with high transconductance. HEXFET transistors also feature all of the well-established advantages of MOSFETs, such as voltage control, very fast switching, ease of paralleling and electrical parameter temperature stability. They are well-suited for applications such as switching power supplies, motor controls, inverters, choppers, audio amplifiers, high energy pulse circuits, and virtually any application where high reliability is required. The HEXFET transistor's totally isolated package eliminates the need for additional isolating material between the device and the heatsink. This improves thermal efficiency and reduces drain capacitance.

Features:

- Simple Drive Requirements
- Ease of Paralleling
- Hermetically Sealed
- Electrically Isolated
- Dynamic dv/dt Rating
- Light-weight

Absolute Maximum Ratings (Per Die)

| | Parameter | N-Channel | P-Channel | Units |
|---|-------------------------------|---|-----------|-------|
| I _D @ V _{GS} = ±10V, T _C = 25°C | Continuous Drain Current | 1.0 | -0.75 | A |
| I _D @ V _{GS} = ±10V, T _C = 100°C | Continuous Drain Current | 0.6 | -0.5 | |
| I _{DM} | Pulsed Drain Current ① | 4.0 | -3.0 | |
| P _D @ T _C = 25°C | Max. Power Dissipation | 1.4 | 1.4 | W |
| | Linear Derating Factor | 0.011 | 0.011 | W/°C |
| V _{GS} | Gate-to-Source Voltage | ±20 | ±20 | V |
| EAS | Single Pulse Avalanche Energy | 75 ② | 75 ⑤ | mJ |
| I _{AR} | Avalanche Current ① | 1.0 | -0.75 | A |
| E _{AR} | Repetitive Avalanche Energy ① | 0.14 | 0.14 | mJ |
| dv/dt | Peak Diode Recovery dv/dt | 5.5 ③ | -5.5 ⑥ | V/ns |
| T _J | Operating Junction | -55 to 150 | | °C |
| T _{STG} | Storage Temperature Range | | | |
| | Lead Temperature | 300 (0.63 in./1.6 mm from case for 10s) | | |
| | Weight | 1.3 (Typical) | | g |

For footnotes, refer to the last page

Electrical Characteristics For Each N-Channel Device @ T_j = 25°C (Unless Otherwise Specified)

| | Parameter | Min | Typ | Max | Units | Test Conditions |
|-------------------------------------|--|------|------|------------|-------|---|
| BV _{DSS} | Drain-to-Source Breakdown Voltage | 100 | — | — | V | V _{GS} = 0V, I _D = 1.0mA |
| ΔBV _{DSS} /ΔT _J | Temperature Coefficient of Breakdown Voltage | — | 0.13 | — | V/°C | Reference to 25°C, I _D = 1.0mA |
| R _{DS(on)} | Static Drain-to-Source On-State Resistance | — | — | 0.7 0.8 | Ω | V _{GS} = 10V, I _D = 0.6A ④ V _{GS} = 10V, I _D = 1.0A |
| V _{GS(th)} | Gate Threshold Voltage | 2.0 | — | 4.0 | V | V _{DS} = V _{GS} , I _D = 250μA |
| g _{fs} | Forward Transconductance | 0.86 | — | — | S | V _{DS} > 15V, I _{DS} = 0.6A ④ |
| I _{DSS} | Zero Gate Voltage Drain Current | — | — | 25 250 | μA | V _{DS} = 80V, V _{GS} = 0V V _{DS} = 80V, V _{GS} = 0V, T _J = 125°C |
| I _{GSS} | Gate-to-Source Leakage Forward | — | — | 100 | nA | V _{GS} = 20V |
| I _{GSS} | Gate-to-Source Leakage Reverse | — | — | -100 | nA | V _{GS} = -20V |
| Q _g | Total Gate Charge | — | — | 15 | nC | V _{GS} = 10V, I _D = 1.0A, V _{DS} = 50V |
| Q _{gs} | Gate-to-Source Charge | — | — | 7.5 | nC | |
| Q _{gd} | Gate-to-Drain ('Miller') Charge | — | — | 7.5 | nC | |
| t _{d(on)} | Turn-On Delay Time | — | — | 20 | ns | V _{DD} = 50V, I _D = 1.0A, V _{GS} = 10V, R _G = 7.5Ω |
| t _r | Rise Time | — | — | 25 | | |
| t _{d(off)} | Turn-Off Delay Time | — | — | 40 | | |
| t _f | Fall Time | — | — | 40 | | |
| L _S + L _D | Total Inductance | — | 10 | — | nH | Measured from drain lead (6mm/ 0.25in. from package) to source lead (6mm/0.25in. from package) |
| C _{iss} | Input Capacitance | — | 180 | — | pF | V _{GS} = 0V, V _{DS} = 25V f = 1.0MHz |
| C _{oss} | Output Capacitance | — | 82 | — | | |
| C _{rss} | Reverse Transfer Capacitance | — | 15 | — | | |

Source-Drain Diode Ratings and Characteristics (Per Die)

| | Parameter | Min | Typ | Max | Units | Test Conditions |
|-----------------|--|--|-----|------|-------|--|
| I _S | Continuous Source Current (Body Diode) | — | — | 1.0 | A | T _j = 25°C, I _S = 1.0A, V _{GS} = 0V ④ |
| I _{SM} | Pulse Source Current (Body Diode) ① | — | — | 4.0 | | |
| V _{SD} | Diode Forward Voltage | — | — | 1.5 | V | T _j = 25°C, I _F = 1.0A, di/dt ≤ 100A/μs |
| t _{rr} | Reverse Recovery Time | — | — | 200 | nS | V _{DD} ≤ 50V ④ |
| Q _{RR} | Reverse Recovery Charge | — | — | 0.83 | nC | |
| t _{on} | Forward Turn-On Time | Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by L _S + L _D . | | | | |

Thermal Resistance (Per Die)

| | Parameter | Min | Typ | Max | Units | Test Conditions |
|-------------------|---------------------|-----|-----|-----|-------|----------------------|
| R _{thJC} | Junction-to-Case | — | — | 17 | °C/W | Typical socket mount |
| R _{thJA} | Junction-to-Ambient | — | — | 90 | | |

Note: Corresponding Spice and Saber models are available on International Rectifier Website.

For footnotes, refer to the last page

Electrical Characteristics For Each P-Channel Device @ T_j = 25°C (Unless Otherwise Specified)

| | Parameter | Min | Typ | Max | Units | Test Conditions |
|-------------------------------------|--|------|--------|------|-------|--|
| B _V DSS | Drain-to-Source Breakdown Voltage | -100 | — | — | V | V _{GS} = 0V, I _D = -1.0mA |
| ΔB _V DSS/ΔT _J | Temperature Coefficient of Breakdown Voltage | — | -0.098 | — | V/°C | Reference to 25°C, I _D = -1.0mA |
| R _{DS(on)} | Static Drain-to-Source On-State Resistance | — | — | 1.4 | Ω | V _{GS} = -10V, I _D = -0.5A ④ |
| | | — | — | 1.73 | | V _{GS} = -10V, I _D = -0.75A |
| V _{GS(th)} | Gate Threshold Voltage | -2.0 | — | -4.0 | V | V _{DS} = V _{GS} , I _D = -250μA |
| g _{fs} | Forward Transconductance | 0.67 | — | — | S | V _{DS} > -15V, I _{DS} = -0.5A ④ |
| I _{DSS} | Zero Gate Voltage Drain Current | — | — | -25 | μA | V _{DS} = -80V, V _{GS} = 0V |
| | | — | — | -250 | | V _{DS} = -80V, V _{GS} = 0V, T _J = 125°C |
| I _{GSS} | Gate-to-Source Leakage Forward | — | — | -100 | nA | V _{GS} = -20V |
| I _{GSS} | Gate-to-Source Leakage Reverse | — | — | 100 | nA | V _{GS} = 20V |
| Q _g | Total Gate Charge | — | — | 15 | nC | V _{GS} = -10V, I _D = -0.75A, V _{DS} = -50V |
| Q _{gs} | Gate-to-Source Charge | — | — | 7.0 | | |
| Q _{gd} | Gate-to-Drain ('Miller') Charge | — | — | 8.0 | | |
| t _{d(on)} | Turn-On Delay Time | — | — | 30 | ns | V _{DD} = -50V, I _D = -0.75A, V _{GS} = -10V, R _G = 7.5Ω |
| t _r | Rise Time | — | — | 60 | | |
| t _{d(off)} | Turn-Off Delay Time | — | — | 70 | | |
| t _f | Fall Time | — | — | 80 | | |
| L _S + L _D | Total Inductance | — | 10 | — | nH | Measured from drain lead (6mm/0.25in. from package) to source lead (6mm/0.25in. from package) |
| C _{iss} | Input Capacitance | — | 200 | — | pF | V _{GS} = 0V, V _{DS} = -25V f = 1.0MHz |
| C _{oss} | Output Capacitance | — | 85 | — | | |
| C _{rss} | Reverse Transfer Capacitance | — | 30 | — | | |

Source-Drain Diode Ratings and Characteristics (Per Die)

| | Parameter | Min | Typ | Max | Units | Test Conditions |
|-----------------|--|--|-----|-------|-------|--|
| I _S | Continuous Source Current (Body Diode) | — | — | -0.75 | A | T _j = 25°C, I _S = -0.75A, V _{GS} = 0V ④ |
| I _{SM} | Pulse Source Current (Body Diode) ① | — | — | -3.0 | | |
| V _{SD} | Diode Forward Voltage | — | — | -5.5 | V | T _j = 25°C, I _F = -0.75A, di/dt ≤ -100A/μs |
| t _{rr} | Reverse Recovery Time | — | — | 200 | nS | V _{DD} ≤ -50V |
| Q _{RR} | Reverse Recovery Charge | — | — | 9.0 | nC | |
| t _{on} | Forward Turn-On Time | Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by L _S + L _D . | | | | |

Thermal Resistance (Per Die)

| | Parameter | Min | Typ | Max | Units | Test Conditions |
|-------------------|---------------------|-----|-----|-----|-------|----------------------|
| R _{thJC} | Junction-to-Case | — | — | 17 | °C/W | Typical socket mount |
| R _{thJA} | Junction-to-Ambient | — | — | 90 | | |

For footnotes, refer to the last page

N-Channel
G1,G3




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance Vs. Temperature

N-Channel
G1,G3




Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 8. Maximum Safe Operating Area

N-Channel
G1,G3




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

N-Channel
G1,G3




Fig 12a. Unclamped Inductive Test Circuit




Fig 12c. Maximum Avalanche Energy Vs. Drain Current




Fig 12b. Unclamped Inductive Waveforms




Fig 13a. Basic Gate Charge Waveform




Fig 13b. Gate Charge Test Circuit

P-Channel
 G2,G4




Fig 14. Typical Output Characteristics




Fig 15. Typical Output Characteristics




Fig 16. Typical Transfer Characteristics




Fig 17. Normalized On-Resistance
 Vs. Temperature

P-Channel
G2,G4




Fig 18. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 19. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 20. Typical Source-Drain Diode Forward Voltage




Fig 21. Maximum Safe Operating Area

P-Channel
G2,G4




Fig22. Maximum Drain Current Vs. Case Temperature




Fig 23a. Switching Time Test Circuit




Fig 23b. Switching Time Waveforms




Fig 24. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

P-Channel
G2,G4




Fig 25a. Unclamped Inductive Test Circuit




Fig 25c. Maximum Avalanche Energy
Vs. Drain Current




Fig 25b. Unclamped Inductive Waveforms




Fig 26a. Basic Gate Charge Waveform




Fig 26b. Gate Charge Test Circuit



IRFG6110



Footnotes:



- ① Repetitive Rating; Pulse width limited by maximum junction temperature.
- ② $V_{DD} = 25V$, starting $T_J = 25^\circ C$, $L = 150mH$, Peak $I_L = 1.0A$, $V_{GS} = 10V$
- ③ $I_{SD} \leq 1.0A$, $di/dt \leq 75A/\mu s$, $V_{DD} \leq 100V$, $T_J \leq 150^\circ C$
- ④ Pulse width $\leq 300 \mu s$; Duty Cycle $\leq 2\%$
- ⑤ $V_{DD} = -25V$, starting $T_J = 25^\circ C$, $L = 266mH$, Peak $I_L = -0.75A$, $V_{GS} = -10V$
- ⑥ $I_{SD} \leq -0.75A$, $di/dt \leq -75A/\mu s$, $V_{DD} \leq -100V$, $T_J \leq 150^\circ C$

Case Outline and Dimensions — MO-036AB



LEGEND

| | | |
|-----------|--------------------|---------------|
| G = GATE | S = SOURCE | N Ch.- G1, G3 |
| D = DRAIN | NC = NO CONNECTION | P Ch.- G2, G4 |



NOTES:

1. DIMENSIONING & TOLERANCING PER ASME Y14.5M-1994.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
4. OUTLINE CONFORMS TO JEDEC OUTLINE MO-036AB.
- ⑤ MEASURED WITH THE LEADS CONSTRAINED TO BE PERPENDICULAR TO DATUM PLANE C.



IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
 IR LEOMINSTER : 205 Crawford St., Leominster, Massachusetts 01453, USA Tel: (978) 534-5776
 TAC Fax: (310) 252-7903

Visit us at www.irf.com for sales contact information.
 Data and specifications subject to change without notice. 02/2010