

DEMOBOARD BTN8962TA

- [Overview](#)
- [Parametrics](#)
- [Documents](#)
- [Order](#)
- [Support](#)

Description:

The NovalithIC™ H-Bridge/Dual-Halfbridge Demo Board contains two NovalithICs used as two half-bridges or in atypical H-bridge configuration including peripheral components and reverse polarity protection. Control signals can be supplied via a 26 pin header connector. The board is suitable for all members of the NovalithIC™ family.

Target Applications:

- Motor Control & Drives
- Automotive



Solution Finder

MOSFET
IGBT
Vreg
MCU
More

<input type="radio"/> ESD Protection	<input type="radio"/> Sim Models
<input type="radio"/> Bipolar Transistor	<input type="radio"/> Eval Boards
<input type="radio"/> Diode (Rectifier)	<input checked="" type="radio"/> Infineon Tools
<input type="radio"/> Smart Switch	<input type="radio"/> IGBT Tools
<input type="radio"/> Transceivers	

Reset
Find >

Follow us



© 1999 - 2017 Infineon Technologies AG, 苏ICP备15016286号

[Usage of this website is subject to our Usage Terms](#) > [Imprint](#) > [Contact](#) > [Privacy Policy](#) > [Glossary](#)

[Switch to Mobile Version](#)

This site uses cookies. By accepting cookies you can optimize your browsing experience. Please read our [Privacy Policy](#) for more information.

OK