


40 V, 2 x 5 A low forward voltage power Schottky rectifier



Features

- Low profile design – 1.1mm package typical height
- Wettable flanks for automatic visual inspection
- Very low conduction losses
- High forward surge current capability
- ECOPACK2 compliant

Applications

- DC/DC converter
- Stand by power
- Oring
- Polarity protection

Description

This 2 x 5 A, 40 V Schottky diode is suitable for power supply, especially for lighting power, as well as auxiliary power in server or telecom SMPS.

Packaged in PSMC (TO-277A), this STPS10L40CSF, dual diode device provides a high level of efficiency in a compact and flat package is ideal for oring function in server for instance.



Product status link

[STPS10L40CSF](#)

Product summary

$I_{F(AV)}$	2 x 5 A
V_{RRM}	40 V
$T_j \text{ (max.)}$	150 °C
$V_F \text{ (typ.)}$	0.370 V

1 Characteristics

Table 1. Absolute ratings (limiting values per diode at 25 °C, unless otherwise specified)

Symbol	Parameter				Value	Unit
V _{RRM}	Repetitive peak reverse voltage				40	V
I _{F(AV)}	Average forward current, δ = 0.5 square wave	T _C = 135 °C ⁽¹⁾	Per diode	5	A	
			Per device	10		
P _{ARM}	Repetitive avalanche power	t _p = 10 μs	T _J = 125 °C	165	W	
I _{FSM}	Surge non repetitive forward current	t _p = 10 ms sinusoidal		120	A	
T _{stg}	Storage temperature range			-65 to +175	°C	
T _J	Maximum operating junction temperature ⁽²⁾			+150	°C	

1. Value based on $R_{th(j-c)}(max.)$.

2. $(dP_{tot}/dT_j) < (1/R_{th(j-a)})$ condition to avoid thermal runaway for a diode on its own heatsink.

Table 2. Thermal resistance parameter

Symbol	Parameter		Typ. value	Unit
$R_{th(j-c)}$	Junction to case, per device	PSMC (TO-277)	1.0	°C/W

For more information, please refer to the following application note:

- AN5088: Rectifiers thermal management, handling and mounting recommendations

Table 3. Static electrical characteristics (per diode)

Symbol	Parameter	Test conditions		Min.	Typ.	Max.	Unit
$I_R^{(1)}$	Reverse leakage current	$T_j = 25\text{ °C}$	$V_R = V_{RRM}$	-		125	μA
		$T_j = 125\text{ °C}$		-	30	50	mA
$V_F^{(2)}$	Forward voltage drop	$T_j = 25\text{ °C}$	$I_F = 5\text{ A}$	-		0.495	V
		$T_j = 125\text{ °C}$		-	0.370	0.430	
		$T_j = 25\text{ °C}$	$I_F = 10\text{ A}$	-		0.600	
		$T_j = 125\text{ °C}$		-	0.505	0.590	

1. Pulse test: $t_p = 5\text{ ms}$, $\delta < 2\%$

2. Pulse test: $t_p = 380\text{ }\mu\text{s}$, $\delta < 2\%$

To evaluate the conduction losses, use the following equation:

$$P = 0.25 \times I_{F(AV)} + 0.036 \times I_{F(RMS)}^2$$

For more information, please refer to the following application notes related to the power losses :

- AN604: Calculation of conduction losses in a power rectifier
- AN4021: Calculation of reverse losses on a power diode

1.1 Characteristics (curves)

Figure 1. Average forward current versus case temperature ($\delta = 0.5$, per diode)




Figure 2. Relative variation of thermal impedance junction to case versus pulse duration




Figure 3. Reverse leakage current versus reverse voltage applied (typical values, per diode)




Figure 4. Junction capacitance versus reverse voltage applied (typical values, per diode)




Figure 5. Forward voltage drop versus forward current (typical values, per diode)




Figure 6. Thermal resistance junction to ambient versus copper surface under tab (typical values, epoxy printed board FR4, $e_{Cu} = 70 \mu m$)





Figure 7. Normalized avalanche power derating versus pulse duration ($T_j = 125\text{ }^{\circ}\text{C}$)



2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

2.1 PSMC (TO-277A) package information

- Epoxy meets UL94,V0
- Cooling method : by conduction (C)

Figure 8. PSMC (TO-277A) package outline





Table 4. PSMC (TO-277A) package mechanical data

Ref.	Dimensions					
	Millimeters			Inches (for reference only)		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	1.00	1.10	1.20	0.039	0.043	0.047
b	1.05	1.20	1.35	0.041	0.047	0.053
b2	1.90	2.05	2.20	0.075	0.081	0.087
b4		0.75			0.029	
C	0.15	0.23	0.40	0.006	0.009	0.016
D	4.45	4.60	4.75	0.175	0.181	0.187
D1	4.25	4.40	4.45	0.167	0.173	0.175
D2	3.40	3.60	3.70	0.134	0.142	0.146
E	6.35	6.50	6.65	0.250	0.256	0.262
E1	6.05	6.10	6.15	0.238	0.240	0.242
E2	4.50	4.60	4.70	0.177	0.181	0.185
E3		3.94			1.55	
e		2.13			0.084	
e1		3.33			0.131	
G		1.20			0.047	
G1		0.70			0.027	
L	0.90	1.05	1.24	0.035	0.041	0.049
L4	0.02			0.0008		
L5	0.02			0.0008		

Figure 9. PSMC (TO-277A) package footprint in mm (in inches)


Note: For package and tape orientation, reel and inner box dimensions and tape outline please check [TN1173](#)

3 Ordering information

Table 5. Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
STPS10L40CSF	10L40C	PSMC (TO-277A)	90 mg	6000	Tape and reel

Revision history

Table 6. Document revision history

Date	Version	Changes
20-May-2021	1	Initial release.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2021 STMicroelectronics – All rights reserved