

Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild guestions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officer



November 2011

MPSA64 / MMBTA64 / PZTA64 PNP Darlington Transistor

Features

- · This device is designed for applications requiring extremely high current gain at currents to 800 mA.
- · Sourced from Process 61.



Absolute Maximum Ratings* T_a = 25°C unless otherwise noted

Symbol	Parameter	Value	Units
V _{CES}	Collector-Emitter Voltage	-30	V
V_{CBO}	Collector-Base Voltage	-30	V
V _{EBO}	Emitter-Base Voltage	-10	V
I _C	Collector Current - Continuous	-1.2	Α
T _{J,} T _{stg}	Operating and Storage Junction Temperature Range	-55 to +150	°C

^{*} These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

- 1) These ratings are based on a maximum junction temperature of 150 degrees C.
- 2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Thermal Characteristics $T_a = 25$ °C unless otherwise noted

Symbol	Parameter	Max.			Units
Зуппоот		MPSA64	*MMBTA64	**PZTA64	Ullits
P _D	Total Device Dissipation Derate above 25°C	625 5.0	350 2.8	1,000 8.0	mW mW/°C
$R_{ heta JC}$	Thermal Resistance, Junction to Case	83.3			°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	200	357	125	°C/W

^{*} Device mounted on FR-4 PCB 1.6" X 1.6" X 0.06."

© 2011 Fairchild Semiconductor Corporation MPSA64 / MMBTA64 / PZTA64 Rev. B0 www.fairchildsemi.com


^{**} Device mounted on FR-4 PCB 36 mm X 18 mm X 1.5 mm; mounting pad for the collector lead min. 6 cm².


Electrical Characteristics $T_a = 25$ °C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Max.	Units	
OFF CHARAC	OFF CHARACTERISTICS					
V _{(BR)CES}	Collector-Emitter Breakdown Voltage	$I_C = -100 \mu A, I_B = 0$	-30		V	
I _{CBO}	Collector-Cutoff Current	$V_{CB} = -30V, I_{E} = 0$		-100	nA	
I _{EBO}	Emitter-Cutoff Current	$V_{EB} = -10V, I_{C} = 0$		-100	nA	
ON CHARACT	ON CHARACTERISTICS*					
h _{FE}	DC Current Gain	I _C = -10mA, V _{CE} = -5.0V I _C = -100mA, V _{CE} = -5.0V	10,000 20,000			
V _{CE(sat)}	Collector-Emitter Saturation Voltage	$I_C = -100 \text{mA}, I_B = -0.1 \text{mA}$		-1.5	V	
V _{BE(on)}	Base-Emitter On Voltage	$I_C = -100 \text{mA}, V_{CE} = -5.0 \text{V}$		-2.0	V	
SMALL SIGNAL CHARACTERISTICS						
f _T	Current Gain - Bandwidth Product	$I_C = -10 \text{mA}, V_{CE} = -5.0 \text{V},$ f = 100MHz	125		MHz	


^{*} Pulse Test: Pulse Width $\leq 300 \mu s$, Duty Cycle $\leq 2.0\%$


Typical Performance Characteristics








Typical Performance Characteristics (continued)















TRADEMARKS

CTL™

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

 $\begin{array}{lll} 2 Cool^{\text{TM}} & & \text{FPS}^{\text{TM}} \\ \text{AccuPower}^{\text{TM}} & & \text{F-PFS}^{\text{TM}} \\ \text{Auto-SPM}^{\text{TM}} & & \text{FRFET}^{\text{B}} \end{array}$

AX-CAP^{TM*} Global Power ResourceSM

 BitSiC®
 Green FPS™

 Build it Now™
 Green FPS™ e-Series™

 $\begin{array}{ccc} \mathsf{CorePLUS^{\intercal M}} & \mathsf{G}\textit{max}^{\intercal M} \\ \mathsf{CorePOWER}^{\intercal M} & \mathsf{GTO}^{\intercal M} \\ \mathsf{CROSSVOLT^{\intercal M}} & \mathsf{IntelliMAX^{\intercal M}} \end{array}$

Current Transfer Logic™ Making Small Speakers Sound Louder

ISOPLANAR™

DUAL COOLTM
ECOSPARK®
MICROCOUPLER™
EfficientMax™
ESBC™
MicroPak™
MicroPak™
MicroPak™
MillerDrive™

Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FAST®
FastvCore™

MillerDrive™
Motion-Max™
Motion-SPM™
Motion-SPM™
mWSaver™
OptoHiT™
OPTOLGIES
OPTOLGIES
OPTOLGIES
OPTOLGIES
OPTOLGIES
OPTOLGIES
OPTOLGIES

FastvCore™ OPTOPLANAR® FETBench™ FlashWriter®*

PDP SPMTM
Power-SPMTM
PowerTrench[®]
PowerXSTM

Programmable Active Droop™

QFĒT[®]
QS™
Quiet Series™
RapidConfigure™

Saving our world, 1mW/W/kW at a time™

SignalWise™
SmartMax™
SMART START™
SMMS
STEALTH™
SuperFET®
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SuperMOS®
SyncFET™
Sync-Lock™

SuperSOTM-8
SupreMOS®
SyncFETTM
Sync-LockTM
SYSTEM
GENERAL®*

The Power Franchise®

Franchise
TinyBoost™
TinyBuck™
TinyCalc™
TinyCogic®
TINYOPTO™
TinyPower™
TinyPower™
TinyPWM™
TinyWire™
TranSiC®
TriFault Detect™
TRUECURRENT®**

µSerDes™ SerDes UHC®

Ultra FRFET™ UniFET™ VCX™ VisualMax™ VoltagePlus™ XS™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

- Life support devices or systems are devices or systems which, (a)
 are intended for surgical implant into the body or (b) support or
 sustain life, and (c) whose failure to perform when properly used in
 accordance with instructions for use provided in the labeling, can be
 reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. 157

ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hol

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910

Phone: 421 33 790 2910 **Japan Customer Focus Center**Phone: 81–3–5817–1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative