SBT700-06RH

ON Semiconductor®

http://onsemi.com

Schottky Barrier Diode

60V, 70A, VF; 0.66V Dual To-3PF-3L Cathode Common

Applications

· High frequency rectification (switching regulators, converters, choppers)

Features

- Guaranteed up to Tj=150°C
- · Fast reverse recovery time
- · High reliability due to highly reliable planar structure
- Low forward voltage (VF max=0.66V)
- · Low switching noise

Specifications


Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Repetitive Peak Reverse Voltage	VRRM		60	V
Nonrepetitive Peak Reverse Surge Voltage	VRSM		66	V
Average Output Current	I _O	50Hz resistive load, Sine wave Tc=44°C	70	А
Surge Forward Current	I _{FSM}	50Hz sine wave, 1 cycle	200	Α
Junction Temperature	Tj		150	°C
Storage Temperature	Tstg		-55 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions

unit: mm (typ) 7538A-003




Ordering & Package Information

Device	Package	Shipping	memo	
SBT700-06RH-1E	BT700-06RH-1E TO-3PF-3L SC-94		Pb-Free	

Marking




Electrical Connection





Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max] UIIII
Reverse Voltage	VR	I _R =10mA, Tc=25°C *	60			V
Forward Voltage	VF	I _F =30A, Tc=25°C *			0.66	V
Reverse Current	IR	V _R =30V, Tc=25°C *			1	mA
Interterminal Capacitance	С	V _R =10V, Tc=25°C *, f=100kHz		1400		pF
Thermal Resistance	Rth(j-c)	Junction-Case : Smoothed DC			1.5	°C / W

Note) * : Value per element.








Outline Drawing

SBT700-06RH-1E



ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equa