

XGS 45000

CMOS Image Sensor, 44.7 Mp, Global Shutter

Product Overview

For complete documentation, see the data sheet.

The XGS 45000 is a 44.7 Mp (8192 x 5460) CMOS image sensor in Super 35 mm optical format, supporting up to 48 frames per second readout with 12-bit output at full resolution, and up to 60 fps with 8K video format compatible ROI output (8192 x 4320).

This device provides high resolution, global shutter imaging with high readout speed and a low power footprint for industrial imaging customers. Three speed grades are available to match device output to key computer interfaces and application requirements. The XGS 45000 shares a common design and footprint with other members of the XGS family, such as the XGS 20000 or XGS 30000, allowing one camera design to support multiple resolutions to simplify and speed time to market for new camera designs. The XGS 45000 is available in a 251-pin µPGA package in both monochrome and Bayer color configurations.

Features

- Advanced 3.2 µm global shutter pixel
- Available speed grades
- · Energy efficient design

Applications

Image capture

Benefits

- High resolution with high image quality and uniformity
- Match to key computer interfaces and application requirements
- · Reduced power and thermal footprints

End Products

- · Industrial cameras and systems
- Inspection system (food, bottles, recycling labels, etc.)
- · Security cameras and systems
- Machine Vision camera
- Broadcasting

Part Electrical Specifications												
Product	Pricing (\$/Unit)	Complian ce	Status	Туре	Megapi xels	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interfac e	Color	Packag e Type
NOIX0SE045KB -GTI		РЬ Н	Active	CMOS	44.7	48	Super 35 mm	Global Shutter	3.2 x 3.2	HiSPi™	Bayer Color	CPGA2 51 44.40x 37.25
NOIX0SN045KB -GTI		РЬ Н	Active	CMOS	44.7	48	Super 35 mm	Global Shutter	3.2 x 3.2	HiSPi™	Mono	CPGA2 51 44.40x 37.25
NOIX1SE045KB- GTI		РЬ Н	Active	CMOS	44.7	31	Super 35 mm	Global Shutter	3.2 x 3.2	HiSPi™	Bayer Color	CPGA2 51 44.40x 37.25
NOIX1SN045KB- GTI		РЬ Н	Active	CMOS	44.7	31	Super 35 mm	Global Shutter	3.2 x 3.2	HiSPi™	Mono	CPGA2 51 44.40x 37.25
NOIX2SE045KB- GTI		РЬ Н	Active	CMOS	44.7	12	Super 35 mm	Global Shutter	3.2 x 3.2	HiSPi™	Bayer Color	CPGA2 51 44.40x 37.25
NOIX2SN045KB -GTI		РЬ Н	Active	CMOS	44.7	12	Super 35 mm	Global Shutter	3.2 x 3.2	HiSPi™	Mono	CPGA2 51 44.40x 37.25