

DDR4 SDRAM LRDIMM Addendum

MTA72ASS16G72LZ – 128GB

Introduction

- Information provided here is in addition to or supersedes information provided in the Micron DDR4 LRDIMM Core data sheet.
- DDR4 functionality and operations supported as defined in the component data sheet
- Features and specifications supported in the Micron DDR4 LRDIMM Core data sheet
- 288-pin, command/address/control-registered, data-buffered, load-reduced dual in-line memory module (LRDIMM)
- Fast data transfer rates: PC4-3200, PC4-2933
- 128GB (16 Gig x 72)
- Quad-rank, using 32Gb TwinDie DDR4
- Each die with 16 internal banks; 4 groups of 4 banks each

Options

- Operating temperature
 - Commercial ($0^{\circ}\text{C} \leq T_{\text{OPER}} \leq 95^{\circ}\text{C}$)
- Package
 - 288-pin DIMM (Green)
- Frequency/CAS latency
 - 0.625ns @ CL = 22 (DDR4-3200)
 - 0.682ns @ CL = 21 (DDR4-2933)

Marking

None
Z
-3G2
-2G9

Figure 1: 288-Pin LRDIMM (R/C-E2)




Figure 2: 288-Pin LRDIMM (R/C-D3)




Table 1: Addressing

Parameter	128GB
Row address	256K A[17:0]
Column address	1K A[9:0]
Device bank group address	4 BG[1:0]
Device bank address per group	4 BA[1:0]
Device configuration	32Gb TwinDie (8 Gig x 4), 16 Banks
Package rank address	4 CS_n[3:0]



Table 2: Part Numbers and Timing Parameters – 128GB Modules

Part Number	Module Density	Configuration	Module Bandwidth	Memory Clock/ Data Rate	Clock Cycles (CL _n RCD _n RP)
MTA72ASS16G72LZ-3G2__	128GB	16 Gig x 72	25.6 GB/s	0.625ns/3200 MT/s	22-22-22
MTA72ASS16G72LZ-2G9__			23.47 GB/s	0.682ns/2933 MT/s	21-21-21

- Notes: 1. Base device: MT40A8G4, 32Gb TwinDie DDR4 SDRAM. The data sheet for the base device can be found on micron.com.
2. All part numbers end with a two-place code (not shown) that designates component and PCB revisions. Consult factory for current revision codes (ex. MTA72ASS16G72LZ-3G2F1).



Important Notes and Warnings

Micron Technology, Inc. ("Micron") reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions. This document supersedes and replaces all information supplied prior to the publication hereof. You may not rely on any information set forth in this document if you obtain the product described herein from any unauthorized distributor or other source not authorized by Micron.

Automotive Applications. Products are not designed or intended for use in automotive applications unless specifically designated by Micron as automotive-grade by their respective data sheets. Distributor and customer/distributor shall assume the sole risk and liability for and shall indemnify and hold Micron harmless against all claims, costs, damages, and expenses and reasonable attorneys' fees arising out of, directly or indirectly, any claim of product liability, personal injury, death, or property damage resulting directly or indirectly from any use of non-automotive-grade products in automotive applications. Customer/distributor shall ensure that the terms and conditions of sale between customer/distributor and any customer of distributor/customer (1) state that Micron products are not designed or intended for use in automotive applications unless specifically designated by Micron as automotive-grade by their respective data sheets and (2) require such customer of distributor/customer to indemnify and hold Micron harmless against all claims, costs, damages, and expenses and reasonable attorneys' fees arising out of, directly or indirectly, any claim of product liability, personal injury, death, or property damage resulting from any use of non-automotive-grade products in automotive applications.

Critical Applications. Products are not authorized for use in applications in which failure of the Micron component could result, directly or indirectly in death, personal injury, or severe property or environmental damage ("Critical Applications"). Customer must protect against death, personal injury, and severe property and environmental damage by incorporating safety design measures into customer's applications to ensure that failure of the Micron component will not result in such harms. Should customer or distributor purchase, use, or sell any Micron component for any critical application, customer and distributor shall indemnify and hold harmless Micron and its subsidiaries, subcontractors, and affiliates and the directors, officers, and employees of each against all claims, costs, damages, and expenses and reasonable attorneys' fees arising out of, directly or indirectly, any claim of product liability, personal injury, or death arising in any way out of such critical application, whether or not Micron or its subsidiaries, subcontractors, or affiliates were negligent in the design, manufacture, or warning of the Micron product.

Customer Responsibility. Customers are responsible for the design, manufacture, and operation of their systems, applications, and products using Micron products. ALL SEMICONDUCTOR PRODUCTS HAVE INHERENT FAILURE RATES AND LIMITED USEFUL LIVES. IT IS THE CUSTOMER'S SOLE RESPONSIBILITY TO DETERMINE WHETHER THE MICRON PRODUCT IS SUITABLE AND FIT FOR THE CUSTOMER'S SYSTEM, APPLICATION, OR PRODUCT. Customers must ensure that adequate design, manufacturing, and operating safeguards are included in customer's applications and products to eliminate the risk that personal injury, death, or severe property or environmental damages will result from failure of any semiconductor component.

Limited Warranty. In no event shall Micron be liable for any indirect, incidental, punitive, special or consequential damages (including without limitation lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort, warranty, breach of contract or other legal theory, unless explicitly stated in a written agreement executed by Micron's duly authorized representative.



DQ Map

Table 3: Component-to-Module DQ Map, Front (R/C - E2)

Component Reference Number	Component DQ	Module DQ	Module Pin Number	Component Reference Number	Component DQ	Module DQ	Module Pin Number
U1	0	7	155	U2	0	15	166
	1	5	148		1	13	159
	2	6	10		2	14	21
	3	4	3		3	12	14
U3	0	23	177	U4	0	31	188
	1	21	170		1	29	181
	2	22	32		2	30	43
	3	20	25		3	28	36
U5	0	CB7	199	U7	0	39	247
	1	CB5	192		1	37	240
	2	CB6	54		2	38	102
	3	CB4	47		3	36	95
U8	0	47	258	U9	0	55	269
	1	45	251		1	53	262
	2	46	113		2	54	124
	3	44	106		3	52	117
U10	0	63	280	U12	0	2	12
	1	61	273		1	1	150
	2	62	135		2	3	157
	3	60	128		3	0	5
U13	0	8	16	U14	0	16	27
	1	10	23		1	18	34
	2	9	161		2	17	172
	3	11	168		3	19	179
U15	0	26	45	U16	0	CB2	56
	1	25	183		1	CB1	194
	2	27	190		2	CB3	201
	3	24	38		3	CB0	49
U17	0	34	104	U18	0	42	115
	1	32	97		1	40	108
	2	35	249		2	43	260
	3	33	242		3	41	253
U19	0	50	126	U20	0	56	130
	1	48	119		1	58	137
	2	51	271		2	57	275
	3	49	264		3	59	282



Table 4: Component-to-Module DQ Map, Back (R/C - E2)

Component Reference Number	Component DQ	Module DQ	Module Pin Number	Component Reference Number	Component DQ	Module DQ	Module Pin Number
U21	0	61	273	U22	0	53	262
	1	63	280		1	55	269
	2	60	128		2	52	117
	3	62	135		3	54	124
U23	0	45	251	U24	0	37	240
	1	47	258		1	39	247
	2	44	106		2	36	95
	3	46	113		3	38	102
U25	0	CB5	192	U26	0	29	181
	1	CB7	199		1	31	188
	2	CB4	47		2	28	36
	3	CB6	54		3	30	43
U27	0	21	170	U28	0	13	159
	1	23	177		1	15	166
	2	20	25		2	12	14
	3	22	32		3	14	21
U29	0	5	148	U30	0	58	137
	1	7	155		1	56	130
	2	4	3		2	59	282
	3	6	10		3	57	275
U31	0	48	119	U32	0	40	108
	1	50	126		1	42	115
	2	49	264		2	41	253
	3	51	271		3	43	260
U33	0	32	97	U34	0	CB1	194
	1	34	104		1	CB2	56
	2	33	242		2	CB0	49
	3	35	249		3	CB3	201
U35	0	25	183	U36	0	18	34
	1	26	45		1	16	27
	2	24	38		2	19	179
	3	27	190		3	17	172
U37	0	10	23	U38	0	1	150
	1	8	16		1	2	12
	2	11	168		2	0	5
	3	9	161		3	3	157



Table 5: Component-to-Module DQ Map, Front (R/C - D3)

Component Reference Number	Component DQ	Module DQ	Module Pin Number	Component Reference Number	Component DQ	Module DQ	Module Pin Number
U1	0	6	10	U2	0	14	21
	1	4	3		1	12	14
	2	7	155		2	15	166
	3	5	148		3	13	159
U3	0	22	32	U4	0	30	43
	1	20	25		1	28	36
	2	23	177		2	31	188
	3	21	170		3	29	181
U5	0	CB6	54	U7	0	38	102
	1	CB4	47		1	36	95
	2	CB7	199		2	39	247
	3	CB5	192		3	37	240
U8	0	46	113	U9	0	54	124
	1	44	106		1	52	117
	2	47	258		2	55	269
	3	45	251		3	53	262
U10	0	62	135	U12	0	2	12
	1	60	128		1	0	5
	2	63	280		2	3	157
	3	61	273		3	1	150
U13	0	10	23	U14	0	18	34
	1	8	16		1	16	27
	2	11	168		2	19	179
	3	9	161		3	17	172
U15	0	26	45	U16	0	CB2	56
	1	24	38		1	CB0	49
	2	27	190		2	CB3	201
	3	25	183		3	CB1	194
U17	0	34	104	U18	0	42	115
	1	32	97		1	40	108
	2	35	249		2	43	260
	3	33	242		3	41	253
U19	0	50	126	U20	0	58	137
	1	48	119		1	56	130
	2	51	271		2	59	282
	3	49	264		3	57	275



Table 6: Component-to-Module DQ Map, Back (R/C - D3)

Component Reference Number	Component DQ	Module DQ	Module Pin Number	Component Reference Number	Component DQ	Module DQ	Module Pin Number
U21	0	60	128	U22	0	52	117
	1	62	135		1	54	124
	2	61	273		2	53	262
	3	63	280		3	55	269
U23	0	44	106	U24	0	36	95
	1	46	113		1	38	102
	2	45	251		2	37	240
	3	47	258		3	39	247
U25	0	CB4	47	U26	0	28	36
	1	CB6	54		1	30	43
	2	CB5	192		2	29	181
	3	CB7	199		3	31	188
U27	0	20	25	U28	0	12	14
	1	22	32		1	14	21
	2	21	170		2	13	159
	3	23	177		3	15	166
U29	0	4	3	U30	0	56	130
	1	6	10		1	58	137
	2	5	148		2	57	275
	3	7	155		3	59	282
U31	0	48	119	U32	0	40	108
	1	50	126		1	42	115
	2	49	264		2	41	253
	3	51	271		3	43	260
U33	0	32	97	U34	0	CB0	49
	1	34	104		1	CB2	56
	2	33	242		2	CB1	194
	3	35	249		3	CB3	201
U35	0	24	38	U36	0	16	27
	1	26	45		1	18	34
	2	25	183		2	17	172
	3	27	190		3	19	179
U37	0	8	16	U38	0	0	5
	1	10	23		1	2	12
	2	9	161		2	1	150
	3	11	168		3	3	157



I_{DD} Specifications

Table 7: DDR4 I_{DD} Specifications and Conditions (0°C ≤ T_C ≤ 85°C) – 128GB (Die Revision B)

Values are for the MT40A8G4 DDR4 TwinDie SDRAM only and are computed from values specified in the 32Gb (8 Gig x 4) component data sheet

Parameter	Symbol	3200	2933	Units
One bank ACTIVATE-PRECHARGE current	I _{CDD0}	3402	3384	mA
One bank ACTIVATE-PRECHARGE, wordline boost, I _{pp} current	I _{CPP0}	234	234	mA
One bank ACTIVATE-READ-PRECHARGE current	I _{CDD1}	3582	3564	mA
Precharge standby current	I _{CDD2N}	3258	3240	mA
Precharge standby ODT current	I _{CDD2NT}	3330	3312	mA
Precharge power-down current	I _{CDD2P}	3096	3096	mA
Precharge quite standby current	I _{CDD2Q}	3168	3168	mA
Active standby current	I _{CDD3N}	3726	3708	mA
Active standby I _{pp} current	I _{CPP3N}	216	216	mA
Active power-down current	I _{CDD3P}	3564	3546	mA
Burst read current	I _{CDD4R}	5418	5274	mA
Burst write current	I _{CDD4W}	5274	5148	mA
Distributed refresh current (1x REF)	I _{CDD5R}	3744	3726	mA
Distributed refresh I _{pp} current (1x REF)	I _{CPP5R}	252	252	mA
Self refresh current: Normal temperature range (0°C to 85°C)	I _{CDD6N}	3528	3528	mA
Self refresh current: Extended temperature range (0°C to 95°C)	I _{CDD6E}	4500	4500	mA
Self refresh current: Reduced temperature range (0°C to 45°C)	I _{CDD6R}	2844	2844	mA
Auto self refresh current (25°C)	I _{CDD6A (25°C)}	2502	2502	mA
Auto self refresh current (45°C)	I _{CDD6A (45°C)}	2844	2844	mA
Auto self refresh current (75°C)	I _{CDD6A (75°C)}	3420	3420	mA
Auto self refresh current (95°C)	I _{CDD6A (95°C)}	4500	4500	mA
Auto self refresh I _{pp} current	I _{CPP6X}	504	504	mA
Bank interleave read current	I _{CDD7}	6606	6480	mA
Bank interleave read I _{pp} current	I _{CPP7}	360	360	mA
Maximum power-down current	I _{CDD8}	2880	2880	mA

Notes: 1. When T_C > 85°C, the I_{DD} and I_{pp} values must be derated. Refer to the base device data sheet I_{DD} and I_{pp} specification tables for derating values for the applicable die-revision.



128GB (x72, TwinDie, ECC, QR) 288-Pin DDR4 LRDIMM I_{DD} Specifications

Table 8: DDR4 I_{DD} Specifications and Conditions (0°C ≤ T_C ≤ 85°C) – 128GB (Die Revision F)

Values are for the MT40A8G4 DDR4 TwinDie SDRAM only and are computed from values specified in the 32Gb (8 Gig x 4) component data sheet

Parameter	Symbol	3200	Units
One bank ACTIVATE-PRECHARGE current	I _{CDD0}	3042	mA
One bank ACTIVATE-PRECHARGE, wordline boost, I _{pp} current	I _{CPP0}	162	mA
One bank ACTIVATE-READ-PRECHARGE current	I _{CDD1}	3240	mA
Precharge standby current	I _{CDD2N}	2862	mA
Precharge standby ODT current	I _{CDD2NT}	2970	mA
Precharge power-down current	I _{CDD2P}	2736	mA
Precharge quite standby current	I _{CDD2Q}	2808	mA
Active standby current	I _{CDD3N}	3132	mA
Active standby I _{pp} current	I _{CPP3N}	144	mA
Active power-down current	I _{CDD3P}	2916	mA
Burst read current	I _{CDD4R}	4338	mA
Burst write current	I _{CDD4W}	3780	mA
Distributed refresh current (1x REF)	I _{CDD5R}	3276	mA
Distributed refresh I _{pp} current (1x REF)	I _{CPP5R}	180	mA
Self refresh current: Normal temperature range (0°C to 85°C)	I _{CDD6N}	3276	mA
Self refresh current: Extended temperature range (0°C to 95°C)	I _{CDD6E}	4608	mA
Self refresh current: Reduced temperature range (0°C to 45°C)	I _{CDD6R}	2088	mA
Auto self refresh current (25°C)	I _{CDD6A (25°C)}	1764	mA
Auto self refresh current (45°C)	I _{CDD6A (45°C)}	2088	mA
Auto self refresh current (75°C)	I _{CDD6A (75°C)}	3204	mA
Auto self refresh current (95°C)	I _{CDD6A (95°C)}	4608	mA
Auto self refresh I _{pp} current	I _{CPP6X}	216	mA
Bank interleave read current	I _{CDD7}	6912	mA
Bank interleave read I _{pp} current	I _{CPP7}	306	mA
Maximum power-down current	I _{CDD8}	2592	mA


Notes: 1. When T_C > 85°C, the I_{DD} and I_{pp} values must be derated. Refer to the base device data sheet I_{DD} and I_{pp} specification tables for derating values for the applicable die-revision.



128GB (x72, TwinDie, ECC, QR) 288-Pin DDR4 LRDIMM Functional Block Diagram

Functional Block Diagram

Figure 3: Functional Block Diagram



Note: 1. The ZQ ball on each DDR4 component is connected to an external 240Ω ±1% resistor that is tied to ground. It is used for the calibration of the component's ODT and output driver.

8000 S. Federal Way, P.O. Box 6, Boise, ID 83707-0006
208-368-4000, micron.com/support
Micron and the Micron logo are trademarks of Micron Technology, Inc.
All other trademarks are the property of their respective owners.

This data sheet contains minimum and maximum limits specified over the power supply and temperature range set forth herein. Although considered final, these specifications are subject to change, as further product development and data characterization sometimes occur.