

Evaluation Kit Based on i.MX 8M Mini Applications Processors

The i.MX 8M Mini EVK is a feature-rich development platform that enables evaluation and development of high-performance, scalable and cost-optimized solutions.

The i.MX 8M Mini EVK hardware and software board support packages provide a comprehensive platform for evaluation of the i.MX 8M Mini and i.MX 8M Mini Lite applications processors utilizing 1, 2, or 4 Arm® Cortex®-A53 cores and 1 Cortex-M4 core. It offers high performance with low power, flexible options for memory and high-speed interfaces, as well as industry-leading audio and video capabilities.

The EVK offers a large assortment of features to support graphics, video, image processing, audio and voice functions. It is complemented by optimized drivers and software to enable a variety of applications for the embedded consumer and industrial markets.

The EVK topology consists of a base board and a compute module. The compute module plugs into the base board, which enables the MIPI-DSI and MIPI-CSI connectors, USB 3.0 connector, and PCIe high-speed interfaces ideal for connected, high performance embedded applications. In addition, the base board has SD/MMC slot, 10/100/1000 Ethernet port, and includes a 3.5mm speaker jack. Included in the box is the MIPI-DSI to HDMI adapter card and miniSAS cable, to provide out-of-the-box display capabilities.

The compute module is a size-optimized design that contains the i.MX 8M Mini applications processor, PMIC, LPDDR4 or DDR4 DRAM, eMMC, and provides wireless connectivity via a Murata SDIO-based Wi-Fi/BT module.

AUDIO, VIDEO, AND GRAPHICS

The EVK includes hardware-accelerated video and graphics capabilities. The integrated video support decodes most relevant video formats such as 264, VP8, and VP9 for video decode, and H.264, VP8 for video encode and renders up to 1080p60 video resolution. Applications such as video streaming HMI, surveillance and robotics can take advantage of the high level of multimedia integration. Proven system solutions for audio and voice enablement are provided through NXP's ecosystem partners.

HMI AND CONNECTIVITY

Today, Human Machine Interface (HMI) applications must respond accurately, and in 4 milliseconds, to touch screen and gesture inputs. Connectivity is a must, demanding increasingly faster and more reliable wired and wireless capabilities, associated with security to protect privacy and sensitive data. The i.MX 8M Mini EVK provides capabilities to develop these key functionalities.



TARGET APPLICATIONS

- ▶ General-purpose Human Machine Interface (HMI) solutions
- Building Automation fire and security panel, elevator control, HVAC control, surveillance monitoring
- Smart Homes surveillance monitoring, video doorbell, voice controlled light switches, smart appliances, smart thermostats
- ▶ Imaging and Machine Vision retail inventory management, thermal/IR scanners, drones, mobile service robots
- ▶ Video Conferencing two-way 1080p video conferencing for industrial, consumer or medical applications
- Audio Entertainment soundbars, audio video receivers, wireless speakers, portable music players, public address systems

i.MX 8M MINI EVK COMPUTE MODULE

Part Number	8MMINILPD4-EVK	8MMINID4-EVK
Memory	• LPDDR4 x32 w/2 GB	DDR4 x16 w/2 GBMicroSD (external)
	SD/MMC connector QSPI w/64 MB	
Processor	 i.MX 8M Mini Quad applications processor 4x Arm Cortex-A53 @ 1.8 GHz Arm Cortex-M4 @ 400 MHz 	
Power Management	Murata Type 1PJ	Murata Type 1MW
Wireless	 Wi-Fi 802.11 a/b/g/n/ac MIMO 2x2 Onboard chip antenna External antenna connector 	

i.MX 8M MINI EVK CONTENTS

- ▶ i.MX 8M Mini EVK base board and compute module
- ▶ Quick Start Guide
- ▶ USB 3.0 Type C to Type A
- ▶ USB 2.0 Type A to Type Micro
- ▶ USB Type C Power Supply
- ▶ HDMI MIPI-DSI to HDMI Adapter Card and miniSAS Cable

SOFTWARE AND TOOLS

The i.MX 8M Mini EVK comes pre-installed with a boot image flashed. Hardware design files, software tools and board support packages (BSPs) for Linux, Android and FreeRTOS are available from NXP to use as a reference for starting designs. Other reference designs and tools are also available from NXP's ecosystem partners. Additional information can be found at www.nxp.com/iMX8MMiniEVK.

There are a number of accessory boards that pair with the i.MX 8M Mini EVK including support for cameras and displays. Visit www.nxp.com/i.MX8-ACCESSORY-BOARDS to see the complete list.

i.MX 8M MINI EVK DISPLAY BOARD

Description	Part Number	Photo
MIPI-DSI OLED Display	MX8_DSI_OLED1	


i.MX 8M MINI EVK BASE BOARD

Display/ Camera Connectors	MIPI-CSI Camera mini-SAS connector MIPI-DSI Display mini-SAS connector
Audio	 Audio DAC 24-bit 192 kHz stereo HP Jack 3.5 mm audio connector Board expansion connector for audio interfaces
Connectivity	10/100/1000 EthernetUSB 3.0 Type C connectorPCle M.2 interface
Debug	JTAG connector UART via USB
Tools and OS support	LinuxAndroidFreeRTOS

Description

MIPI-DSI to

HDMI Adapter



i.MX 8M MINI EVK ACCESSORY BOARDS

Part Number

(IMX-MIPI-HDMI

included with the

Evaluation Kit)



Photo

ORDERING INFORMATION

Part Number: 8MMINILPD4-EVK or 8MMINID4-EVK Memory: 2 GB LPDDR4, 16 GB eMMC 5.0/5.1

www.nxp.com/iMX8MMiniEVK and imxcommunity.org

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. Arm, Cortex and Keil are registered trademarks of Arm Limited (or its subsidiaries) in the EU and/or elsewhere. Mbed is a trademark of Arm Limited (or its subsidiaries) in the EU and/or elsewhere. All rights reserved. © 2019 NXP B.V.

Document Number: IMX8MMINIEVKFSA4 REV 2