

PMEM1505NG

NPN transistor/Schottky rectifier module

Rev. 02 — 31 August 2009

Product data sheet

1. Product profile

1.1 General description

Combination of an NPN transistor with low V_{CEsat} and high current capability and a planar Schottky barrier rectifier with an integrated guard ring for stress protection in a SOT353 (SC-88A) small plastic package. PNP complement: PMEM1505PG

1.2 Features

- 300 mW total power dissipation
- Current capability up to 0.5 A
- Reduces printed-circuit board area required
- Reduces pick and place costs
- Small plastic SMD package
- Transistor
 - ◆ Low collector-emitter saturation voltage.
- Diode
 - ◆ Ultra high-speed switching
 - ◆ Very low forward voltage
 - ◆ Guard ring protected

1.3 Applications

- DC-to-DC converters
- General purpose load drivers
- MOSFET drivers
- Inductive load drivers
- Reverse polarity protection circuits

1.4 Quick reference data

Table 1. Quick reference data

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
NPN transistor						
V_{CEO}	collector-emitter voltage	open base	-	-	15	V
I_C	collector current (DC)	continuous	[1]	-	0.5	A
Schottky barrier rectifier						
V_R	continuous reverse voltage		-	-	20	V
I_F	continuous forward current		-	-	0.5	A

[1] Mounted on a FR4 printed-circuit board, single-sided copper, tin-plated, standard footprint for SOT353.

2. Pinning information

Table 2. Discrete pinning

Pin	Description	Simplified outline	Symbol
1	anode		
5	cathode		
4	collector		
2	base		
3	emitter		

sym023

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
PMEM1505NG	-	plastic surface mounted package; 5 leads	SOT353

4. Marking

Table 4. Marking

Type number	Marking code ^[1]
PMEM1505NG	L7*

- [1] * = p: made in Hong Kong
 * = t: made in Malaysia
 * = W: made in China

5. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
NPN transistor					
V_{CBO}	collector-base voltage	open emitter	-	15	V
V_{CEO}	collector-emitter voltage	open base	-	15	V
V_{EBO}	emitter-base voltage	open collector	-	6	V
I_C	collector current (DC)	continuous	[1]	0.5	A
		continuous	[2]	0.6	A
		continuous; $T_s \leq 55\text{ }^\circ\text{C}$	[3]	1	A
I_{CM}	peak collector current		-	1	A
I_{BM}	peak base current		-	100	mA

Table 5. Limiting values ...continued
In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
P _{tot}	total power dissipation	T _{amb} ≤ 25 °C [1]	-	200	mW
		T _{amb} ≤ 25 °C [2]	-	250	mW
		T _s ≤ 55 °C [3]	-	800	mW
T _j	junction temperature		-	150	°C
Schottky barrier rectifier					
V _R	continuous reverse voltage		-	20	V
I _F	continuous forward current		-	0.5	A
I _{FSM}	non-repetitive peak forward current	t = 8.3 ms; square wave	-	5	A
P _{tot}	total power dissipation	T _{amb} ≤ 25 °C [1]	-	100	mW
		T _{amb} ≤ 25 °C [2]	-	200	mW
		T _s ≤ 55 °C [3]	-	800	mW
T _j	junction temperature		[2]	125	°C
Combined device					
P _{tot}	total power dissipation	T _{amb} ≤ 25 °C [2]	-	300	mW
T _{stg}	storage temperature		-65	+150	°C
T _{amb}	operating ambient temperature		[2]	+125	°C

- [1] Mounted on a FR4 printed-circuit board, single-sided copper, tin-plated, standard footprint for SOT353.
- [2] Device mounted on a printed-circuit board, single-sided copper, tin-plated, 1 cm² mounting pad for both collector and cathode.
- [3] Solder point of collector or cathode tab.

6. Thermal characteristics

Table 6. Thermal characteristics[1]

Symbol	Parameter	Conditions	Typ	Unit
Single device				
R _{th(j-s)}	thermal resistance from junction to solder point	in free air	[2] 120	K/W
R _{th(j-a)}	thermal resistance from junction to ambient	in free air	[3] 395	K/W
			[4] 495	K/W
Combined device				
R _{th(j-a)}	thermal resistance from junction to ambient	in free air	[5] 410	K/W


- [1] For Schottky barrier rectifiers thermal run-away has to be considered, as in some applications the reverse power losses P_R are a significant part of the total power losses. Nomograms for determining the reverse power losses P_R and I_{F(AV)} rating will be available on request.
- [2] Solder point of collector or cathode tab.
- [3] Device mounted on a printed-circuit board, single-sided copper, tin-plated, 1 cm² mounting pad for both collector and cathode.
- [4] Mounted on a FR4 printed-circuit board, single-sided copper, tin-plated, standard footprint for SOT353.
- [5] Mounted on a ceramic printed-circuit board, single-sided copper, tin-plated, standard footprint.

7. Characteristics

Table 7. Characteristics
 $T_{amb} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Conditions	Min	Typ	Max	Unit	
NPN transistor							
I_{CBO}	collector-base cut-off current	$V_{CB} = 15\text{ V}; I_E = 0\text{ A}$	-	-	100	nA	
		$V_{CB} = 15\text{ V}; I_E = 0\text{ A}; T_j = 150\text{ }^{\circ}\text{C}$	-	-	50	μA	
I_{EBO}	emitter-base cut-off current	$V_{EB} = 5\text{ V}; I_C = 0\text{ A}$	-	-	100	nA	
h_{FE}	DC current gain	$V_{CE} = 2\text{ V}; I_C = 10\text{ mA}$	200	-	-		
		$V_{CE} = 2\text{ V}; I_C = 100\text{ mA}$	150	-	-		
		$V_{CE} = 2\text{ V}; I_C = 500\text{ mA}$	90	-	-		
V_{CEsat}	collector-emitter saturation voltage	$I_C = 10\text{ mA}; I_B = 0.5\text{ mA}$	-	-	25	mV	
		$I_C = 200\text{ mA}; I_B = 10\text{ mA}$	-	-	150	mV	
		$I_C = 500\text{ mA}; I_B = 50\text{ mA}$	-	-	250	mV	
R_{CEsat}	equivalent on-resistance	$I_C = 500\text{ mA}; I_B = 50\text{ mA}$	[1]	-	300	$< 500\text{ m}\Omega$	
V_{BEsat}	base-emitter saturation voltage	$I_C = 500\text{ mA}; I_B = 50\text{ mA}$	[1]	-	-	1.1 V	
V_{BEon}	base-emitter turn-on voltage	$V_{CE} = 2\text{ V}; I_C = 100\text{ mA}$	[1]	-	-	0.9 V	
f_T	transition frequency	$V_{CE} = 5\text{ V}; I_C = 100\text{ mA}; f = 100\text{ MHz}$	250	420	-	MHz	
C_c	collector capacitance	$V_{CB} = 10\text{ V}; I_E = I_e = 0\text{ A}; f = 1\text{ MHz}$	-	4.4	6	pF	
Schottky barrier rectifier							
V_F	continuous forward voltage	see Figure 1					
		$I_F = 10\text{ mA}$	[1]	-	240	270	mV
		$I_F = 100\text{ mA}$	[1]	-	300	350	mV
		$I_F = 500\text{ mA}$	[1]	-	400	460	mV
I_R	reverse current	see Figure 2					
		$V_R = 5\text{ V}$	[1]	-	5	10	μA
		$V_R = 8\text{ V}$	[1]	-	7	20	μA
		$V_R = 15\text{ V}$	[1]	-	10	50	μA
C_d	diode capacitance	$V_R = 5\text{ V}; f = 1\text{ MHz};$ see Figure 3	-	19	25	pF	


[1] Pulse test: $t_p \leq 300\text{ }\mu\text{s}; \delta \leq 0.02$



Schottky barrier rectifier

- (1) $T_{amb} = 125\text{ °C}$
- (2) $T_{amb} = 85\text{ °C}$
- (3) $T_{amb} = 25\text{ °C}$


Fig 1. Forward current as a function of forward voltage; typical values



Schottky barrier rectifier


- (1) $T_{amb} = 125\text{ °C}$
- (2) $T_{amb} = 85\text{ °C}$
- (3) $T_{amb} = 25\text{ °C}$

Fig 2. Reverse current as a function of reverse voltage; typical values



Schottky barrier rectifier; $f = 1\text{ MHz}$; $T_{amb} = 25\text{ °C}$


Fig 3. Diode capacitance as a function of reverse voltage; typical values



NPN transistor; $V_{CE} = 2\text{ V}$


- (1) $T_{amb} = 150\text{ °C}$
- (2) $T_{amb} = 25\text{ °C}$
- (3) $T_{amb} = -55\text{ °C}$

Fig 4. DC current gain as a function of collector current; typical values




NPN transistor; $V_{CE} = 2\text{ V}$
 (1) $T_{amb} = -55\text{ }^\circ\text{C}$
 (2) $T_{amb} = 25\text{ }^\circ\text{C}$
 (3) $T_{amb} = 150\text{ }^\circ\text{C}$

Fig 5. Base-emitter voltage as a function of collector current; typical values



NPN transistor; $I_C/I_B = 20$
 (1) $T_{amb} = 150\text{ }^\circ\text{C}$
 (2) $T_{amb} = 25\text{ }^\circ\text{C}$
 (3) $T_{amb} = -55\text{ }^\circ\text{C}$


Fig 6. Collector-emitter saturation voltage as a function of collector current; typical values



NPN transistor; $I_C/I_B = 20$
 (1) $T_{amb} = 150\text{ }^\circ\text{C}$
 (2) $T_{amb} = 25\text{ }^\circ\text{C}$
 (3) $T_{amb} = -55\text{ }^\circ\text{C}$

Fig 7. Equivalent on-resistance as a function of collector current; typical values

8. Application information



9. Package outline

Plastic surface-mounted package; 5 leads

SOT353




Fig 10. Package outline

10. Revision history

Table 8. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
PMEM1505NG_2	20090831	Product data	-	PMEM1505NG_1
Modifications:	<ul style="list-style-type: none">• This data sheet was changed to reflect the new company name NXP Semiconductors, including new legal definitions and disclaimers. No changes were made to the technical content.• Table 2 “Discrete pinning”: amended• Figure 10 “Package outline”: updated			
PMEM1505NG_1	20040525	Product data	-	-

11. Legal information

11.1 Data sheet status

Document status ^{[1][2]}	Product status ^[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

11.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

11.3 Disclaimers

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental

damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

11.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

12. Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

13. Contents

1 Product profile 1

1.1 General description. 1

1.2 Features 1

1.3 Applications 1

1.4 Quick reference data. 1

2 Pinning information. 2

3 Ordering information. 2

4 Marking. 2

5 Limiting values. 2

6 Thermal characteristics. 3

7 Characteristics. 4

8 Application information. 7

9 Package outline 8

10 Revision history. 9

11 Legal information. 10

11.1 Data sheet status 10

11.2 Definitions 10

11.3 Disclaimers 10

11.4 Trademarks 10

12 Contact information. 10

13 Contents 11

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.



© NXP B.V. 2009. **All rights reserved.**

For more information, please visit: <http://www.nxp.com>
 For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 31 August 2009
 Document identifier: PMEM1505NG_2