




M86296G12 (Active)

C2K 900MHz Device with options: 16 VOIP channels USB2.0, USB3.0 DECT ECC RGMII (X3) SPI (X2)



Package :
[FBGA625](#)
 FCPBGA 625 21*21*2.4 P.8

[Buy Options](#) | [Environmental Information](#) | [Quality Information](#) | [Shipping Information](#)

Environmental Information

Material Declaration	PbFree	EU RoHS	Halogen Free	RHF Indicator	2nd Level Interconnect	REACH SVHC	Weight (mg)
M86296G12 (935323612557)	Yes	Yes	Yes	D	e1	REACH SVHC	3110.0

Quality Information

Material Declaration	Safe Assure Functional Safety	Moisture Sensitivity Level (MSL)	Peak Package Body Temperature (PPT) (C°)	Maximum Time at Peak Temperatures (s)
		Lead Free Soldering	Lead Free Soldering	Lead Free Soldering
M86296G12 (935323612557)	No	3	250	30

Shipping Information

Part Number	Harmonized Tariff (US) Disclaimer	Export Control Classification Number (US)	CCATS
M86296G12 (935323612557)	854231	5A002A1	G142070

ABOUT NXP

- [Investors](#)
- [Press, News, Blogs](#)
- [Careers](#)

RESOURCES

- [Mobile Apps](#)
- [Contact Us](#)

FOLLOW US



News 26 Feb 2019 [<](#) [>](#)

NXP Announces K32 Energy-efficient Microcontroller Series for Advanced Security and Physical Protection

[Read More](#)