

## Molded Inductors, Axial Leads, High Frequency and Noise Suppression Applications




### FEATURES

- Accurate dimensions
- Superior moisture protection
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

These inductors have copper winding on magnetic core structure.

### DIMENSIONS in millimeters ( $\pm 0.5$ )



### STANDARD ELECTRICAL SPECIFICATIONS

MODEL	INDUCTANCE RANGE $\mu\text{H}$	RATED POWER $P_{70^\circ\text{C}}$ W	LIMITING ELEMENT VOLTAGE $V_{\text{RMS}}$	TOLERANCE <sup>(1)</sup> $\pm \%$	Q RANGE	I RANGE mA
TR025	1 to 8200	0.500	500	10	25 to 85	80 to 1960

**Note**

<sup>(1)</sup>  $\pm 10 \%$  for  $1 \mu\text{H} < L \leq 8200 \mu\text{H}$ . On request:  $\pm 5 \%$  for  $1 \mu\text{H} < L \leq 1000 \mu\text{H}$

### MECHANICAL SPECIFICATIONS

Coating	Molded epoxy
Weight	2.7 g

### PACKAGING

Standard: tape and reel 500 pieces, code R10 (R)  
On request: 250 pieces tape in box "ammopack", code A15 (B)

### ENVIRONMENTAL SPECIFICATIONS

Operating temperature range	0 °C to +70 °C
Temperature limits	-55 °C to +125 °C

### MARKING

Standard:  
print marked-manufacturer, inductance value, tolerance

### ORDERING INFORMATION (part number)

T	R	0	2	5	1	0	2	K	A	1	0						
MODEL		STYLE			VALUE			TOLERANCE		PACKAGING			SPECIAL				
TR		025			From 1 $\mu\text{H}$ to 8200 $\mu\text{H}$ <b>102</b> = 1 MH			K: $\pm 10 \%$ On request: J: $\pm 5 \%$		R10 = reel 500 pieces On request: A15 = ammopack 250 pieces			Special code given by Vishay				

### PART NUMBER DESCRIPTION (for information only)

TR	025	1 MH	10 %	R		e1
MODEL	STYLE	VALUE	TOLERANCE	PACKAGING	SPECIAL	LEAD (Pb)-FREE



STANDARD VALUES						
INDUCTANCE VALUE μH	TOLERANCE %	Q MIN.	TEST FREQUENCY MHz	RESISTANCE MAX. Ω	SRF MIN. MHz	I MAX. mA
1	± 10	55	25	0.14	200	1900
1.2	± 10	30	7.9	0.19	180	1640
1.5	± 10	30	7.9	0.28	160	1340
1.8	± 10	30	7.9	0.37	150	1160
2.2	± 10	30	7.9	0.50	135	1000
2.7	± 10	30	7.9	0.65	120	875
3.3	± 10	30	7.9	1	105	710
3.9	± 10	30	7.9	1.2	100	645
4.7	± 10	30	7.9	1.8	90	530
5.6	± 10	25	7.9	0.13	55	1960
6.8	± 10	25	7.9	0.20	50	1580
8.2	± 10	25	7.9	0.22	44	1510
10	± 10	25	7.9	0.26	42	1380
12	± 10	35	2.5	0.45	34	1060
15	± 10	35	2.5	0.52	32	980
18	± 10	40	2.5	0.70	28	840
22	± 10	50	2.5	1	24	705
27	± 10	50	2.5	1.3	22	620
33	± 10	50	2.5	1.5	20	575
39	± 10	60	2.5	2	16	500
47	± 10	85	2.5	2.2	18	475
56	± 10	85	2.5	2.3	16	465
68	± 10	85	2.5	3	14	405
82	± 10	85	2.5	3.5	12.5	375
100	± 10	80	2.5	3.8	11	365
120	± 10	75	0.79	4.2	10	345
150	± 10	60	0.79	5	8.3	315
180	± 10	65	0.79	5.3	6	305
220	± 10	65	0.79	5.9	5.5	290
270	± 10	65	0.79	6.6	5	275
330	± 10	60	0.79	7.2	4.2	260
390	± 10	60	0.79	8.6	3.9	240
470	± 10	65	0.79	9	3.6	235
560	± 10	65	0.79	9.7	3.4	225
680	± 10	60	0.79	10	3.1	220
820	± 10	60	0.79	12	2.6	200
1000	± 10	60	0.79	15	2.6	180
1200	± 10	50	0.25	18	2.3	165
1500	± 10	60	0.25	21	2.1	150
1800	± 10	60	0.25	23	2	145
2200	± 10	60	0.25	26	1.7	135
2700	± 10	60	0.25	33	1.7	120
3300	± 10	55	0.25	39	1.2	110
3900	± 10	55	0.25	44	1	105
4700	± 10	55	0.25	64	0.9	85
5600	± 10	55	0.25	66	0.85	85
6800	± 10	50	0.25	70	0.80	82
8200	± 10	60	0.25	72	0.75	80



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.