



1 - 1/4" Rectangular Multi-Turn Cermet

FEATURES

- Improved Wiper
- Unique "T" Slider Block Design Assure Excellent Setability and Stability
- CRV of 3% or 3Ω
- Temperature coefficient of 100 ppm/°C
- RT Tolerance ± 10% STD (± 5% Available)



DIMENSIONS in inches (millimeters)



ELECTRICAL SPECIFICATIONS	
Resistance Range	10Ω thru 2MΩ
Standard Resistance Tolerance	10% (para. 3.7.1)
End Resistance	2% maximum (para. 3.7.2)
Actual Effective Electrical Travel	20 turns nominal (para. 3.8)
Contact Resistance Variation	3% or 3Ω, whichever is greater (para. 3.9)
Dielectric Withstanding Voltage	1000 VAC at sea level, 350 VAC at 80,000 feet (para. 3.10) 24,400 meters)
Insulation Resistance	1000MΩ (para. 3.11)
Power Rating	1.0 watt at 85°C derated linearly to zero watts at 150°C (para. 3.5) maximum voltage not to exceed 400 volts
Temperature coefficient of resistance	± 100ppm/°C 100Ω to 2MΩ - 100 to 200ppm/°C 10Ω, 20Ω and 50Ω



MECHANICAL SPECIFICATIONS	
Stops	Wiper idles against stops (para. 3.4.7.1)
Operating Torque	5 oz-in (360 gm-cm) maximum (para. 3.12.1)
Rotational Life	200 cycles minimum with loaded circuit, maximum change in resistance 2% (para 3.23) or 500 cycles minimum without discontinuity unloaded
Weight	0.116 oz (3.3 grams) maximum

ENVIRONMENTAL SPECIFICATIONS			
		MAXIMUM TOTAL RESISTANCE	CHANGE SETTING
Operating Temperature Range	- 55°C to + 150°C	-	-
Salt Spray	96 hours (para. 3.18)	-	-
Terminal Strength	2lbs (900gms) minimum push/pull (para. 3.24)	-	-
Sealed	All units sealed to permit cleaning in common solvents immersion	-	-
Thermal Shock	- 65°C to + 125°C (para. 3.13)	2%	1%
Shock	100g's 6ms (para 3.16)	1%	1%
Vibration	30g's 10 to 2000Hz (para. 3.17)	1%	1%
Load Life	1000 hours (para. 3.20)	3%	1%
Low Temperature Operation	- 55°C (para. 3.21)	2%	2%
High Temperature Exposure	+ 150°C (para. 3.22)	3%	2%
Resistance to Solder Heat	350°C for 3 seconds (para. 3.19)	1%	-

MARKING

Unit Identification: Manufacturer's name and part number including EIA resistance code, date code, circuit diagram and military style designation as applicable

ORDERING INFORMATION			
70 MODEL	L TERMINAL STYLE	103 EIA RESISTANCE CODE	T000 SPECIAL (omit if standard)
	L = Leadwire Y = Printed circuit pins		T601 Panel mount added to terminal style L

SAP PART NUMBERING GUIDELINES														
M	7	0	L	1	0	3	K	B	4	0	□	□	□	□
MODEL			STYLE	OHMIC VALUE			TOL	PACKAGING CODE			SPECIAL (IF APPLICABLE)			
See the end of this data book for conversion tables														



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.