





## High Speed Optocoupler, 1 MBd, Photodiode with Transistor Output, 110 °C Rated



### FEATURES

- Operating temperature from -55 °C to +110 °C
- Isolation test voltages: 5300 V<sub>RMS</sub>
- TTL compatible
- High bit rates: 1 MBd
- Bandwidth 2 MHz
- Open-collector output
- External base wiring possible
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

### DESCRIPTION

The 6N1135 and 6N1136 are 110 °C rated optocouplers with a GaAlAs infrared emitting diode, optically coupled with an integrated photo detector which consists of a photo diode and a high-speed transistor in a DIP-8 plastic package.

Signals can be transmitted between two electrically separated circuits up to frequencies of 2 MHz. The potential difference between the circuits to be coupled should not exceed the maximum permissible reference voltages.

### AGENCY APPROVALS

- UL1577 (pending)
- DIN EN 60747-5-5 (VDE 0884) (pending)
- cUL (pending)
- CQC (pending)

### ORDERING INFORMATION




6 N 1 1 3 # -

PART NUMBER

X 0 0 # T

PACKAGE OPTION

TAPE AND REEL



| AGENCY CERTIFIED/PACKAGE | CTR (%)      |              |
|--------------------------|--------------|--------------|
| <b>UL</b>                | <b>≥ 7</b>   | <b>≥ 19</b>  |
| DIP-8                    | 6N1135       | 6N1136       |
| DIP-8, 400 mil, option 6 | 6N1135-X006  | 6N1136-X006  |
| SMD-8, option 9          | 6N1135-X009T | 6N1136-X009T |

### ABSOLUTE MAXIMUM RATINGS (T<sub>amb</sub> = 25 °C, unless otherwise specified)

| PARAMETER                     | TEST CONDITION            | SYMBOL            | VALUE      | UNIT |
|-------------------------------|---------------------------|-------------------|------------|------|
| <b>INPUT</b>                  |                           |                   |            |      |
| Reverse voltage               |                           | V <sub>R</sub>    | 5          | V    |
| Forward current               |                           | I <sub>F</sub>    | 25         | mA   |
| Peak forward current          | t = 1 ms, duty cycle 50 % | I <sub>FM</sub>   | 50         | mA   |
| Maximum surge forward current | t ≤ 1 μs, 300 pulses/s    | I <sub>FSM</sub>  | 1          | A    |
| Thermal resistance            |                           | R <sub>th</sub>   | 700        | K/W  |
| Power dissipation             | T <sub>amb</sub> = 70 °C  | P <sub>diss</sub> | 45         | mW   |
| <b>OUTPUT</b>                 |                           |                   |            |      |
| Supply voltage                |                           | V <sub>CC</sub>   | -0.5 to 15 | V    |
| Output voltage                |                           | V <sub>O</sub>    | -0.5 to 15 | V    |
| Emitter base voltage          |                           | V <sub>EBO</sub>  | 5          | V    |
| Output current                |                           | I <sub>O</sub>    | 8          | mA   |
| Maximum Output current        |                           |                   | 16         | mA   |



| ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                                  |            |             |                    |
|-------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|------------|-------------|--------------------|
| PARAMETER                                                                                       | TEST CONDITION                                                                   | SYMBOL     | VALUE       | UNIT               |
| <b>OUTPUT</b>                                                                                   |                                                                                  |            |             |                    |
| Base current                                                                                    |                                                                                  | $I_B$      | 5           | mA                 |
| Thermal resistance                                                                              |                                                                                  |            | 300         | K/W                |
| Power dissipation                                                                               | $T_{amb} = 70\text{ }^{\circ}\text{C}$                                           | $P_{diss}$ | 100         | mW                 |
| <b>COUPLER</b>                                                                                  |                                                                                  |            |             |                    |
| Isolation test voltage (between emitter and detector climate per DIN 50014 part 2, Nov. 74)     | $t = 1\text{ min}$                                                               | $V_{ISO}$  | 5300        | $V_{RMS}$          |
| Storage temperature range                                                                       |                                                                                  | $T_{stg}$  | -55 to +150 | $^{\circ}\text{C}$ |
| Ambient temperature range                                                                       |                                                                                  | $T_{amb}$  | -55 to +100 | $^{\circ}\text{C}$ |
| Soldering temperature <sup>(1)</sup>                                                            | Max. $\leq 10\text{ s}$ , dip soldering<br>$\geq 0.5\text{ mm}$ from case bottom | $T_{sld}$  | 260         | $^{\circ}\text{C}$ |

**Notes**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.
- <sup>(1)</sup> Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).

| ELECTRICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                           |        |                           |      |       |      |                        |
|---------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|--------|---------------------------|------|-------|------|------------------------|
| PARAMETER                                                                                         | TEST CONDITION                                                            | PART   | SYMBOL                    | MIN. | TYP.  | MAX. | UNIT                   |
| <b>INPUT</b>                                                                                      |                                                                           |        |                           |      |       |      |                        |
| Forward voltage                                                                                   | $I_F = 1.6\text{ mA}$                                                     |        | $V_F$                     | -    | 1.6   | 1.9  | V                      |
| Breakdown voltage                                                                                 | $I_R = 10\text{ }\mu\text{A}$                                             |        | $V_{BR}$                  | 5    | -     | -    | V                      |
| Reverse current                                                                                   | $V_R = 5\text{ V}$                                                        |        | $I_R$                     | -    | 0.5   | 10   | $\mu\text{A}$          |
| Capacitance                                                                                       | $V_R = 0\text{ V}$ , $f = 1\text{ MHz}$                                   |        | $C_I$                     | -    | 125   | -    | pF                     |
| Temperature coefficient, forward voltage                                                          | $I_F = 1.6\text{ mA}$                                                     |        | $\Delta V_F / \Delta T_A$ | -    | - 1.7 | -    | mV/ $^{\circ}\text{C}$ |
| <b>OUTPUT</b>                                                                                     |                                                                           |        |                           |      |       |      |                        |
| Logic low supply current                                                                          | $I_F = 1.6\text{ mA}$ , $V_O = \text{open}$ ,<br>$V_{CC} = 15\text{ V}$   |        | $I_{CCL}$                 | -    | 150   | -    | $\mu\text{A}$          |
| Logic high supply current                                                                         | $I_F = 0\text{ mA}$ , $V_O = \text{open}$ ,<br>$V_{CC} = 15\text{ V}$     |        | $I_{CCH}$                 | -    | 0.01  | 1    | $\mu\text{A}$          |
| Output voltage, output low                                                                        | $I_F = 16\text{ mA}$ , $V_{CC} = 4.5\text{ V}$ ,<br>$I_O = 1.1\text{ mA}$ | 6N1135 | $V_{OL}$                  | -    | 0.1   | 0.4  | V                      |
|                                                                                                   | $I_F = 16\text{ mA}$ , $V_{CC} = 4.5\text{ V}$ ,<br>$I_O = 2.4\text{ mA}$ | 6N1136 | $V_{OL}$                  | -    | 0.1   | 0.4  | V                      |
| Output current, output high                                                                       | $I_F = 0\text{ mA}$ , $V_O = V_{CC} = 5.5\text{ V}$                       |        | $I_{OH}$                  | -    | 3     | 500  | nA                     |
|                                                                                                   | $I_F = 0\text{ mA}$ , $V_O = V_{CC} = 15\text{ V}$                        |        | $I_{OH}$                  | -    | 0.01  | 1    | $\mu\text{A}$          |
| <b>COUPLER</b>                                                                                    |                                                                           |        |                           |      |       |      |                        |
| Capacitance (input to output)                                                                     | $f = 1\text{ MHz}$                                                        |        | $C_{IO}$                  | -    | 0.6   | -    | pF                     |

**Note**

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

| CURRENT TRANSFER RATIO |                                                                          |        |        |      |      |      |      |
|------------------------|--------------------------------------------------------------------------|--------|--------|------|------|------|------|
| PARAMETER              | TEST CONDITION                                                           | PART   | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Current transfer ratio | $I_F = 16\text{ mA}$ , $V_O = 0.4\text{ V}$ ,<br>$V_{CC} = 4.5\text{ V}$ | 6N1135 | CTR    | 7    | 16   | -    | %    |
|                        |                                                                          | 6N1136 | CTR    | 19   | 35   | -    | %    |
|                        | $I_F = 16\text{ mA}$ , $V_O = 0.5\text{ V}$ ,<br>$V_{CC} = 4.5\text{ V}$ | 6N1135 | CTR    | 5    | -    | -    | %    |
|                        |                                                                          | 6N1136 | CTR    | 15   | -    | -    | %    |

**SWITCHING CHARACTERISTICS**

| PARAMETER   | TEST CONDITION                                                               | PART   | SYMBOL    | MIN. | TYP. | MAX. | UNIT          |
|-------------|------------------------------------------------------------------------------|--------|-----------|------|------|------|---------------|
| High to low | $I_F = 16 \text{ mA}$ , $V_{CC} = 5 \text{ V}$ , $R_L = 4.1 \text{ k}\Omega$ | 6N1135 | $t_{PHL}$ | -    | 0.3  | 1.5  | $\mu\text{s}$ |
|             | $I_F = 16 \text{ mA}$ , $V_{CC} = 5 \text{ V}$ , $R_L = 1.9 \text{ k}\Omega$ | 6N1136 | $t_{PHL}$ | -    | 0.2  | 0.8  | $\mu\text{s}$ |
| Low to high | $I_F = 16 \text{ mA}$ , $V_{CC} = 5 \text{ V}$ , $R_L = 4.1 \text{ k}\Omega$ | 6N1135 | $t_{PLH}$ | -    | 0.3  | 1.5  | $\mu\text{s}$ |
|             | $I_F = 16 \text{ mA}$ , $V_{CC} = 5 \text{ V}$ , $R_L = 1.9 \text{ k}\Omega$ | 6N1136 | $t_{PLH}$ | -    | 0.2  | 0.8  | $\mu\text{s}$ |




Fig. 1 - Switching Times

**COMMON MODE TRANSIENT IMMUNITY**

| PARAMETER | TEST CONDITION                                                                                               | PART   | SYMBOL   | MIN. | TYP. | MAX. | UNIT                   |
|-----------|--------------------------------------------------------------------------------------------------------------|--------|----------|------|------|------|------------------------|
| High      | $I_F = 0 \text{ mA}$ , $V_{CM} = 10 \text{ V}_{P-P}$ , $V_{CC} = 5 \text{ V}$ , $R_L = 4.1 \text{ k}\Omega$  | 6N1135 | $ CM_H $ | -    | 1000 | -    | $\text{V}/\mu\text{s}$ |
|           | $I_F = 0 \text{ mA}$ , $V_{CM} = 10 \text{ V}_{P-P}$ , $V_{CC} = 5 \text{ V}$ , $R_L = 1.9 \text{ k}\Omega$  | 6N1136 | $ CM_H $ | -    | 1000 | -    | $\text{V}/\mu\text{s}$ |
| Low       | $I_F = 16 \text{ mA}$ , $V_{CM} = 10 \text{ V}_{P-P}$ , $V_{CC} = 5 \text{ V}$ , $R_L = 4.1 \text{ k}\Omega$ | 6N1135 | $ CM_L $ | -    | 1000 | -    | $\text{V}/\mu\text{s}$ |
|           | $I_F = 16 \text{ mA}$ , $V_{CM} = 10 \text{ V}_{P-P}$ , $V_{CC} = 5 \text{ V}$ , $R_L = 1.9 \text{ k}\Omega$ | 6N1136 | $ CM_L $ | -    | 1000 | -    | $\text{V}/\mu\text{s}$ |




Fig. 2 - Common-Mode Interference Immunity



## SAFETY AND INSULATION RATINGS

| PARAMETER                                                                              | TEST CONDITION                                         | SYMBOL     | MIN.      | TYP.          | MAX. | UNIT              |
|----------------------------------------------------------------------------------------|--------------------------------------------------------|------------|-----------|---------------|------|-------------------|
| Climatic classification                                                                | According to IEC 68 part 1                             |            | -         | 55 / 110 / 21 | -    |                   |
| Pollution degree (DIN VDE 0109)                                                        |                                                        |            | -         | 2             | -    |                   |
| Comparative tracking index per DIN IEC112/VDE 0303 part 1, group IIIa per DIN VDE 6110 |                                                        | CTI        | 175       | -             | 399  |                   |
| $V_{IOTM}$                                                                             |                                                        | $V_{IOTM}$ | 8000      | -             | -    | V                 |
| $V_{IORM}$                                                                             |                                                        | $V_{IORM}$ | 630       | -             | -    | V                 |
| Isolation resistance                                                                   | $V_{IO} = 500 \text{ V}, T_{amb} = 25^\circ \text{C}$  | $R_{IO}$   | $10^{12}$ | -             | -    | $\Omega$          |
|                                                                                        | $V_{IO} = 500 \text{ V}, T_{amb} = 100^\circ \text{C}$ | $R_{IO}$   | $10^{11}$ | -             | -    | $\Omega$          |
| $P_{SI}$                                                                               |                                                        | $P_{SI}$   | -         | -             | 500  | mA                |
| $I_{SI}$                                                                               |                                                        | $I_{SI}$   | -         | -             | 300  | mW                |
| $T_{SI}$                                                                               |                                                        | $T_{SI}$   | -         | -             | 175  | $^\circ \text{C}$ |
| Creepage distance                                                                      |                                                        |            | 8         | -             | -    | mm                |
| Clearance distance                                                                     |                                                        |            | 7         | -             | -    | mm                |
| Insulation thickness                                                                   |                                                        |            | 0.4       | -             | -    | mm                |

## Note

- As per IEC 60747-5-5, §7.4.3.8.1, this optocoupler is suitable for “safe electrical insulation” only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.


TYPICAL CHARACTERISTICS ( $T_{amb} = 25^\circ \text{C}$ , unless otherwise specified)

Fig. 3 - Forward Voltage vs. Forward Current




Fig. 5 - Collector Current vs. Collector Emitter Voltage




Fig. 4 - Collector Current vs. Collector Emitter Voltage




Fig. 6 - Collector Emitter Dark Current vs. Ambient Temperature




Fig. 7 - Normalized Current Transfer Ratio vs. Ambient Temperature




Fig. 10 - Normalized Current Transfer Ratio vs. Ambient Temperature




Fig. 8 - Normalized Current Transfer Ratio vs. Ambient Temperature




Fig. 11 - Normalized Current Transfer Ratio vs. Ambient Temperature





Fig. 9 - Output Current vs. Temperature

Fig. 12 - Normalized  $h_{FE}$  vs. Base Current



Fig. 13 - Normalized  $h_{FE}$  vs. Base Current

Fig. 16 - Switching Time vs. Load Resistance




Fig. 14 - Photo Current vs. Forward Current




Fig. 17 - Switching Time vs. Load Resistance




Fig. 15 - Photo Current vs. Forward Current




Fig. 18 - Propagation Delay vs. Ambient Temperature




Fig. 19 - Propagation Delay vs. Ambient Temperature




Fig. 21 - Small Signal Current Transfer Ratio vs. Quiescent Input Current









Fig. 20 - Small Signal CTR vs. Forward Current

**PACKAGE DIMENSIONS** in millimeters**Standard**




22672




**Option 6**



**Option 9**



## PACKAGE MARKING



21764-70






## Footprint and Schematic Information for 6N1135, 6N1136

The footprint and schematic symbols for the following parts can be accessed using the associated links. They are available in Eagle, Altium, KiCad, OrCAD / Allegro, Pulsonix, and PADS.

Note that the 3D models for these parts can be found on the Vishay product page.

| PART NUMBER  | FOOTPRINT / SCHEMATIC                                                                                                          |
|--------------|--------------------------------------------------------------------------------------------------------------------------------|
| 6N1135       | <a href="http://www.snapeda.com/parts/6N1135/Vishay/view-part/">www.snapeda.com/parts/6N1135/Vishay/view-part/</a>             |
| 6N1135-X009T | <a href="http://www.snapeda.com/parts/6N1135-X009T/Vishay/view-part/">www.snapeda.com/parts/6N1135-X009T/Vishay/view-part/</a> |
| 6N1136       | <a href="http://www.snapeda.com/parts/6N1136/Vishay/view-part/">www.snapeda.com/parts/6N1136/Vishay/view-part/</a>             |
| 6N1136-X009T | <a href="http://www.snapeda.com/parts/6N1136-X009T/Vishay/view-part/">www.snapeda.com/parts/6N1136-X009T/Vishay/view-part/</a> |

For technical issues and product support, please contact [optocoupleranswers@vishay.com](mailto:optocoupleranswers@vishay.com).





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.