



## N-Channel 80- and 90-V (D-S) MOSFETs

PRODUCT SUMMARY				
Part Number	V <sub>(BR)DSS</sub> Min (V)	r <sub>DS(on)</sub> Max (Ω)	V <sub>GS(th)</sub> (V)	I <sub>D</sub> (A)
VN0808L	80	4 @ V <sub>GS</sub> = 10 V	0.8 to 2	0.3
VN0808LS		4 @ V <sub>GS</sub> = 10 V	0.8 to 2	0.33
VQ1006P	90	4 @ V <sub>GS</sub> = 10 V	0.8 to 2.5	0.4

### FEATURES


- Low On-Resistance: 3.6 Ω
- Low Threshold: 1.6 V
- Low Input Capacitance: 35 pF
- Fast Switching Speed: 6 ns
- Low Input and Output Leakage

### BENEFITS

- Low Offset Voltage
- Low-Voltage Operation
- Easily Driven Without Buffer
- High-Speed Circuits
- Low Error Voltage



### APPLICATIONS

- Direct Logic-Level Interface: TTL/CMOS
- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories, Transistors, etc.
- Battery Operated Systems
- Solid-State Relays



Top View  
VN0808L


Front View:  
VN0808L




Top View  
VN0808LS

Front View:

VN0808LS




"S" = Siliconix Logo  
f = Factory Code  
// = Lot Traceability  
xxyy = Date Code



Top View  
Sidebrazed: VQ1006P

Top View:

VQ1006P



ABSOLUTE MAXIMUM RATINGS (T <sub>A</sub> = 25°C UNLESS OTHERWISE NOTED)							
Parameter	Symbol	VN0808L	VN0808LS	VQ1006P		Unit	
				Single	Total Quad		
Drain-Source Voltage	V <sub>DS</sub>	80	80	90		V	
Gate-Source Voltage	V <sub>GS</sub>	±30	±30	±20			
Continuous Drain Current (T <sub>J</sub> = 150°C)	I <sub>D</sub>	T <sub>A</sub> = 25°C	0.3	0.33	0.4	A	
		T <sub>A</sub> = 100°C	0.19	0.21	0.23		
Pulsed Drain Current <sup>a</sup>	I <sub>DM</sub>	1.9	1.9	2			
Power Dissipation	P <sub>D</sub>	T <sub>A</sub> = 25°C	0.8	0.9	1.3	2	W
		T <sub>A</sub> = 100°C	0.32	0.4	0.52	0.8	
Thermal Resistance, Junction-to-Ambient	R <sub>thJA</sub>	156	139	96	62.5	°C/W	
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	-55 to 150					°C

Notes

a. Pulse width limited by maximum junction temperature.

SPECIFICATIONS ( $T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)								
Parameter	Symbol	Test Conditions	Typ <sup>a</sup>	Limits				Unit
				VN0808L/LS		VQ1006P		
				Min	Max	Min	Max	
<b>Static</b>								
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0\text{ V}, I_D = 10\ \mu\text{A}$	125	80		90		V
Gate-Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 1\ \text{mA}$	1.6	0.8	2	0.8	2.5	
Gate-Body Leakage	$I_{GSS}$	$V_{DS} = 0\ \text{V}, V_{GS} = \pm 15\ \text{V}$			$\pm 100$		$\pm 100$	nA
			$T_J = 125^\circ\text{C}$				$\pm 500$	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 80\ \text{V}, V_{GS} = 0\ \text{V}$			10			$\mu\text{A}$
			$T_J = 125^\circ\text{C}$			500		
			$V_{DS} = 72\ \text{V}, V_{GS} = 0\ \text{V}$				1	
			$T_J = 125^\circ\text{C}$				500	
On-State Drain Current <sup>b</sup>	$I_{D(on)}$	$V_{DS} = 10\ \text{V}, V_{GS} = 10\ \text{V}$	1.8	1.5		1.5		A
Drain-Source On-Resistance <sup>b</sup>	$r_{DS(on)}$	$V_{GS} = 5\ \text{V}, I_D = 0.3\ \text{A}$					5	$\Omega$
			$V_{GS} = 10\ \text{V}, I_D = 1\ \text{A}$	3.6		4	4.5	
			$T_J = 125^\circ\text{C}$	6.7		8	8.6	
Forward Transconductance <sup>b</sup>	$g_{fs}$	$V_{DS} = 10\ \text{V}, I_D = 0.5\ \text{A}$	350	170		170		mS
Common Source Output Conductance <sup>b</sup>	$g_{os}$	$V_{DS} = 10\ \text{V}, I_D = 0.1\ \text{A}$	0.23					
<b>Dynamic</b>								
Input Capacitance	$C_{iss}$	$V_{DS} = 25\ \text{V}, V_{GS} = 0\ \text{V}, f = 1\ \text{MHz}$	35		50		60	pF
Output Capacitance	$C_{oss}$		15		40		50	
Reverse Transfer Capacitance	$C_{rss}$		2		10		10	
<b>Switching<sup>c</sup></b>								
Turn-On Time	$t_{ON}$	$V_{DD} = 25\ \text{V}, R_L = 23\ \Omega$ $I_D \cong 1\ \text{A}, V_{GEN} = 10\ \text{V}$ $R_G = 25\ \Omega$	6		10		10	ns
Turn-Off Time	$t_{OFF}$		8		10		10	







## Notes

- a. For DESIGN AID ONLY, not subject to production testing.  
 b. Pulse test:  $PW \leq 300\ \mu\text{s}$  duty cycle  $\leq 2\%$ .  
 c. Switching time is essentially independent of operating temperature.






VNDQ09



**TYPICAL CHARACTERISTICS (T<sub>A</sub> = 25°C UNLESS OTHERWISE NOTED)**



### TYPICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)





## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.