

INTERNATIONAL RECTIFIER

60HFU... SERIES


SUPER FAST RECTIFIER DIODE 60 Amp 60ns

Major ratings and characteristics

	60HFU	Units
I_F (AVG)	60	A
T_c	82	°C
I_{RMS}	94	A
I_{FSM} @ 10ms	830	A
I_{FSM} @ 8.3ms	870	A
V_{RRM}	100 to 600	V
T_J	-40 to 125	°C

Description and Features

- Very low reverse recovery time
- Reduced switching losses
- Soft recovery characteristics
- High surge current capability
- No voltage derating up to 150°C
- Stud cathode and stud anode versions
- Designed for switching applications:
Free wheeling diode in converters and control circuits
Rectifier in S.M.P.S.



ELECTRICAL SPECIFICATIONS
Forward Conduction

Parameters	Value	Units	Conditions
$I_{(M)}$ Maximum average forward current	60	A	180° conduction, half sine cond @ Case temperature = 82°C
	67	A	180° conduction, rect cond @ Case temperature = 82°C
$I_{(RM)}$ Maximum RMS current	84	A	
$I_{(SM)}$ Maximum peak, one-cycle non-repetitive forward current Initial $I_j = I_{j \text{ max}}$	830	A	$t = 10\text{ms}$ No voltage reapplied
	870	A	$t = 8.3\text{ms}$
	700	A	$t = 10\text{ms}$ 100% V_{REV} reapplied
	730	A	$t = 8.3\text{ms}$
$P_{(T)}$ Maximum $P_{(T)}$ for fusing Initial $I_j = I_{j \text{ max}}$	3460	mW	$t = 10\text{ms}$ No voltage reapplied
	3160	mW	$t = 8.3\text{ms}$
	2450	mW	$t = 10\text{ms}$ 100% V_{REV} reapplied
	2240	mW	$t = 8.3\text{ms}$
$P_{(NT)}$ Maximum $P_{(NT)}$ for fusing	34800	mW	$t = 0$ to 10ms , no voltage reapplied
$V_{(TIO)}$ Maximum value of threshold voltage	1.08	V	$T_j = 125^\circ\text{C}$
r_{θ} Maximum value of forward state resistance	3.40	$\text{m}\Omega$	$T_j = 125^\circ\text{C}$
$V_{(F)}$ Maximum forward voltage drop	1.50	V	$I_{FM} = 80 \text{ Apk}$, $T_j = 25^\circ\text{C}$
	1.30	V	$I_{FM} = 80 \text{ Apk}$, $T_j = 125^\circ\text{C}$

Thermal and Mechanical Specifications

T_j Junction temperature range	-40 to 125	°C	
T_{sto} Storage temperature range	-40 to 150	°C	
$R_{\theta(j-c)}$ Maximum thermal resistance junction to case	0.36	$\text{K}/^\circ\text{W}$	DC operation per junction
$R_{\theta(j-h)}$ Maximum thermal resistance, case to heatsink	0.25	$\text{K}/^\circ\text{W}$	Mounting surface, smooth and greased
T Mounting torque, base to heatsink $\pm 10\%$	2.5	Nm	A mounting compound is recommended and the torque should be rechecked after a period of about 3 hours to allow for the spread of the compound
w Approximate weight	25	g	

Recovery Characteristics

Parameters	Typ.	Max.	Units	Conditions
t_{rr} Recovery time	60	80	ns	$T_j = 25^\circ\text{C}$ IF = 1A, $dI/dt = -100 \text{ A}/\mu\text{s}$, $V_r = -30\text{V}$
Q_{rr} Recovered charge	250	300	nC	$T_j = 25^\circ\text{C}$ IF = 1A, $dI/dt = -100 \text{ A}/\mu\text{s}$, $V_r = -30\text{V}$

$t_{rr} = t_a + t_b$

Voltage ratings ($T_j = T_{j \text{ max}}$)

Type number	V_{RRM} , maximum repetitive peak reverse voltage	V_{RSM} , maximum non-repetitive peak reverse voltage	I_{RSM} Max @ 100°C	I_{RSM} Max @ 150°C	I_{RSM} Typ. @ 25°C
60HF U(R)-100	V	V	mA	mA	μA
	100	110	5	15	50
60HF U(R)-200	200	220	5	15	50
60HF U(R)-300	300	330	5	15	50
60HF U(R)-400	400	440	5	15	50
60HF U(R)-500	500	550	5	25	50
60HF U(R)-600	600	660	5	25	50

ΔR Conduction (per junction)

(The following table shows the increment of thermal resistance $R_{th(j-c)}$ when devices operate at different conduction angles than DC.)

Conduction angle	Sinusoidal Conduction	Rectangular Conduction	Units	Conditions
180°	0.06	0.05	K/W	
120°	0.08	0.09	K/W	
90°	0.10	0.12	K/W	
60°	0.15	0.16	K/W	
30°	0.24	0.24	K/W	

Fig.1 - Maximum Forward Energy Loss Per Pulse Characteristics















Fig.2 - Maximum Forward Energy Loss Per Pulse Characteristics







indemnify Vishay for any damages resulting from such improper use or sale.

International Rectifier®, IR®, the IR logo, HEXFET®, HEXSense®, HEXDIP®, are registered trademarks of International Rectifier Corporation in the U.S. names noted herein may be trademarks of their respective owners.

Document Number: 99901
Revision: 12-Mar-07