




Surface Mount Multilayer Ceramic Chip Capacitors DSCC Qualified Type 03028



FEATURES

- US defense supply center approved
- Federal stock control number, CAGE CODE 95275
- Small case size (0603)
- Stable BP, BR and BX dielectrics
- Excellent aging characteristics
- Lead (Pb)-free applied for "M" termination code
- Tin/Lead "Z" termination code is available
- Surface-mount, precious metal technology, wet build process
- Made with a combination of design, materials and tight process control to achieve very high field reliability



RoHS*
COMPLIANT

ELECTRICAL SPECIFICATIONS

Note: Electrical characteristics at + 25 °C unless otherwise specified

Operating Temperature: BP, BR, BX: - 55 °C to + 125 °C

Capacitance Range:

BP = 0.5 pF to 1000 pF

BR = 100 pF to 0.1 μF

BX = 100 pF to 0.1 μF

Voltage Rating: 10 Vdc to 100 Vdc

Temperature Coefficient of Capacitance (TCC):

BP = 0 ± 30 ppm/°C from - 55 °C to + 125 °C with zero (0) V(DC) applied

BP = 0 ± 30 ppm/°C from - 55 °C to + 125 °C with 100 % rated Vdc applied

BR = ± 15 % from - 55 °C to + 125 °C with zero (0) V(DC) applied

BR = + 15 %, - 40 % from - 55 °C to + 125 °C with 100 % rated Vdc applied

BX = ± 15 % from - 55 °C to + 125 °C with zero (0) V(DC) applied

BX = + 15 %, - 25 % from - 55 °C to + 125 °C with 100 % rated Vdc applied

Dissipation Factor (DF):

BP: 0.15 % max. at 1.0 Vrms and 1 MHz for values ≤ 1000 pF
0.15 % max. at 1.0 Vrms and 1 kHz for values > 1000 pF
BR and BX: ≤ 25 V ± 3.5 % max. at 1.0 Vrms and 1 kHz
≥ 50 V ± 2.5 % max. at 1.0 Vrms and 1 kHz

Aging Rate:

BP = 0 % maximum per decade

BR, BX = 1 % maximum per decade

Insulation Resistance (IR):

At + 25 °C and rated voltage 100 000 MΩ minimum or 1000 ΩF, whichever is less

At + 125 °C and rated voltage 10 000 MΩ minimum or 100 ΩF, whichever is less

Dielectric Withstanding Voltage (DWV):

This is the maximum voltage the capacitors are tested for a 1 to 5 second period and the charge/discharge current does not exceed 50 mA

≤ 200 Vdc: DWV at 250 % of rated voltage

DIMENSIONS					
PART ORDERING NUMBER	LENGTH	WIDTH	MAXIMUM THICKNESS (T)	TERMINATION PAD	
				MINIMUM	MAXIMUM
VJ03028-	0.063 ± 0.005 [1.60 ± 0.12]	0.031 ± 0.005 [0.80 ± 0.12]	0.035 [0.89]	0.012 [0.30]	0.018 [0.46]

ORDERING INFORMATION							
PART NUMBER	DIELECTRIC	CAPACITANCE NOMINAL CODE	DC VOLTAGE RATING ¹⁾	CAPACITANCE TOLERANCE	TERMINATION	GROUP C TESTING OPTION	PACKAGING
VJ03028-	BX	102	B	J	Z	-	T
DSCC NUMBER							
CASE SIZE 0603	BP BR BX	Expressed in picofarads (pF). The first two digits are significant, the third is a multiplier. An "R" indicates a decimal point. Examples: 101 = 100 pF 1R8 = 1.8 pF	Y = 16 V Z = 25 V A = 50 V B = 100 V	C = ± 0.25 pF D = ± 0.5 pF F = ± 1 % G = ± 2 % H = ± 3 % J = ± 5 % K = ± 10 % NOTE: C, D < 10 pF (BP) F, G, H ≥ 10 pF (BP) J, K ≥ 10 pF (BP, BR, BX)	M = Palladium silver Z = Ni barrier with tin/lead plate min. 4 % lead	C = Full Group C L = 2000 hours life test only M = 1000 hours life test only H = Low voltage humidity	T = 7" Reel Plastic tape C = 7" Reel Paper tape J = 7" Reel (low quantity) R = 11 1/4" Reel Plastic tape P = 11 1/4" Reel Paper tape B = Bulk

Note:

1. DC voltage rating should not be exceeded in application

* Pb containing terminations are not RoHS compliant, exemptions may apply



Surface Mount Multilayer Ceramic Chip Capacitors

DIELECTRIC													
STYLE		03028											
EIA TYPE		0603											
DIELECTRIC		BP				BR				BX			
VOLTAGE V(DC)		16	25	50	100	16	25	50	100	16	25	50	100
CAP. CODE	CAP.												
0R5	0.5 pF	•	•	•	•								
R75	0.75 pF	•	•	•	•								
1R0	1.0 pF	•	•	•	•								
1R2	1.2 pF	•	•	•	•								
1R5	1.5 pF	•	•	•	•								
1R8	1.8 pF	•	•	•	•								
2R2	2.2 pF	•	•	•	•								
2R4	2.4 pF	•	•	•	•								
2R7	2.7 pF	•	•	•	•								
3R0	3.0 pF	•	•	•	•								
3R3	3.3 pF	•	•	•	•								
3R6	3.6 pF	•	•	•	•								
3R9	3.9 pF	•	•	•	•								
4R7	4.7 pF	•	•	•	•								
5R1	5.1 pF	•	•	•	•								
5R6	5.6 pF	•	•	•	•								
6R2	6.2 pF	•	•	•	•								
6R8	6.8 pF	•	•	•	•								
7R5	7.5 pF	•	•	•	•								
8R2	8.2 pF	•	•	•	•								
9R1	9.1 pF	•	•	•	•								
100	10 pF	•	•	•	•								
110	11 pF	•	•	•	•								
120	12 pF	•	•	•	•								
130	13 pF	•	•	•	•								
150	15 pF	•	•	•	•								
160	16 pF	•	•	•	•								
180	18 pF	•	•	•	•								
200	20 pF	•	•	•	•								
220	22 pF	•	•	•	•								
240	24 pF	•	•	•	•								
270	27 pF	•	•	•	•								
300	30 pF	•	•	•	•								
330	33 pF	•	•	•	•								
360	36 pF	•	•	•	•								
390	39 pF	•	•	•	•								
430	43 pF	•	•	•	•								
470	47 pF	•	•	•	•								
510	51 pF	•	•	•	•								
560	56 pF	•	•	•	•								
620	62 pF	•	•	•	•								
680	68 pF	•	•	•	•								
750	75 pF	•	•	•	•								
820	82 pF	•	•	•	•								
910	91 pF	•	•	•	•								



Surface Mount Multilayer Ceramic Chip Capacitors

Vishay Vitramon

DIELECTRIC													
STYLE		03028											
EIA TYPE		0603											
DIELECTRIC		BP				BR				BX			
VOLTAGE V(DC)		16	25	50	100	16	25	50	100	16	25	50	100
101	100 pF	•	•	•	•			•					
121	120 pF	•	•	•	•			•				•	
151	150 pF	•	•	•	•			•				•	
181	180 pF	•	•	•	•			•				•	
221	220 pF	•	•	•	•			•				•	
271	270 pF	•	•	•	•			•				•	
331	330 pF	•	•	•	•	•	•	•	•	•	•	•	•
391	390 pF	•	•	•	•	•	•	•	•	•	•	•	•
471	470 pF	•	•	•	•	•	•	•	•	•	•	•	•
561	560 pF	•	•	•	•	•	•	•	•	•	•	•	•
681	680 pF	•	•	•	•	•	•	•	•	•	•	•	•
821	820 pF	•	•	•	•	•	•	•	•	•	•	•	•
102	1000 pF	•	•			•	•	•	•	•	•	•	•
122	1200 pF					•	•	•	•	•	•	•	•
152	1500 pF					•	•	•	•	•	•	•	•
182	1800 pF					•	•	•	•	•	•	•	•
222	2200 pF					•	•	•	•	•	•	•	•
272	2700 pF					•	•	•	•	•	•	•	•
332	3300 pF					•	•	•	•	•	•	•	•
392	3900 pF					•	•	•	•	•	•	•	•
472	4700 pF					•	•	•	•	•	•	•	•
562	5600 pF					•	•	•	•	•	•	•	•
682	6800 pF					•	•	•	•	•	•	•	•
822	8200 pF					•	•	•	•	•	•	•	•
103	0.010 μF					•	•	•	•	•	•	•	•
123	0.012 μF					•	•	•	•	•	•	•	•
153	0.015 μF					•	•	•	•	•	•	•	•
183	0.018 μF					•	•	•	•	•	•	•	•
223	0.022 μF					•	•	•	•	•	•	•	•
273	0.027 μF					•	•	•		•	•	•	
333	0.033 μF					•	•	•		•	•	•	
393	0.039 μF					•	•	•		•	•	•	
473	0.047 μF					•	•	•		•	•	•	
563	0.056 μF					•	•			•	•		
683	0.068 μF					•	•			•	•		
823	0.082 μF					•	•			•	•		
104	0.10 μF					•	•			•	•		
124	0.12 μF												
154	0.15 μF												
184	0.18 μF												
224	0.22 μF												

Note

1. See soldering recommendations within this data book, or visit www.vishay.com/doc?45034

DSCC PACKAGING QUANTITIES 1/2/3/4)							
		7" REEL QUANTITIES		11 1/4" AND 13" REEL QUANTITIES		BULK QUANTITIES	
BODY SIZE	TAPE SIZE	PAPER TAPE PACKAGING CODE "C"	PAPER TAPE PACKAGING CODE "J"	PAPER TAPE PACKAGING CODE "P"		VIAL PACKAGING CODE "B"	WAFFLE PACKAGING CODE "W"
0603	8 mm	4000	1000	10 000		100	N/A

Note

1. Vishay Vitramon uses embossed plastic carrier tape and punch paper carrier tape
2. REFERENCE: EIA Standard RS 481 - "Taping of Surface Mount Components for Automatic Placement"



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.