


## Schottky Rectifier, 2 x 6 A


**D-PAK**


### FEATURES

- Popular D-PAK outline
- Center tap configuration
- Small foot print, surface mountable
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Lead (Pb)-free ("PbF" suffix)
- Designed and qualified for industrial level


 Available  
**RoHS\***  
 COMPLIANT

### DESCRIPTION

The 12CWQ10GPbF surface mount, center tap, Schottky rectifier series has been designed for applications requiring low forward drop and small foot prints on PC board. Typical applications are in disk drives, switching power supplies, converters, freewheeling diodes, battery charging, and reverse battery protection.

### PRODUCT SUMMARY

|             |         |
|-------------|---------|
| $I_{F(AV)}$ | 2 x 6 A |
| $V_R$       | 100 V   |

### MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL      | CHARACTERISTICS                      | VALUES      | UNITS      |
|-------------|--------------------------------------|-------------|------------|
| $I_{F(AV)}$ | Rectangular waveform                 | 12          | A          |
| $V_{RRM}$   |                                      | 100         | V          |
| $I_{FSM}$   | $t_p = 5 \mu s$ sine                 | 330         | A          |
| $V_F$       | 6 Apk, $T_J = 125^\circ C$ (per leg) | 0.65        | V          |
| $T_J$       | Range                                | - 55 to 150 | $^\circ C$ |

### VOLTAGE RATINGS

| PARAMETER                            | SYMBOL    | 12CWQ10GPbF | UNITS |
|--------------------------------------|-----------|-------------|-------|
| Maximum DC reverse voltage           | $V_R$     | 100         | V     |
| Maximum working peak reverse voltage | $V_{RWM}$ |             |       |

### ABSOLUTE MAXIMUM RATINGS

| PARAMETER   | SYMBOL      | TEST CONDITIONS   | VALUES | UNITS |
|---|-------------|---|--------|-------|
| Maximum average forward current<br>See fig. 5                             | $I_{F(AV)}$ | 50 % duty cycle at $T_C = 135^\circ C$ , rectangular waveform   | 6      | A     |
|   |             |   | 12     |       |
| Maximum peak one cycle non-repetitive surge current per leg<br>See fig. 7 | $I_{FSM}$   | 5 $\mu s$ sine or 3 $\mu s$ rect. pulse   | 330    | A     |
|   |             | 10 ms sine or 6 ms rect. pulse  |        |       |
| Non-repetitive avalanche energy per leg                                   | $E_{AS}$    | $T_J = 25^\circ C$ , $I_{AS} = 1 A$ , $L = 12 mH$   | 6      | mJ    |
| Repetitive avalanche current per leg                                      | $I_{AR}$    | Current decaying linearly to zero in 1 $\mu s$<br>Frequency limited by $T_J$ maximum $V_A = 1.5 \times V_R$ typical | 1      | A     |

\* Pb containing terminations are not RoHS compliant, exemptions may apply

| ELECTRICAL SPECIFICATIONS                             |                |  |                                   |        |            |
|---|----------------|--|-----------------------------------|--------|------------|
| PARAMETER   | SYMBOL         | TEST CONDITIONS  |                                   | VALUES | UNITS      |
| Maximum forward voltage drop per leg<br>See fig. 1    | $V_{FM}^{(1)}$ | 6 A  | $T_J = 25\text{ }^\circ\text{C}$  | 0.80   | V          |
|   |                | 12 A   |                                   | 0.95   |            |
|   |                | 6 A  | $T_J = 125\text{ }^\circ\text{C}$ | 0.65   |            |
|   |                | 12 A   |                                   | 0.78   |            |
| Maximum reverse leakage current per leg<br>See fig. 2 | $I_{RM}^{(1)}$ | $T_J = 25\text{ }^\circ\text{C}$   | $V_R = \text{Rated } V_R$         | 0.22   | mA         |
|   |                | $T_J = 125\text{ }^\circ\text{C}$  |                                   | 4      |            |
| Threshold voltage                                     | $V_{F(TO)}$    | $T_J = T_J \text{ maximum}$  |                                   | 0.47   | V          |
| Forward slope resistance                              | $r_t$          |  |                                   | 20.68  | m $\Omega$ |
| Typical junction capacitance per leg                  | $C_T$          | $V_R = 5 V_{DC}$ , (test signal range 100 kHz to 1 MHz) $25\text{ }^\circ\text{C}$ |                                   | 183    | pF         |
| Typical series inductance per leg                     | $L_S$          | Measured lead to lead 5 mm from package body                                       |                                   | 5.0    | nH         |

**Note**

(1) Pulse width < 300  $\mu\text{s}$ , duty cycle < 2 %

| THERMAL - MECHANICAL SPECIFICATIONS             |             |  |            |             |                    |
|---|-------------|--|------------|-------------|--------------------|
| PARAMETER                                       | SYMBOL      | TEST CONDITIONS                        |            | VALUES      | UNITS              |
| Maximum junction temperature range              | $T_J^{(1)}$ |  |            | - 55 to 150 | $^\circ\text{C}$   |
| Maximum storage temperature range               | $T_{Stg}$   |  |            |             |                    |
| Maximum thermal resistance,<br>junction to case | $R_{thJC}$  | DC operation<br>See fig. 4             | per leg    | 3.0         | $^\circ\text{C/W}$ |
|   |             |  | per device | 1.5         |                    |
| Approximate weight                              |             |  |            | 0.3         | g                  |
|   |             |  |            | 0.01        | oz.                |
| Marking device                                  |             | Case style D-PAK (similar to TO-252AA) | 12CWQ10G   |             |                    |

**Note**

(1)  $\frac{dP_{tot}}{dT_J} < \frac{1}{R_{thJA}}$  thermal runaway condition for a diode on its own heatsink




Fig. 1 - Maximum Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage (Per Leg)




Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics (Per Leg)




Fig. 5 - Maximum Allowable Case Temperature vs. Average Forward Current (Per Leg)




Fig. 6 - Forward Power Loss Characteristics (Per Leg)





Fig. 7 - Maximum Non-Repetitive Surge Current (Per Leg)

**Note**

- (1) Formula used:  $T_C = T_J - (P_d + P_{dREV}) \times R_{thJC}$ ;  
 $P_d$  = Forward power loss =  $I_{F(AV)} \times V_{FM}$  at  $(I_{F(AV)}/D)$  (see fig. 6);  
 $P_{dREV}$  = Inverse power loss =  $V_{R1} \times I_R (1 - D)$ ;  $I_R$  at  $V_{R1} = 80\%$  rated  $V_R$



### ORDERING INFORMATION TABLE



- 1** - Current rating
- 2** - C = Common cathode
- 3** - Package:  
W = D-PAK (TO-252AA)
- 4** - Q = Schottky "Q" series
- 5** - Voltage rating: code x 10 =  $V_{RRM}$  (10 = 100 V)
- 6** - Schottky generation
- 7** -
  - None = Tube (75 pieces)
  - TR = Tape and reel
  - TRL = Tape and reel (left oriented)
  - TRR = Tape and reel (right oriented)
- 8** -
  - None = Standard production
  - PbF = Lead (Pb)-free

| LINKS TO RELATED DOCUMENTS |   |
|----------------------------|---|
| Dimensions                 | <a href="http://www.vishay.com/doc?95016">http://www.vishay.com/doc?95016</a> |
| Part marking information   | <a href="http://www.vishay.com/doc?95059">http://www.vishay.com/doc?95059</a> |
| Packaging information      | <a href="http://www.vishay.com/doc?95033">http://www.vishay.com/doc?95033</a> |



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.