Note: This datasheet may be out of date.

Please download the latest datasheet of DEA1X3D220JD1B from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DEA1X3D220JD1B

DEA1X3D220JD1B
















Appearance & Shape







References

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	500

Mass (typ.)	
1 piece	0.11g

1 of 2

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date.

Please download the latest datasheet of DEA1X3D220JD1B from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=DEA1X3D220JD1B

DEA1X3D220JD1B



Specifications

L size or Outer diameter D	4.5mm max.	
-		
T size	5.0mm max.	
Lead spacing F	5.0±0.8mm	
Lead diameter d	0.5±0.05mm	
Paint dripping e	3.0mm max.	
Capacitance	22pF ±5%	
Rated voltage	2000Vdc	
Temperature characteristics	SL(JIS)	
Temperature range of	20°C to 85°C	
temperature characteristics		
Operating Temperature Range	-25°C to 125°C	
тс	+350 to -1000ppm/°C	

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

