


935157425510-xxA

In Production

Recommended

Appearance & Shape



Features

- | Ultra broadband performance up to 67GHz
 - | Resonance free allowing ultra group delay variation
 - | Ultra low insertion loss thanks to an excellent impedance matching in transmission mode
 - | Low ESL and low ESR in bypass grounding mode
 - | High stability of capacitance value over temperature, voltage and aging
 - | High reliability
 - | Compatible with standard wire bonding assembly (ball and wedge) and embedding.
- (please refer to our assembly application note for more details)

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

935157425510-xxA

Specifications

Series	UBEC
Applications	Broadband
Features	High Frequency
Mounting Method	Wire-bonding/Embedded
Operating Temperature Range	-55°C to 150°C
Size Code (in inch)	0201M
L x W (size)	0.60 x 0.30mm
Frequency	60GHz+
Breakdown Voltage (For the rated voltage, please see the FAQ.)	11Vdc
Capacitance	10nF
Thickness	100µm

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.