


## Inductors (Coils)

- [Product Top Page](#)
- [Search by Part No.](#)
- [Search by Characteristics](#)
- [Cross Reference](#)
- [Catalog](#)
- [Tech Notes](#)

▼ more

# MHQ0402P6N2JT000

Applications



Commercial Grade

Feature

Multilayer

Multilayer

Non-Mag Core

Non-Magnetic Core (Dielectric Ceramic)

Super High Q

Super High Q

Series | Type

MHQ-P


Status



Production (Not Recommended for New Design)

Recommended Alternate Part No. : [MHQ0402PSA6N2JT000](#) (Interchangeability is not guaranteed.)

Brand

TDK

Images are for reference only and show exemplary products.

Size	
Length(L)	0.44mm ±0.02mm
Width(W)	0.24mm ±0.02mm
Thickness   Height	0.24mm ±0.02mm
Recommended Land Pattern (A)	0.15mm to 0.20mm
Recommended Land Pattern (B)	0.20mm Nom.
Recommended Land Pattern (C)	0.18mm to 0.20mm

Electrical Characteristics	
Inductance	6.2nH ±5% at 500MHz
Rated Current	200mA
DC Resistance [Typ.]	600mΩ
DC Resistance [Max.]	1Ω
Self Resonant Frequency [Min.]	4GHz
Self Resonant Frequency [Typ.]	5.6GHz
Q [Min.]	10 at 500MHz
Q [Typ.]	15 at 500MHz

Other	
Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125°C
Soldering Method	Reflow
AEC-Q200	No
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	20000pcs
Weight	0.00011g

?


RoHS

REACH SVHC-Free


Halogen Free

Lead Free


PDF file of this page





Contact





Documents

Catalog


RoHS Certificate

SVHC/REACH Certificate


Product Lineup


[Selection Guide] Inductors for high frequency applications 


Update


Sample Kits

Technical Support Tools

S-parameter

SPICE Netlist (Simple)

SPICE Netlist (Precision)

Equivalent Circuit Model

## Characteristic Graph (This is reference data, and does not guarantee the products characteristics.)



MHQ0402P6N2JT000

Change settings

MHQ0402P6N2JT000

Change settings

Inductance

MHQ0402P6N2JT000

Change settings

Q

MHQ0402P6N2JT000

Change settings



Selection Guides

Search by Part No.

Search by Characteristics

Distributor Inventory Check

Cross Reference

Products

- Capacitors
- Inductors (Coils)
- EMC Components
- RF Components and Modules
- Voltage / Current / Temperature Protection Devices
- Sensors and Sensor Systems
- Ceramic Switching / Heating, Piezo Components, Buzzers and Microphones
- Transformers
- Ferrites and Accessories
- Noise Suppressing / Magnetic Sheet
- Anechoic Chambers and Radio Wave Absorbers
- Power Supplies
- Magnets
- Flash Storages
- Wireless Power Transfer
- FA Systems

Transparent Conductive Film	>
Micro Modules (Substrates with Built-in ICs, Products Utilizing with SESUB)	>
Solar Cells	>
Biosensor	>
Application Specific IC (ASIC) Development and Supply	>

Application Guides

Technical Support

Tech Library

Environment

Contact

News

Home

About TDK

TDK Worldwide

[Terms of Use](#)   [Privacy Policy](#)   [Cookie Policy](#)

Copyright(c) 2019 TDK Corporation. All rights reserved.  
TDK logo is a trademark or registered trademark of TDK Corporation.

