

NLC565050T-220K-PF RoHS Reach

Applications	Commercial Grade	
	No Directivity No Directivity	
Feature	Wire Wound Wire Wound	
	Ferrite Core	
Series Type	NLC565050	
Status	⚠ Obsolete	
	Recommended Alternate Part No. : None	
	Discontinue Issue Date : May.21, 2015	
	Last Purchase Order Date : Dec.22, 2016	
	Last Shipment Date : Jun.30, 2017	
Brand	TDK	



Size		
Length(L)	5.60mm ±0.30mm	
Width(W)	5.00mm ±0.30mm	
Thickness Height	5.00mm ±0.30mm	
Recommended Land Pattern (A)	2.00mm Nom.	
Recommended Land Pattern (B)	4.00mm Nom.	
Recommended Land Pattern (C)	4.50mm Nom.	

Electrical Characteristics		
Inductance	22μH ±10% at 2.52MHz	
Rated Current	480mA	
DC Resistance [Typ.]		
DC Resistance [Max.]	430mΩ	
Self Resonant Frequency [Min.]	13MHz	
Self Resonant Frequency [Typ.]		
Q [Min.]	10 at 2.52MHz	
Q [Typ.]		

Other		
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 105°C	
	Wave (Flow)	
Soldering Method	Reflow	
	Iron Soldering	
AEC-Q200	NO	
Packing	Embossed (Plastic)Taping [180mm Reel]	
Package Quantity	400pcs	
Weight	0.38g	


[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.


 $^{! \ \}mbox{All specifications}$ are subject to change without notice.


RoHS Reach


Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)















[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{! \ \}mbox{\ensuremath{\mathsf{III}}}$ specifications are subject to change without notice.

NLC565050T-220K-PF

Associated Images



 $^{! \ \}mbox{Images}$ are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

 $^{! \ \}mbox{All specifications}$ are subject to change without notice.