

**Applications**



Commercial Grade

**Feature**

**Multilayer** Multilayer

**Non-Mag Core** Non-Magnetic Core (Dielectric Ceramic)

**High Q** High Q

**Series | Type**

MLG-P

**Status**



Production

**Brand**

TDK



**Size**

Length(L)	0.60mm ±0.03mm
Width(W)	0.30mm ±0.03mm
Thickness   Height	0.30mm ±0.03mm
Recommended Land Pattern (A)	0.25mm Nom.
Recommended Land Pattern (B)	0.30mm Nom.
Recommended Land Pattern (C)	0.30mm Nom.

**Electrical Characteristics**





Inductance	15nH ±5% at 500MHz
Rated Current	250mA
DC Resistance [Typ.]	940mΩ
DC Resistance [Max.]	1.2Ω
Self Resonant Frequency [Min.]	3.2GHz
Self Resonant Frequency [Typ.]	3.7GHz
Q [Min.]	14 at 500MHz
Q [Typ.]	18 at 500MHz

**Other**

Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125°C
Soldering Method	Reflow
AEC-Q200	NO
Packing	Punched (Paper)Taping [180mm Reel, Tape width 8mm]
Package Quantity	15000pcs
Weight	0.0002g

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)



! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

## Associated Images

