

<b>Applications</b>	Commercial Grade
<b>Feature</b>	<div style="border: 1px solid black; padding: 2px;">Multilayer</div> <div style="border: 1px solid black; padding: 2px;">Non-Mag Core</div> <div style="border: 1px solid black; padding: 2px;">Super High Q</div>
<b>Series   Type</b>	MHQ-P
<b>Status</b>	<div style="border: 1px solid black; padding: 2px;"> Obsolete</div> <p>Recommended Alternate Part No. : <a href="#">Contact</a></p> <p>Discontinue Issue Date : Nov.29, 2019</p> <p>Last Purchase Order Date : Dec.31, 2020</p> <p>Last Shipment Date : Mar.31, 2021</p>
<b>Brand</b>	TDK







Size	
Length(L)	0.44mm ±0.02mm
Width(W)	0.24mm ±0.02mm
Thickness   Height	0.24mm ±0.02mm
Recommended Land Pattern (A)	0.15mm to 0.20mm
Recommended Land Pattern (B)	0.20mm Nom.
Recommended Land Pattern (C)	0.18mm to 0.20mm

Electrical Characteristics	
Inductance	4.6nH ±3% at 500MHz
Rated Current	200mA
DC Resistance [Typ.]	500mΩ
DC Resistance [Max.]	700mΩ
Self Resonant Frequency [Min.]	5GHz
Self Resonant Frequency [Typ.]	6.8GHz
Q [Min.]	10 at 500MHz
Q [Typ.]	14 at 500MHz

Other	
Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125°C
Soldering Method	Reflow
AEC-Q200	NO
Packing	Punched (Paper)Taping [180mm Reel, Tape width 8mm]
Package Quantity	20000pcs
Weight	0.00011g

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)



! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

## Associated Images

