

[Home](#) [Design Center](#) > [Evaluation Hardware & Software](#) > [Product Evaluation Boards and Kits](#) >[EVAL-HMC8327](#) [Design Center](#) > [Evaluation Hardware & Software](#) > [Product Evaluation Boards and Kits](#) >[EVAL-HMC8327](#)

EVAL-HMC8327

HMC8327 Evaluation Board



Overview

Product Details

The EV2HMC8327LG is a fully populated 4-layer evaluation board that allows evaluation of the 81 GHz to 86 GHz HMC8327LG E-band low noise downconverter system-in-package (SiP).

The board assembly includes 4 edge mounted SMA connectors for the differential I and Q mixer outputs as well as a single edge mounted 2.9mm connector for the LO drive input signal. The evaluation board is mounted on an aluminum backplate which includes a standard WR-12 waveguide hole pattern for the E-band signal input.

The board is equipped with LDOs for DC bias and only +5/-5V are needed for powering up the LDOs.

Please refer to the data sheet for detailed biasing requirements and application circuit information.

Applicable Parts

- [HMC8327](#)

Buy

Model	Description	RoHS	
EV2HMC8327LG Production	Evaluation Board	-	Yes

Pricing displayed is based on 1-piece. The USA list pricing shown is for budgetary use only, shown in United States dollars (FOB USA per unit), and is subject to change. International prices may vary due to local duties, taxes, fees and exchange rates.

SOCIAL



QUICK LINKS

[About ADI](#)
[Analog Dialogue](#)
[Contact us](#)
[News Room](#)
[Sales & Distribution](#)
[Partners](#)
[Careers](#)
[Investor Relations](#)
[Quality & Reliability](#)
[Analog Garage](#)

LANGUAGES

[English](#)
[简体中文](#)
[日本語](#)
[Русский](#)

NEWSLETTERS

Interested in the latest news and articles about ADI products, design tools, training and events? Choose from one of our 12 newsletters that match your product area of interest, delivered monthly or quarterly to your inbox.

[Sign Up](#)