

Inductors (Coils)

- Product Top Page
- Search by Part No.
- Search by Characteristics
- Cross Reference
- Catalog
- Tech Notes

▼ more

MHQ0402P1N3CT000




Applications Commercial Grade

- Feature**
- Multilayer** Multilayer
 - Non-Mag Core** Non-Magnetic Core (Dielectric Ceramic)
 - Super High Q** Super High Q

Series | Type MHQ-P

Status Production (Not Recommended for New Design)
Recommended Alternate Part No. : [MHQ0402PSA1N3CT000](#) (Interchangeability is not guaranteed.)

Brand TDK



Images are for reference only and show exemplary products.

PDF file of this page

Contact

Documents

- Catalog
- RoHS Certificate
- SVHC/REACH Certificate
- Product Lineup
- [Selection Guide] Inductors for high frequency applications [Update](#)
- Sample Kits

Technical Support Tools

- S-parameter
- SPICE Netlist (Simple)
- SPICE Netlist (Precision)
- Equivalent Circuit Model

Size

Length(L)	0.44mm ±0.02mm
Width(W)	0.24mm ±0.02mm
Thickness Height	0.24mm ±0.02mm
Recommended Land Pattern (A)	0.15mm to 0.20mm
Recommended Land Pattern (B)	0.20mm Nom.
Recommended Land Pattern (C)	0.18mm to 0.20mm

Electrical Characteristics

Inductance	1.3nH ±0.2nH at 500MHz
Rated Current	320mA
DC Resistance [Typ.]	120mΩ
DC Resistance [Max.]	200mΩ
Self Resonant Frequency [Min.]	8GHz
Self Resonant Frequency [Typ.]	11.3GHz
Q [Min.]	10 at 500MHz
Q [Typ.]	15 at 500MHz

Other

Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125°C
Soldering Method	Reflow
AEC-Q200	No
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	20000pcs
Weight	0.00011g

Characteristic Graph (This is reference data, and does not guarantee the products characteristics.)

Impedance

Rac

MHQ0402P1N3CT000

Change settings

MHQ0402P1N3CT000

Change settings

Inductance

MHQ0402P1N3CT000

Change settings

Q

MHQ0402P1N3CT000

Change settings



[Selection Guides](#) [Search by Part No.](#) [Search by Characteristics](#) [Distributor Inventory Check](#) [Cross Reference](#)

Products

- Capacitors >
- Inductors (Coils) >
- EMC Components >
- RF Components and Modules >
- Voltage / Current / Temperature Protection Devices >
- Sensors and Sensor Systems >
- Ceramic Switching / Heating, Piezo Components, Buzzers and Microphones >
- Transformers >
- Ferrites and Accessories >
- Noise Suppressing / Magnetic Sheet >
- Anechoic Chambers and Radio Wave Absorbers >
- Power Supplies >
- Magnets >
- Flash Storages >
- Wireless Power Transfer >
- FA Systems >

- Transparent Conductive Film >
- Micro Modules (Substrates with Built-in ICs, Products Utilizing with SESUB) >
- Solar Cells >
- Biosensor >
- Application Specific IC (ASIC) Development and Supply >

Application Guides

Technical Support

Tech Library

Environment

Contact

News

Home

About TDK

TDK Worldwide

[Terms of Use](#) [Privacy Policy](#) [Cookie Policy](#)

Copyright(c) 2019 TDK Corporation. All rights reserved.
TDK logo is a trademark or registered trademark of TDK Corporation.

