Global Website **Investor Relations** News Careers Contact Us



## **HN-214DX**

Order Number HN-214DX

Compact Outdoor 2.4GHz Wireless Serial Modem with DIN-rail mount serial interface and four foot cable and external antenna connector

- 2.4GHz Proprietary FHSS Serial Modem
- Network Topology: Point-to-Point and Point-to-Multipoint

## 460.8 Kbps RF data rate

- Outdoor NEMA 4X/IP 66 enclosure
- Compatible with HN 10 Series Products
- Ideal for pole mounting





Data Sheet Contact Us Add to Compare List

Description	Specs	Documents	Applications	Purchase

Minimum Order Quantity	1
Product Type	Serial Modem
Frequency	2.4GHz
Antenna	Reverse TNC
RF Conn/ Antenna	Reverse TNC
Operating Temperature Range	-30 to +70
Operating Temperature °C (min)	-30
Operating Temperature °C (max)	70
Mounting Type	DIN-rail
Dimension	130.00 x 79.00 x 35.00 mm
Supply Voltage min	9.0
Supply Voltage max	30.0
Transmit Power Configurable	Yes
Transmit Power	100mW
Receiver Sensitivity	-93 dBm
Data Rate	460.80 kbps
Data Rate Configurable	No
Range	Indoor 100m, Outdoor 10,000m
Technology	Proprietary FHSS
Network	Point-to-Point and Point-to-Multipoint
Host Interface	RS-232C
FCC/IC Certified	FCC/IC Certified
ETSI Certified	ETSI Certified
RoHs Compliant	Yes
CE Compliant	CE Marked
ISO9001	Yes

## Related Links

Applications for Wireless
Support for Wireless
Wireless Modules for IoT Applications
Wi-Fi/Bluetooth Modules for NXP i.MX
LoRa Modules

## **Related Product Categories**

« Go Back
Wi-Fi
Wi-Fi + Bluetooth
Bluetooth
LPWA Modules
IoT System-On-Module *New
802.15.4
Wi-Fi Bluetooth for NXP i.MX
HyperMesh / FHSS
M2M & Sensor Networking
Wireless Network / Telemetry
RFIC Radios
Resonators
Filters

Investor Relations About Us Contact Us My Murata Site Policy Privacy Site Help Site Map

Copyright Murata Manufacturing Co., Ltd. All Rights Reserved