

3 mm Square SMT Trimmer Potentiometers with the rotation stopper (Cermet, Open Frame Type)



Type: **EVM3V**


Features

- Rotation stopper featured type
- Automatic adjustment type
- High reliability realized by cermet element
- Excellent mountability
- Conforms to JIS C5260-1:1999
- RoHS compliant

Recommended Applications

- Audio/visual, office, and communication equipment
- General electronic equipment

Explanation of Part Numbers



Specifications		
Total Resistance Value Resistance Tolerance	100 Ω to 1 M Ω ±25 %	
Power Rating Limiting Element Voltage	0.15 W 50 V	
Rotation Torque	2 to 10 mN·m	
Stopper Strength	15 mN·m min.	
Temperature Coefficient of Resistance	±250 × 10 ⁻⁶ /°C	

Minimum Quantity/Packing Unit

Part Number	Taping		
Fait Number	Quantity per reel	Packaging quantity	Dia. of reel (mm)
EVM3V	2,000	10,000	φ178

The standard packaging methods for a reel is ϕ 178.

Please contact us, if you would like different packaging methods. (Bulk, Reel of ϕ 330, Reel of ϕ 380)

Dimensions in mm (not to scale)

3-terminal, for Automatic Trimming Adjustment

