PDF file of this page

**公TDK** 

Products News

Catalog

**Product Center** Product information and services

Application Guides Technical Support

Tech Library

Environment

Contact

**Status** 

**Brand** 

TDK

Pr Vc Te Chip NTC Thermistors (Protection Device) Detailed Information

## Chip NTC Thermistors (Protection Device)

Search by Part No. Search by Characteristics Product Top Page Cross Reference Catalog Tech Notes Technical Support Tools NTCG164BH332HT1









Applications	Commercial Grade
Features	125°C 125°C UL Certificate
Series	NTCG
Status	Production

Images are for reference only and show exemplary products.

Contact **Documents** Latalog RoHS Certificate SVHC/REACH Certificate RT Sheet

Size		
Length(L)	1.60mm ±0.10mm	
Width(W)	0.80mm ±0.10mm	
Thickness(T)	0.80mm ±0.10mm	
Terminal Width(B)	0.20mm Min.	
Recommended Land Pattern (PA)	0.70mm ±0.10mm	
Recommended Land Pattern (PB)	0.70mm ±0.10mm	
Recommended Land Pattern (PC)	0.70mm ±0.10mm	
Electrical Characteristics		

Electrical Characteristics	
Resistance [at 25°C]	3.3kΩ
Resisltance Tolerance	±3%
B value (Typ.) [25/50°C]	4067K
B value (Typ.) [25/85°C]	4100K
B value (Typ.) [25/100°C]	4110K
B value Tolerance	±3%
Max. Electric Power [at 25°C] ?	100mW
Permissive Operating Current [at 25°C] ?	550μΑ
Thermal Dissipation Constant [at 25°C] ?	1mW/°C   1mW/K

Other			
Max. Operating Temperature	125°C		
Soldering Method	Reflow		
UL File No.	E250289		
AEC-Q200	No		
Packing	Punched (Paper)Taping [180mm Reel]		
Package Quantity	4000pcs		
Weight	0.005g		

## **Products**

» Search by Part No. » Search by Characteristics » Distributor Inventory Check

» Capacitors

» Inductors (Coils)

» EMC Components

Downloaded from Arrow.com.

» RF / SAW Components and Modules

» Voltage / Current / Temperature Protection Devices

» Sensors and Sensor Systems

» Anechoic Chambers and Radio Wave Absorbers » Power Supplies

» Magnets

» Flash Storages

» Wireless Charging

» FA Systems

Transparent Conductive Film

**Application Guides** 

**Environment** 

Home

**Technical Support Tech Library** Contact News

Buzzers

» Transformers

» Ferrites and Accessories » Noise Suppressing / Magnetic Sheet » Micro Modules (Substrates with Built-in ICs, Products Utilizing with SESUB)

» Solar Cells

» Biosensor



TDK Worldwide

Terms of Use

Copyright(c) 1996-2017 TDK Corporation. All rights reserved. TDK logo is a trademark or registered trademark of TDK Corporation.