	D. I. I	0				About TDK ENGLISH TDK Worldwide			
⊗TDK	Product inform	Center ation and services				Sea	rch by Part Number of	Keywo Search	
News	Products	Catalog	Application Guides	Technical Support	Tech Lil	orary	Environment	Contact	
ightarrow $ ightarrow$ $ ig$	ITC Thermistors (Protect								
Chip NTC Thermistors (Protection Device)									
			, 100)						
Product Top Page Sea	arch by Part No.	Search by Char	acteristics Cross Ret	ference Catalog	Tech Notes	Techni	cal Support Tools		
NTCG163JX103	BDTDS						? Rohs RE	ACH Halogen Lead C-Free Free Free	
Applications Automotive Grade					. –	PDF file	of this page		
125°C	125°C				ľ	Buy Nov	N		
Features UL	UL Certificate	<b>;</b>		Ē		DUY NOV	V	¥	
AEC-Q20	AEC-Q200			••	_	Contact			
Series NTCG	NTCG			Images are for reference on and show exemplary produc					
Status Pro	us Production			_		Document RT Shee			
Brand TDK									
Size									
Length(L)		1.60	0mm ±0.10mm						
Width(W)		0.80	0mm ±0.10mm						
Thickness(T)		0.80	0mm ±0.10mm						
Terminal Width(B)			0.20mm Min.						
Recommended Land Pattern (PA)		0.70	0mm ±0.10mm						
Recommended Land Pattern (PB)		0.70	0mm ±0.10mm						
Recommended Land Pattern (PC)		0.70	0mm ±0.10mm						
Electrical Characteristi	cs								
Resistance [at 25°C]			Ω						
Resisitance Tolerance		±0.9	5%						
B value (Typ.) [25/50°C]		338	ОК						
B value (Typ.) [25/85°C]		343	5K						
B value (Typ.) [25/100°C]		345							
B value Tolerance		±0.3							
Max. Electric Power [at 25°C] ? Permissive Operating Current [at 25°C] ?			mW						
Thermal Dissipation Constant [at 25°C] ?		•	μΑ W/°C   1mW/K						
Other Max. Operating Temperat	ture	105	°C						
Soldering Method			125°C Reflow						
UL File No.			E250289						
			Yes						
Packing Punched (Paper)Taping [180mm Reel]									
Package Quantity 400			000pcs						
Weight			)5g						
Products							lication Guides		
» Search by Part No. » Search by Characteristics » Distributor Inventory Check						Technical Support			

» Capacitors

- » Inductors (Coils)
- » EMC Components
- » RF / SAW Components and Modules
- » Voltage / Current / Temperature Protection Devices
- Downloaded from Arrow.com.

- » Anechoic Chambers and Radio Wave Absorbers
- » Power Supplies
- » Magnets
- » Flash Storages
- » Wireless Charging

Technical Support Tech Library Environment Contact News

- » Sensors and Sensor Systems
- » Ceramic Switching / Heating, Piezo Components and
- Buzzers

Terms of Use

- » Noise Suppressing / Magnetic Sheet
- » Transformers
- » Ferrites and Accessories
- » Transparent Conductive Film
  - » Micro Modules (Substrates with Built-in ICs, Products Utilizing with SESUB)

» FA Systems

» Solar Cells » Biosensor

- Home
- About TDK
- TDK Worldwide

Copyright(c) 1996-2017 TDK Corporation. All rights reserved. TDK logo is a trademark or registered trademark of TDK Corporation.

