



AHEAD OF WHAT'S POSSIBLE™

Search



[MYANALOG](#) | [MY HISTORY](#) | [PRODUCTS](#) | [APPLICATIONS](#) | [DESIGN CENTER](#) | [EDUCATION](#) | [SUPPORT](#)
[Home](#) [Design Center](#) > [Evaluation Hardware & Software](#) > [Product Evaluation Boards and Kits](#) > **DC219A**


Enable javascript

DC219A
 LT1505CG | 4A CC-CV Lithium-Ion Battery Charger, $V_{IN} \text{ max} < 24V$, $V_{IN} \text{ min} = V_{bat} + 0.5V$ (thru-hole caps)

Design & Integration Files

1

[View All](#)

Overview

Product Details

Applicable Parts

- [LT1505](#)

DC219A: Demo Board for the LT1505 Constant-Current/Voltage High Efficiency Battery Charger.

Documentation

[View All \(2\)](#) [Design & Integration Files \(1\)](#) [Demo Board Schematic \(1\)](#)

Design & Integration Files

[DC219A - Design File](#)
 ZIP
252.00K

Demo Board Schematic

[DC219A - Schematic](#)
 PDF
36.00K

SOCIAL



QUICK LINKS

About ADI
Analog Dialogue
Contact us
News Room
Sales & Distribution

Partners
Careers
Investor Relations
Quality & Reliability

LANGUAGES

English
简体中文
日本語
Русский

NEWSLETTERS

Interested in the latest news and articles about ADI products, design tools, training and events? Choose from one of our 12 newsletters that match your product area of interest, delivered monthly or quarterly to your inbox.

[Sign Up](#)