Catalog

myTDK About TDK ENGLISH

Tech Library

TDK Worldwide

Contact


Search by Part Number or Keywo Search

Environment



Chip NTC Thermistors (Sensor)

News



Application Guides Technical Support

Size	
Length(L)	1.00mm ±0.05mm
Width(W)	0.50mm ±0.05mm
Thickness(T)	0.50mm ±0.05mm
Terminal Width(B)	0.10mm Min.
Recommended Land Pattern (PA)	0.50mm ±0.10mm
Recommended Land Pattern (PB)	0.50mm ±0.10mm
Recommended Land Pattern (PC)	0.50mm ±0.10mm

Electrical Characteristics	
Resistance [at 25°C]	4.7kΩ
Resistance Tolerance	±3%
B value (Typ.) [25/50°C]	4067K
B value (Typ.) [25/85°C]	4100K
B value (Typ.) [25/100°C]	4110K
B value Tolerance	±3%
Max. Electric Power [at 25°C] ?	100mW
Permissive Operating Current [at 25°C] 2	460µA
Thermal Dissipation Constant [at 25°C] ?	1mW/°C 1mW/K

Other	
Max. Operating Temperature	125°C
Soldering Method	Reflow
UL File No.	E250289
AEC-Q200	No
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	10000pcs
Weight	0.0013g

- » Capacitors
- » Inductors (Coils)
- » EMC Components
- » RF Components and Modules

- » Voltage / Current / Temperature Protection Devices
- » Sensors and Sensor Systems
- » Ceramic Switching / Heating, Piezo Components,

Buzzers and Microphones

- » Ferrites and Accessories
- » Noise Suppressing / Magnetic Sheet

- » Anechoic Chambers and Radio Wave Absorbers
- » Power Supplies
- » Magnets
- » Flash Storages
- » Wireless Power Transfer
- » FA Systems
- » Transparent Conductive Film
- » Micro Modules (Substrates with Built-in ICs, Products Utilizing with SESUB)
- » Biosensor

Tech Library

Environment

Contact

News

Home

About TDK

TDK Worldwide

Terms of Use Privacy Policy

Copyright(c) 1996-2017 TDK Corporation. All rights reserved.

TDK logo is a trademark or registered trademark of TDK