

IRQ-12/12.5-W80NB-C

In Production

Recommended

New

RoHS

Appearance & Shape



Features

150W, 12Vo/12.5A, 16V-160Vin, Isolated DC-DC Converter,
Negative Logic, Meets requirements for EN50155

Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

IRQ-12/12.5-W80NB-C



Specifications

Output power (W)Max	150W
Vin(V)	16V to 160V
Vin(V)typ	72V
Vout(V)	12V
Vout(V)typ	12V
LineRegulation (%)	-0.5% to 0.5%
LoadRegulation (%)	-0.5% to 0.5%
Isolation Voltage (V)	4242V
Efficiency (%)	89%
Size(mm)W	39.62mm
Size(mm)L	61.21mm
Size(mm)T	13.0mm
Operatingtemperature(degC)	-40°C to 85°C
Outputs (#)	1
Iout(A)Max	12.5A
Form	1/4 Brick
Package	DIP
Productseries	IRQ-W80
Product Series Features	150W 10:1 Ultra Wide Input Encapsulated Quarter-Brick Isolated DC-DC Converter for Railway
Regulation	Regulated
Safety Approval	UL 60950-1, IEC/EN60950-1, 2nd Edition
Brand	Murata Power Solutions

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.