


CKCL22C0G1H471K085AA



TDK item description CKCL22C0G1H471KT****

Applications	Commercial Grade
Feature	2 in 1 Array
Series	CKCL22(2012) [EIA 0805]
Status	Obsolete Discontinue Issue Date : Apr.28, 2018 Last Purchase Order Date : Oct.31, 2018 Last Shipment Date : Mar.31, 2019



Size	
Length(L)	2.00mm ±0.15mm
Width(W)	1.25mm ±0.15mm
Thickness(T)	0.85mm ±0.15mm
Terminal Width(C)	0.45mm Nom.
Terminal Spacing(P)	1.00mm Nom.
Recommended Land Pattern (PA)	0.55mm to 0.65mm
Recommended Land Pattern (PB)	0.55mm to 0.65mm
Recommended Land Pattern (PC)	0.40mm to 0.50mm
Recommended Land Pattern (PP)	0.95mm to 1.05mm

Electrical Characteristics	
Capacitance	470pF ±10%
Rated Voltage	50VDC
Temperature Characteristic	C0G(0±30ppm/°C)
Q (Min.)	1000
Insulation Resistance (Min.)	10000MΩ






Other	
Soldering Method	Reflow
AEC-Q200	No
Packing	Blister (Plastic)Taping [180mm Reel]
Package Quantity	4000pcs

! Images are for reference only and show exemplary products.
 ! This PDF document was created based on the data listed on the TDK Corporation website.
 ! All specifications are subject to change without notice.

CKCL22C0G1H471K085AA




Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)



! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.



Associated Images



! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.