QE Series

SDHC Memory Card, Consumer Plus "SLC Lite" Model

Product Outline

QE series are SDHC memory cards adopting built-in consumer type MLC NAND flash memory using an SLC-like access mode. This enables higher endurance/data retention and power fail robustness than Panasonic Consumer Plus MLC model. They are formatted complying with SD card specification.

■ **Product Specification** (specifications and appearances are subject to be changed without notice.)

Appearance		4GB	8GB	16GB
		Panasonic Panasonic	Panasonic Panasonic	Panasonic Panasonic I I I I I I I I I I I I I
Part Number		RP-SDQE04DA1	RP-SDQE08DA1	RP-SDQE16DA1
Capacity	Available user data area capacity *1)	3,971,973,120 bytes	7,960,756,224 bytes	16,001,236,992 bytes
Compliant Specification	SD Physical Specification	Ver. 3.01		
	SD speed class	CLASS		
	UHS speed grade	I U		
	Speed mode	Default Speed mode, High Speed mode, UHS-I (SDR12, SDR25, DDR50, SDR50,SDR104)		
Backside mark	Control Code			
Read/Write Performance (up to)	Read	65MB/s (SDR104 mode)	65MB/s (SDR104 mode)	65MB/s (SDR104 mode)
	Write	65MB/s (SDR104 mode)	65MB/s (SDR104 mode)	65MB/s (SDR104 mode)
Absolute Maximum Ratings	Supply Voltage	Min : -0.3 V ; Max : +4.6 V		
	Input Voltage	Min : -0.3 V ; Max : VDD +0.3 V		
	Output Voltage	Min : -0.3 V ; Max : VDD +0.3 V		
	Output Current	Min : -24 mA ; Max : +24 mA		
Environmental Specification	Operating Temperature	-25 degree C to +85 degree C		
	Storage Temperature	-40 degree C to +85 degree C		
	Humidity	5 % RH to 95 % RH		
	Vibration	15 Gp-p		
	Shock	1,000 G		
	Mating Cycles	10,000 cycles		

*1) Free user area capacity after formatted.


Absolute Maximum Ratings are the values of limitation, which do not damage the card. So those values do not define the operational range.

Products comply with EU RoHS directives.

Panasonic

RP-SDQExxDA1

Marking Specification



System Reliability

- a. Error detect and corrective function
- b. Static wear leveling
- c. Bad block management

Notice and Caution

If you think about the usage for which special quality or reliability of the products is needed and failure or malfunction of the products may directly threaten life or injury for the special usage (aeronautic or cosmic usage, military usage, combustion machine, life support applications or safety applications), please counsel with our contacts in advance.

Write frequency and storage temperature will affect data retention time. Please make a backup for important data.

Warranty

If the product cannot be used because of failure which is determined as defect in design or in production of the product, it is replaced by same product or equivalent one within 12 months from the delivery date of product.