

Troduct Couron Butta Chick

Please download the latest datasheet of GRM188R72A682KA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=GRM188R72A682KA01%23

Note: This datasheet may be out of date.

"#" indicates a package specification code.

GRM188R72A682KA01#
















< List of part numbers with package codes > GRM188R72A682KA01D GRM188R72A682KA01J



Appearance & Shape







References

| Packaging | Specifications | Standard Packing Quantity |
|-----------|------------------|---------------------------------|
| D | 180mm Paper Tape | 4000 |
| J | 330mm Paper Tape | 10000 |

| Mass (typ.) | | |
|-------------|-------|--|
| 1 piece | 6.3mg | |
| φ180mm Reel | 144g | |

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



GRM188R72A682KA01#

Note: This datasheet may be out of date.

Please download the latest datasheet of GRM188R72A682KA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=GRM188R72A682KA01%23

"#" indicates a package specification code.



Specifications

| Length | 1.6±0.1mm |
|--|----------------|
| Width | 0.8±0.1mm |
| Thickness | 0.8±0.1mm |
| Capacitance | 6800pF ±10% |
| Distance between external terminals g | 0.5mm min. |
| External terminal size e | 0.2 to 0.5mm |
| Operating Temperature Range | -55°C to 125°C |
| Rated Voltage | 100Vdc |
| Size code in inch(mm) | 0603 (1608M) |
| Capacitance change rate | ±15.0% |
| Temperature characteristics (complied standard) | X7R(EIA) |
| Temperature range of temperature characteristics | -55°C to 125°C |

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

