


TDK MLCC Datasheet 1

TDK P/N C1005 COG 1H 1R8 B T XXXX 1) 2) 3) 4) 5) 6) 7)

No.	. Segment	Detail	Comments
1	Case Size	1.0 X 0.5 mm	See below for dimensions.
2	Temperature Characteristics	0 to +0 C & -30 to +30 ppm/C	Class1 Conforms to EIA 198
3	Rated Voltage	50.0 <i>v</i>	DC
4	Capacitance	2 pF	1.0 +/- 0.2 Vrms 1 Mhz +/- 10%
5	Capacitance Tolerance	0 to 0 %	Conforms to IEC 384-9
6	Packaging Style	Punched (Paper)Taping [180mm Reel]	EIA 481 Format
7	TDK internal Code	xxxx	(Internal TDK use only)
-	Q	436 min	0.5 - 5.0 Vrms 1 MHz +/- 10%
_	Insulation Resistance	11,674 <i>MOhm</i> min	Apply rated voltage for 60s

Physical Dimensions Symbol Dimensions

Symbol	Dimensions	
L	1	
W	0.5	
Т	0.5	
В	0.1 min	
G	0.3 min	



		Material	
No	Name	Class 1	Class 2
$ldsymbol{le}}}}}}}}}$		TME	TME
1	Dielectric	CaZr03	BaTi03
2	Electrode	Ni	Ni
3		Cu	Cu
4	Termination	Ni	
5		Sn	

¹ This datasheet is to be used for reference purposes only and is subject to change by TDK without notice. It reflects an overview of the product characteristics/performance for the particular part number. For product specification information, please refer to TDK's general product specification. Please note that this standard part is not designed or warranted to meet any specifications of any intermediate or end user different from or in addition to the specifications set fort in TDK's general product specification. Note also that this standard part has not been specially designed or manufactured for, nor is it intended or warranted for use in , or permitted to be resold for, specialized applications such as aviation, medical, and/or governmental/military applications (collectively, "Excluded Applications").



© TDK U.S.A. Corporation 2011. » Privacy Statement » Careers » Site Map TDK Logo is a trademark or registered trademark of TDK Corporation.