


Multilayer Ceramic Chip Capacitors C3225X7S1H475K230AE

RoHS Reach Halogen Free Pb Free

TDK item description C3225X7S1H475KT***S

Applications	Commercial Grade Please refer to Part No. <u>CGA6N3X7S1H475K230AE</u> for Automotive use.	
Feature	Soft Soft Termination	
Series	C3225 [EIA 1210]	
Status	Production	



Size		
Length(L)	3.20mm +0.50,-0.40mm	
Width(W)	2.50mm ±0.30mm	
Thickness(T)	2.30mm +0.30,-0.20mm	
Terminal Width(B)	0.20mm Min.	
Terminal Spacing(G)		
Recommended Land Pattern (PA)	2.00mm to 2.40mm	
Recommended Land Pattern (PB)	1.00mm to 1.20mm	
Recommended Land Pattern (PC)	1.90mm to 2.50mm	

Electrical Characteristics		
Capacitance	4.7μF ±10%	
Rated Voltage	50VDC	
Temperature Characteristic	X7S(±22%)	
Dissipation Factor (Max.)	5%	
Insulation Resistance (Min.)	106ΜΩ	

O ther		
Soldering Method	Reflow	
AEC-Q200	NO	
Packing	Embossed (Plastic)Taping [180mm Reel]	
Package Quantity	1000pcs	


 $^{!\ \}mbox{Images}$ are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.


[!] All specifications are subject to change without notice.





Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)














[!] Images are for reference only and show exemplary products.


[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

RoHS Reach Halogen Free Pb Free



Associated Images



 $^{!\ \}mbox{Images}$ are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.