Note: This datasheet may be out of date.

Please download the latest datasheet of NFA21SL317V1A48# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL317V1A48%23

"#" indicates a package specification code.

## NFA21SL317V1A48#








< List of part numbers with package codes > NFA21SL317V1A48B NFA21SL317V1A48L



### Appearance & Shape









### **Features**

- 1. Steep insertion loss characteristics
- 2. Suitable for noise suppression in 800MHz or higher frequency
- 3. Size: 2.0x1.25mm
- 4. 4 circuits in one package

Applications

Noise suppression for LCD line



### **Applications**

Other Usage For general



### Packaging Information

Packaging	Specifications	Standard Packing Quantity
В	Bulk(Bag)	1000
L	180mm Embossed Tape	4000

1 of 3

### Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL317V1A48%23

Please download the latest datasheet of NFA21SL317V1A48# from the official website of Murata

Note: This datasheet may be out of date.

"#" indicates a package specification code.

# NFA21SL317V1A48#



## **Specifications**

Shape	SMD	
Size Code (in inch)	0805	
Length	2.0mm	
Length Tolerance	±0.1mm	
Width	1.25mm	
Width Tolerance	±0.1mm	
Thickness	0.85mm	
Thickness Tolerance	±0.1mm	
Operating Temperature Range	-55°C to 125°C	
Mass(typ.)	0.012g	
Number of Circuit	4	
Rated Current	100mA	
Rated Voltage	10Vdc	
Withstanding Voltage	30Vdc	
Insulation Resistance(min.)	1000ΜΩ	
Insertion Loss	6dB max.(at Cut-off Frequency),20dB min.(at 800MHz),20dB min.(at 900MHz)	
Nominal Cut-off Frequency	310MHz	
Size Code (in mm)	2012	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date.


Please download the latest datasheet of NFA21SL317V1A48# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=NFA21SL317V1A48%23

"#" indicates a package specification code.

# NFA21SL317V1A48#








**Insertion Loss Characteristics** 

Insertion Loss Characteristics (Main Items)



**Equivalent Circuit** 

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.